

Nowodvorski
LIGHTING



Nowodvorski

LIGHTING


Tadeusz Nowodworski


Bartłomiej Nowodworski


Olga Krywult

NOWODVORSKI LIGHTING

Za każdą lampą Nowodvorski Lighting stoi historia pasji, dbałości o jakość i zamiłowania do nowatorskich rozwiązań.

Behind every Nowodvorski Lighting lamp lies a story of passion, commitment to quality, and a love for inventive solutions.


Borys Nowodworski


Tomasz Słabiak


Anna Bielnik


Aleksandra Kania-Biegus


Łukasz Jaworski


Agnieszka Solecka



Design Lab


Małgorzata Nowodworska

Naszą podróż rozpoczęliśmy w 1994 roku jako mała, rodzinna firma. Dziś, obecni na 45 rynkach świata, tworzymy oświetlenie dla domów, mieszkań i przestrzeni HORECA. Pomagamy piękniej żyć. Udowadniamy, że wyjątkowe wnętrza tworzy się światłem.

Our journey began in 1994 as a small family-owned company. Today, present in 45 markets worldwide, we create lighting for homes, apartments, and HORECA spaces. We inspire a more beautiful life, proving that exceptional interiors are shaped by light.

Sercem naszej marki jest dział rozwoju produktów – Design Lab. To tutaj rodzą się pomysły, które zespół projektantów i konstruktorów przekuwa w wyjątkowe kolekcje. Dopracowane wzornictwo, przemyślana funkcjonalność i pełne skupienie na użytkowniku sprawiają, że nasze oświetlenie wykracza poza utarte schematy. Tworzymy nie tylko lampy zdobiące wnętrza, ale przede wszystkim światło, które pisze codzienne scenariusze.

At the heart of our brand is the Design Lab – our product development department. This is where ideas are born and shaped into unique collections by our team of designers and engineers. Thoughtfully designed aesthetics, carefully considered functionality, and a strong focus on the user make our lighting stand out from the ordinary. We create not just lamps that decorate interiors but also light that sets the scene for everyday life.


Wojciech Paul


Wiktoria Morawska


Damian Olszak





Nasze oprawy powstają w dwóch zakładach produkcyjnych – w Częstochowie i Siemianowicach Śląskich. Każdego dnia ponad 300-osobowy zespół dba o to, by produkty, które trafią do Twojego wnętrza, wyróżniały się designem, precyzją wykonania i najwyższą jakością.
Możemy spełnić tę obietnicę dzięki 20 000 m² powierzchni produkcyjnej i magazynowej, obejmującej nowoczesny, zautomatyzowany park maszynowy, laboratorium fotometryczne oraz centrum logistyczne.

Our lighting fixtures are manufactured in two production facilities – in Częstochowa and Siemianowice Śląskie. Every day, our team of over 300 people ensures that the products reaching your interiors stand out with their design, precise craftsmanship, and top quality. We can fulfill this promise thanks to 20,000 m² of production and warehouse space, which includes a modern, automated machine park, a photometric laboratory, and a logistics center.



























Nasze lampy rozświetlą Twoje wnętrza i pomogą stworzyć wyjątkową atmosferę. Odwiedź Dom Marki Nowodvorski Lighting, nasze stoiska targowe i salony partnerskie – przekonaj się, jak łatwo możesz odmienić swoje otoczenie światłem.

Our lamps will brighten your interiors and help you create a unique atmosphere. Visit the Nowodvorski Lighting Brand Home, our trade fair stands, and partner showrooms to discover how easily you can transform your surroundings with light.

























COLLECTIONS


CIRCOLO LED 24-32


CIRCOLO POWER LED 25-26


LINEO LED 34

VERTIC LED 35

GIAVELLOTTO LED 37


BAR LED 40-41


MOTIVE LED 42

SABER LED 44-45


EASY LED 46


ARM LED 48


SLASH LED 49

SPIN LED 51


IMPULSE LED 52-53


VAN GOGH LED 54


ORTO 58-59


LASER 60-64


STALACTITE 65

LASER WALL 66-67


FOURTY 70-73


FOURTY WALL 74-75


FOURTY SPOTLIGHTS 76-77


MONO S 80-81


MONO SPOTLIGHTS 82-86

MONO CORNER 87


MONO LONG 88


MONO WALL 89


MONO SURFACE 90-91


MONO DEEP 92


MONO SLIDE 93


MONO FLOOR 94-95


MONO TABLE 95


EYE PENDANT 96-98


BATON 99

CYLINDER 100


EYE 101


EYE WALL 102


EYE FLEX 103


EYE SPOT 104-105


EYE SUPER 106-109


MORE EYE 110

MORE TONE 111

IMBRIA 112

SLING 113

KARO 116-117

SNOWBALL 120

KIER 121

PIK 122

GLOBE PLUS 123

SPHERE 124-125

PEAR 126-127

LUXORA LED 130-131

CRISTAL 132-133

HAMPTON 134

NEWPORT 135

CERAMIC LED 138-139

CLAY 141

POLARIS 142

AMALFI 143

MONACO 144-145

VETRO 146-147

SANTANA 150-153

AMARELA 154-157

CEDRO 160-163

LAGO 166-169

TUTOIA 171

POISE 172

TURDA 176-178

LAGUNA 179

CADILAC 180-181

MIST 182

FORM 183

CAMERON 184-185

VIVIANE 186

VIOLET 187

VIPER 188

FALCON 189

ALICE 190-191

HOTEL MOOD 192-194

Nowodvorski LIGHTING


HOTEL PLUS 196


MOSS 197


CHILIN 198


LUSSO 199


DROPS WOOD 202-205


SUNSET 208, 211


SUNSET NATURAL 209


SUNSET LED 210


SUNRISE LED 210


SUN LED 211


RING TIMBER LED 212


WHEEL 214


WHEEL LUX 214-215


RING WOOD LED 216


DISK 218

HEFT 219


KYMI 222


IKA 223


DOVER 226-227


MINIMAL 228


OSLO 228-229


RATTAN 230


PUKET 231


HAVANA 232-233


HAITI 234


BOHO 235


JAPANDI 236


KRABI 237


PUMPKIN 240-241


WAVE 242


NESS 242


LUKSOR 243


ABI 243


SIMONE 246


POINT DUO 248


ZENITH 252-254


SATELLITE 258-259


HERMANOS 260-261


ORBIT 263-265


PILLS 266-267

BERGEN 269

HAGA 269

MALMO 269

RING MIRROR LED 271

RING LED 272-273

COMMA LED 275

RADIUS 276-277

WORKSHOP 278

SILICONE 279

SPIDER 280

TWIG 281

CRATE 282

PLANT 283

TECHNO 284-285

HARMONY 284

PANTOGRAPH 286

CRAFT 287

HIGH-BAY 288

GARRET 289

HEMISPHERE RUST 290

HEMISPHERE SUPER 291,293

HEMISPHERE HIT 292

CANOE 294

EGG 295

ARES 296

GIOTTO LED 297

ORGANIC 298

IRIS LED 299

LIA LED 299

TUBE 299

STRAIGHT CEILING LED 300

STRAIGHT WALL 301

SOFT WALL LED 302

SOFT LED 303-304

ION LED 305

CL OFFICE LED PRO 306-307

MULTI LED 308

NIKKI ROUND LED 310

LID ROUND LED 313

LID SQUARE LED 314

ARENA 316

KASAI 317

SMART LED 319

Nowodvorski LIGHTING

DOWNLIGHTS



COBBLE 322



GAP 322



GROOVE 322-323



PAG 322



OVAL 323



MIDI LED 324-325



MIDI LED RECESSED 326



MINI LED RECESSED 329



FOCUS MINI LED 330



CL IOS LED 332- 333



HALO 334



POINT TONE 334



INDIA 335



FLEA 335



SET 336



EYE TONE 337-338



POINT PLEXI 339



BIT 339



POINT 339

SILBA 340

CRES 340



MURTER 340



MLJET 340



VIS 341



HVAR 341



SOLTA 341



SHINE 341



UNO 342



CUP 343



MYKONOS LED 344



EGINA LED 345



CL KOS LED 346



CL DIA LED 348



CL KEA LED 349



MOD 350



DOWNLIGHT ES111 351



EYE MOD 352



DOT 353

NANO LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 24V



NANO - LVM FOCUS OUT LED 360-361



NANO - LVM LINE OUT LED 362-363

NANO - LVM LINE IN LED 364

NANO - LVM FLEX LINE LED 365

NANO - LVM SPOT LED 366

NANO - LVM MUG LED 367

NANO - LVM SPOT ZOOM LED 368-369

NANO - LVM TRACKS AND ACCESSORIES 370-379

ULTRA THIN LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 48V

UT-LVM FOCUS LED 382-383

UT-LVM LINE LED 384-385

UT-LVM FOCUS OUT LED 386-387

UT-LVM FOCUS SWING LED 388-389

UT-LVM SPOT LED 390-392

UT-LVM ROLLER LED 393

UT-LVM TRACKS AND ACCESSORIES 394-397

Nowodvorski LIGHTING

LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 48V



LVM FOCUS 400-401
LED



LVM FOCUS 402-403
OUT LED



LVM LINE 404-405
LED



LVM SPOT 406-407
LED

LVM ROLLER 408
LED



LVM LID LED 410



LVM SLOT 411
LED



LVM TRACKS AND 414-423
ACCESSORIES

CTLS COMMERCIAL TRACK LIGHT SYSTEM



CTLS MILO 426-427
LED



CTLS NEA 428-430
LED



CTLS TINOS 432-433
LED



CTLS 434
SNOWBALL



CTLS MONO 435



CAMELEON 435
ADAPTER
CTLS



CTLS TRACKS 436-443
AND
ACCESSORIES

PROFILE TRACK LIGHT SYSTEM



PROFILE 446-447
TINOS LED



PROFILE 448-449
IRIS LED



PROFILE 450
MIKE



PROFILE 450
INDIA



PROFILE 450
FOCUS LED



PROFILE 451
ZOOM LED



PROFILE 452
EYE SUPER



PROFILE 452
SNOWBALL



PROFILE 453
BIT PLUS



PROFILE 453
BIT

PROFILE 453
EYE



PROFILE 454
EYE SPOT



PROFILE 454
MONO



PROFILE 454
PUCK



PROFILE 455
SNOWBALL



PROFILE 455
VESPA



CAMELEON 455
ADAPTER
PROFILE



PROFILE 456-463
TRACKS AND
ACCESSORIES

BATHROOM LIGHTING



ICE BALL 466



ALOE 466



ARALIA 467



AGAVE 467



NATALIE 469



ICE TUBE 470-471
LED



BRAZOS 472-473

SIMI 473

ICE EGG 474

SIS 475

CAYO 475

VISTA 476

Nowodvorski
LIGHTING


PAN LED 477


MALAKKA LED 477


TORCH 478


CEARA 478


PALMAS LED 479


BRAVO 480


PARANA 480


BOL 481

MAUN 481


ALPHA 481


FOXTROT 482-483


CHARLIE 484


DELTA 484


GOLF 485


ECHO 485


JULIET 486


HELIOS LED 486


ACRE 487


BAHIA 487

PIN LED 488

PICASSO LED 489

LATH LED 489


CEZANNE LED 491


AGNES ROUND LED PRO 492


AGNES SQUARE LED PRO 493

STONE 496

CUMULUS 498-499

FLOWERPOT 500

CUMULUS CUBE 502

STAR 503

PATIO 503

ZOLA LED 507


RUBY LED 508


TESSA LED 508


LIV LED 509


MIA LED 510


IDA 511


SLIT LED 512


SLIM LED 513


LHOTSE LED 513

STRUCTURE LED 514

SYMMETRY LED 515

TEPIC LED 516

MONTERREY LED 516

THIKA LED 517

POLE LED 518

ZURI LED 519

OTTAWA 520

SOUL 521

NORIN 522

HORN 522

TUBINGS 523

RIO 524-525

OIR 525

MEKONG 526

MISTRAL 527

PATHWAY LED 528-529

NEL LED 530

ORLA LED 531

ISLA LED 532

DEMI LED 533

ARIA LED 535

TRIANGLES LED 536

ELLIPSES LED 536

SEMI LED 537

MARGOT 538

LENS LED 539

ASSOS 540

PRIMM 540

ARRIS 541

NICO 541

FOG 542

NEGRO 543

OUTDOOR LIGHTING


EXE 543


ROCK PRO 544


SIERRA 544


HEXA 545


EDESA LED 545


QUARTZ 546


ORINOKO 546


CABO LED 547


UNIT LED 547


BRICK 547


OSCAR 548


KHUMBU 549


MUNO LED 549


PICNIC LED 550


AMY LED 552


NALA LED 554


MAHE LED 555


PUEBLA LED 556


MERIDA LED 556


PIX LED 557


OUTLINE LED 558


CLINE LED 560


ABBY LED 561


AVA LED 561


BAY LED 562


SIDEWALK SQUARE LED 563


SIDEWALK ROUND LED 563


BASALT 564


ASSAM 564


INA 564


STEP LED 565


OIA LED 565


BUSH 566


SPIKE LED 566


RUMI LED 567


PICCO LED 568


PAT LED 569


PAOLI 569


MON LED 569


CIRCLET LED 569

ANA 570

AMELIA 571

AMUR 572

TAY 572

LANTERN 573

TYBR 573

DON 573

NOOK 574

TAHOE 575

FESTOON LIGHTS 577

LIGHT SOURCES AND ACCESSORIES

BULB LED G9, 7W 580

BULB LED G9, 4W 580

BULB LENS LED, G9, 3W 580

REFLECTOR LED, GU10, R35, 4W 581

REFLECTOR LED, GU10, R50, 7W 581

REFLECTOR LED, GU10, R50, 7W, DIMMABLE 581

BULB GLASS BALL LED, E27, 8W 582

BULB LED E14, T25, 4W 582

BULB LED, GX53, 8W 582

REFLECTOR LENS LED, GU10, ES111, 9W 583

REFLECTOR DIFFUSER LED, GU10, ES111, 9W 583

BULB VINTAGE LED, E27, 6W 584

BULB VINTAGE LED, E27, 6W 584

BULB VINTAGE LED, E27, 6W 584

BULB VINTAGE LED, E27, 6W 584

BULB LED E14, C35, 6W 585

BULB LED E27, A60, 7W 585

BULB LED E27, A60, 10W 585

BULB LED, E27, A60, 2W, 5 PC SET 585



TUBE LED T8 586



WATERPROOF CONNECTOR IP68 687



WATERPROOF „Y" CONNECTOR IP 68 687



MICROWAVE SENSOR 587



48V DC POWER SUPPLY 588



24V DC POWER SUPPLY 588



HONEY COMB 589



ACROBAT 589



BALLERINA 589

Nasze produkty to efekt dbałości o jakość i zamiłowania do nowatorskich rozwiązań, a sposób ich prezentowania jest wizytówką naszej pracy. Wszystkie zdjęcia i wizualizacje zamieszczone w tym katalogu są starannie dostosowane wyłącznie do jego parametrów. Prosimy o niekorzystanie z nich bez naszej wiedzy i zgody. Jeśli potrzebujesz materiałów graficznych do innych potrzeb, skontaktuj się z nami pod adresem marketing@nowodvorski.com

Wszelkie prawa do dysponowania materiałami zamieszczonymi w katalogu i decydowania o sposobie ich wykorzystania przysługują Nowodvorski Lighting sp. z o.o.

Our products are the result of our commitment to quality and passion for inventive solutions, and the way they are presented is a showcase of our work. All photos and visualizations in this catalog have been carefully tailored exclusively to its specifications. Please do not use them without our knowledge and consent. If you need graphic materials for other purposes, please contact us at marketing@nowodvorski.com.

All rights to manage the materials included in this catalog and decide on their use belong to Nowodvorski Lighting sp. z o.o.

Catalogue 2025/2026



Collections

CIRCOLO LED S
10813







CIRCOLO LED
10814





CIRCOLO LED S

painted aluminum, painted steel, plastic PC

■ 10813 3000K ■ 10863 4000K

CIRCOLO LED M

painted aluminum, painted steel, plastic PC

■ 10812 3000K ■ 10862 4000K

■ 11403 3000K □ 11604 3000K

CIRCOLO LED

painted aluminum, painted steel, plastic PC

■ 10814 3000K ■ 10864 4000K

CIRCOLO POWER LED

painted aluminum, painted steel, plastic PC

□ 11646 3000K ■ 11647 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10813	18W LED	3000K	560 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10863	18W LED	4000K	600 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10812	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10862	21W LED	4000K	700 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11403	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11604	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10814	35W LED	3000K	1200 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10864	35W LED	4000K	1300 lm	70°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11646	67W LED	3000K	3700 lm	70°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11647	67W LED	3000K	3100 lm	70°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h

□ WHITE P004 RAL 9003 ■ SILK OLIVE P031 ■ BLACK P013 RAL 9005

□ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005



CIRCOLO LED
10867



CIRCOLO LED 10816



CIRCOLO POWER LED

painted aluminum, painted steel, plastic PC

11649 3000K 11648 3000K

CIRCOLO LED

painted aluminum, painted steel, plastic PC

10817 3000K 10867 4000K

11398 3000K 11602 3000K



CIRCOLO LED

painted aluminum, painted steel, plastic PC

10816 3000K 10866 4000K



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10817	45W LED	3000K	1600 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10867	45W LED	4000K	1800 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11398	45W LED	3000K	1600 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11602	45W LED	3000K	1600 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11648	85W LED	3000K	3750 lm	70 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11649	85W LED	3000K	4600 lm	70 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10816	33W LED	3000K	1100 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10866	33W LED	4000K	1200 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

WHITE P004 RAL 9003 SILK OLIVE P031 BLACK P013 RAL 9005

BLACK P013 RAL 9005



CIRCOLO LED M 11603



CIRCOLO LED M
10815



CIRCOLO LED S

painted aluminum, painted steel, plastic PC

10928 3000K 10930 4000K



CIRCOLO LED M

painted aluminum, painted steel, plastic PC

10815 3000K 10865 4000K

11402 3000K 11603 3000K





CIRCOLO LED XS
10858

CIRCOLO LED XS

painted aluminum, plastic PC

10808 3000K 10858 4000K

11601 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10808	9W LED	3000K	190 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10858	9W LED	4000K	200 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10928	18W LED	3000K	560 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10930	18W LED	4000K	600 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10815	21W LED	3000K	660 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10865	21W LED	4000K	700 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11402	21W LED	3000K	660 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11603	21W LED	3000K	660 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11601	9W LED	3000K	190 lm	70 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

SILK OLIVE P031 WHITE P004 RAL 9003 BLACK P013 RAL 9005

Nowodvorski LIGHTING

CIRCOLO LED S
10810

CIRCOLO LED M
10811

Visualisation by Iwona Ligęza



CIRCOLO LED S

painted aluminum, painted steel, plastic PC

10810 3000K 10860 4000K



CIRCOLO LED M

painted aluminum, painted steel, plastic PC

10811 3000K 10861 4000K

11401 3000K 11605 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10810	18W LED	3000K	560 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10860	18W LED	4000K	600 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10811	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10861	21W LED	4000K	700 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11401	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11605	21W LED	3000K	660 lm	70°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

BLACK P013 RAL 9005 SILK OLIVE P031 WHITE P004 RAL 9003

CIRCOLO LED M
11605

Visualisation by Iwona Ligęza



LINEO LED 11879



LINEO LED

painted aluminum, painted steel, plastic PMMA, plastic PC

■ 11879 □ 11885

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11879	39W LED	3000K	1500 lm	100°	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11885	39W LED	3000K	2100 lm	100°	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

■ BLACK P013 RAL 9005 □ WHITE P004 RAL 9003



VERTIC LED

painted aluminum, painted steel, plastic PMMA

■ 10362 3000K ■ 10857 4000K

□ 11606 3000K □ 11607 4000K



VERTIC LED 10362

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10362	19W LED	3000K	650 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10857	19W LED	4000K	700 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11606	19W LED	3000K	750 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11607	19W LED	4000K	800 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

□ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005

Nowodvorski LIGHTING



GIAVELLOTTO LED S 11886

GIAVELLOTTO LED S
11886





GIAVELLOTTO LED S

painted steel, painted aluminum, plastic PC

11886

GIAVELLOTTO LED M
11887





GIAVELLOTTO LED M

painted steel, painted aluminum, plastic PC

11887

GIAVELLOTTO LED L
11888





GIAVELLOTTO LED L

painted steel, painted aluminum, plastic PC

11888

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11886	18W LED	3000K	1400 lm	120°	~220-230 V, 50/60 Hz	>80	⏚	>0.9	IP20	30000h
11887	25W LED	3000K	2000 lm	120°	~220-230 V, 50/60 Hz	>80	⏚	>0.9	IP20	30000h
11888	35W LED	3000K	2900 lm	120°	~220-230 V, 50/60 Hz	>80	⏚	>0.9	IP20	30000h

BLACK P013 RAL 9005



Visualisation by Iwona Ligęza



BAR LED M
11400



BAR LED M

painted aluminum, painted steel, plastic PMMA

10364 3000K
10848 4000K
11581 3000K
11582 4000K
11400 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11583	27W LED	3000K	1700 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11584	27W LED	4000K	1800 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11581	32W LED	3000K	2000 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10363	27W LED	3000K	1200 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10847	27W LED	4000K	1300 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

WHITE P004 RAL 9003
BLACK P013 RAL 9005



BAR LED S

painted aluminum, painted steel, plastic PMMA

11583 3000K
11584 4000K
10363 3000K
10847 4000K



BAR LED L

painted aluminum, painted steel, plastic PMMA

10365 3000K
10850 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11582	32W LED	4000K	2100 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11400	32W LED	3000K	1600 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10364	32W LED	3000K	1600 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10848	32W LED	4000K	1800 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10365	40W LED	3000K	2200 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10850	40W LED	4000K	2300 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

WHITE P004 RAL 9003
SILK OLIVE P031
BLACK P013 RAL 9005

Nowodvorski LIGHTING



MOTIVE LED M

painted aluminum, plastic PC

■ 10311 3000K ■ 10852 4000K



MOTIVE LED L

painted aluminum, plastic PC

■ 10313 3000K ■ 10851 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10311	11W LED	3000K	380 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10852	11W LED	4000K	410 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10313	16W LED	3000K	540 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10851	16W LED	4000K	570 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

■ BLACK P013 RAL 9005

MOTIVE LED M 10311

MOTIVE LED L 10313



SABER LED M 10312



SABER LED M

painted aluminum, painted steel, plastic PC

10312 3000K 10853 4000K

11378 3000K 11380 4000K

11591 3000K 11592 4000K



SABER LED L

painted aluminum, painted steel, plastic PC

10314 3000K 10854 4000K

11381 3000K 11382 4000K

11588 3000K 11590 4000K

SABER LED L
11381



SABER LED L
11588

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10312	11W LED	3000K	380 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10853	11W LED	4000K	410 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11378	11W LED	3000K	380 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11380	11W LED	4000K	410 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11591	11W LED	3000K	460 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11592	11W LED	4000K	490 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

BLACK P013 RAL 9005 SILK OLIVE P031 WHITE P004 RAL 9003

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10314	16W LED	3000K	540 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10854	16W LED	4000K	570 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11381	16W LED	3000K	540 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11382	16W LED	4000K	570 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11588	16W LED	3000K	740 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
11590	16W LED	4000K	790 lm	100°	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

BLACK P013 RAL 9005 SILK OLIVE P031 WHITE P004 RAL 9003



EASY LED LEFT
11425



EASY LED RIGHT
11426



EASY LED LEFT

aluminum, painted steel, plastic PC

■ 11425 □ 11578

1x GU10 R35, max 10W only LED



EASY LED RIGHT

aluminum, painted steel, plastic PC

■ 11426 □ 11580

1x GU10 R35, max 10W only LED

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11425	11W LED	3000K	380 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11578	11W LED	3000K	450 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11426	11W LED	3000K	380 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11580	11W LED	3000K	450 lm	100°	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

□ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005





ARM LED L 10856



ARM LED M

painted aluminum, plastic PC

■ 10366 3000K ■ 10855 4000K



ARM LED L

painted aluminum, plastic PC

■ 10367 3000K ■ 10856 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10366	10W LED	3000K	360 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10855	10W LED	4000K	390 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10367	14W LED	3000K	520 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10856	14W LED	4000K	550 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

■ BLACK P013 RAL 9005



SLASH LED 11431



SLASH LED

painted aluminum, painted steel, plastic PC

■ 11431

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11431	10W LED	3000K	360 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

■ BLACK P013 RAL 9005

Nowodvorski LIGHTING



SPIN LED M 10370



SPIN LED S

painted aluminum, painted steel, plastic PC

10368 3000K 10620 4000K

11587 3000K



SPIN LED M

painted aluminum, painted steel, plastic PC

10370 3000K 10621 4000K

11586 3000K



SPIN LED L

painted aluminum, painted steel, plastic PC

10371 3000K 10622 4000K

11585 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10368	10W LED	3000K	360 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10620	10W LED	4000K	390 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10370	14W LED	3000K	520 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10621	14W LED	4000K	550 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10371	16W LED	3000K	600 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10622	16W LED	4000K	630 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11587	10W LED	3000K	400 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11586	14W LED	3000K	650 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11585	16W LED	3000K	750 lm	100 °	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

WHITE P004 RAL 9003 BLACK P013 RAL 9005

IMPULSE LED M 8116





IMPULSE LED M

painted aluminum, plastic PC

8116

IMPULSE LED L 8117





IMPULSE LED L

painted aluminum, plastic PC

8117



IMPULSE LED S 8115



IMPULSE LED S

painted aluminum, plastic PC

8115

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8115	6W LED	3000K	200 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP23	30000h
8116	10W LED	3000K	350 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP23	30000h
8117	15W LED	3000K	500 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP23	30000h

BLACK

BLACK

Nowodvorski LIGHTING



VAN GOGH LED S 10286



VAN GOGH LED S

painted aluminum, plastic PC

10289 10292 10286



VAN GOGH LED M

painted aluminum, plastic PC

10288 10291 10285



VAN GOGH LED L

painted aluminum, plastic PC

10287 10290 10284

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10289	9W LED	3000K	370 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10292	9W LED	3000K	430 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10286	9W LED	3000K	290 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10288	13W LED	3000K	490 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10291	13W LED	3000K	640 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10285	13W LED	3000K	430 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10287	18W LED	3000K	800 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10290	18W LED	3000K	940 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10284	18W LED	3000K	650 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

BLACK WHITE CHROME



VAN GOGH LED S 10286









ORTO B 11464



ORTO B 11465



ORTO

painted steel

11460 11461

8xE14, max 10W only LED

BULB LED E14, T25, 4W

11525 3000K



ORTO A

painted steel

11462 11463

12xE14, max 10W only LED

BULB LED E14, T25, 4W

11525 3000K



ORTO B

painted steel

11464 11465

12xE14, max 10W only LED

BULB LED E14, T25, 4W

11525 3000K

BLACK P013 RAL 9005 SILK GRAY P026 RAL 7044

Nowodvorski LIGHTING



LASER 490 10705





LASER 490

painted steel

8922 8923 10705

10xG9, max 10W only LED

solid brass, painted steel

8924

10xG9, max 10W only LED

LASER 490

painted steel

8918 8920 10704

7xG9, max 10W only LED

solid brass, painted steel

8921

7xG9, max 10W only LED



LASER 1000 7668



LASER 1000

painted steel

7667

7xG9, max 10W only LED

solid brass, painted steel

7668

7xG9, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS SATIN GOLD P023 SATIN COPPER P024 SATIN CHOCOLATE P025 RAL 8017

BLACK P013 RAL 9005 BRASS



LASER 490 10453

LASER 490
painted steel

10451 10452 10453

1xG9, max 10W only LED





LASER 490
painted steel

8796 8797

1xG9, max 10W only LED

solid brass, painted steel

8798

1xG9, max 10W only LED

LASER 490 8796

LASER 750 10447











LASER 750 8433



LASER 1000 10445

LASER 1000
painted steel

10444 10445 10446

1xG9, max 10W only LED

LASER 750
painted steel

10447 10448 10450

1xG9, max 10W only LED

LASER 750
painted steel

8432 8433

1xG9, max 10W only LED

solid brass, painted steel

8431

1xG9, max 10W only LED

LASER 1000
painted steel

8435 8436

1xG9, max 10W only LED

solid brass, painted steel

8434

1xG9, max 10W only LED



LASER 1000 8434

SATINE CHOCOLATE P025 RAL 8017 SATINE COPPER P024 SATINE GOLD P023

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS



LASER 750 10910



LASER 750

painted steel

10907 10910

1xG9, max 10W only LED



STALACTITE 9054



STALACTITE 8352



LASER 900 10915



LASER 900

painted steel

10913 10915

1xG9, max 10W only LED



STALACTITE

painted steel

8355

13xG9, max 10W only LED

solid brass, painted steel

9054

13xG9, max 10W only LED



STALACTITE

painted steel, flexible stem

8351

1xG9, max 10W only LED

solid brass, painted steel, flexible stem

8352

1xG9, max 10W only LED

BLACK P013 RAL 9005 SATINE GOLD P023

BLACK P013 RAL 9005 BRASS

LASER WALL L 11814





LASER WALL L

painted steel

11813 11812

11814 11815

2xG9, max 10W only LED



LASER WALL

painted steel

8048 8047 10562

10564 10563

2xG9, max 10W only LED

solid brass, painted steel

8308

2xG9, max 10W only LED



WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS SATINE GOLD P023 SATINE CHOCOLATE P025 RAL 8017 SATINE COPPER P024

Scan QR code to watch video manual on changing the bulb.





FOURTY
11447



FOURTY

painted aluminum, glass, painted steel

11447 11445

11450 11471

2xGU10 R35, 1xG9 max 10W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

BLACK P013 RAL 9005 WHITE P004 RAL 9003 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022



FOURTY
11448



FOURTY

painted aluminum, painted steel

11448 11446

11451 11472

5xGU10 R35, max 10W only LED

2xGU10 R50, 3xGU10 R35 max 10 W only LED

BLACK P013 RAL 9005 WHITE P004 RAL 9003 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022





FOURTY L 10896



FOURTY M 10886



FOURTY S 10734



FOURTY S

painted steel

10734 10735

10883 10884

1xGU10 R35, max 10W only LED

solid brass

10882

1xGU10 R35, max 10W only LED



FOURTY M

painted aluminum

10820 10821

10886 10887

1xGU10 R35, max 10W only LED

solid brass

10885

1xGU10 R35, max 10W only LED



FOURTY XL

painted aluminum

10824 10825

10898 10899

1xGU10 R35, max 10W only LED

solid brass

10897

1xGU10 R35, max 10W only LED



FOURTY L

painted aluminum

10822 10823

10895 10896

1xGU10 R35, max 10W only LED

solid brass

10894

1xGU10 R35, max 10W only LED



FOURTY S 10765

FOURTY M 10770



FOURTY S

painted steel

10764 10765

10900 10901

1xGU10 R35, max 10W only LED

solid brass, painted steel

10766

1xGU10 R35, max 10W only LED



FOURTY M

painted steel

10770 10771

10902 10903

1xGU10 R35, max 10W only LED

solid brass, painted steel

10772

1xGU10 R35, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022





FOURTY 11766

FOURTY

painted steel

11763 11764

11765 11766

1xGU10 R35, max 10W only LED





FOURTY WALL S 10746

FOURTY WALL S

painted steel

10746 10747

10888 10889

1xGU10 R35, max 10W only LED

solid brass, painted steel

10748

1xGU10 R35, max 10W only LED





FOURTY WALL M 10891

FOURTY WALL M

painted steel

10752 10753

10890 10891

2xGU10 R35, max 10W only LED

solid brass, painted steel

10754

2xGU10 R35, max 10W only LED



FOURTY WALL XL

painted steel

10758 10759

10892 10893

2xGU10 R35, max 10W only LED

solid brass, painted steel

10760

2xGU10 R35, max 10W only LED



FOURTY WALL XL 10759

Scan QR code to watch video manual how to change the bulb.

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022

FOURTY SURFACE
11442





FOURTY SURFACE

painted steel

11442 11443
11444 11473

2xGU10 R35, max 10W only LED

cut out 95 x 30 mm

FOURTY
10741





FOURTY

painted aluminum, painted steel

10741 11435
11440 11468

5xGU10 R35, max 10W only LED

FOURTY
10737





FOURTY

painted aluminum, painted steel

10737 11433
11437 11466

2xGU10 R35, max 10W only LED

FOURTY
10739





FOURTY

painted aluminum, painted steel

10739 11434
11438 11467

4xGU10 R35, max 10W only LED

FOURTY
10743





FOURTY

painted aluminum, painted steel

10743 11436
11441 11470

7xGU10 R35, max 10W only LED



Visualisation by Iwona Ligęza

3 warianty kolekcji MONO /
3 variants of the MONO collection



MONO





MONO SURFACE





MONO DEEP







Filtr przeciwolśnieniowy "plaster miodu".
Do zastosowania z kolekcją lamp MONO.

Anti-glare "honeycomb".
For use with the MONO lamp collection.

Scan QR code to watch video manual
on changing the bulb.

Nowodvorski LIGHTING

MONO S 10776

MONO S 10786

Visualisation by Iwona Ligęza



HONEY COMB 11427



MONO S 10777
HONEY COMB 11427



MONO S 10784
HONEY COMB 11427



MONO S 10779
HONEY COMB 11427



MONO S

painted steel

10776 10777 10778
10779 10781 10782
10783 10784 10785
10786

1xGU10 R50, max 10W only LED

solid brass

10780

1xGU10 R50, max 10W only LED

WHITE P004 RAL 9003 GOLD P021 BLACK P013 RAL 9005

BRASS SATINE COPPER P024 SATINE GOLD P023 SATINE CHOCOLATE P025 RAL 8017 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022

Nowodvorski LIGHTING

MONO 7807





MONO

painted steel, plastic ABS

7807 7838

7771 7763

1xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7778

1xGU10 R50, max 10W only LED

MONO 7810





MONO

painted steel, plastic ABS

7810 7841

7774 7766

2xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7782

2xGU10 R50, max 10W only LED



MONO 7811



MONO

painted steel, plastic ABS

7811 7842

7775 7767

3xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7783

3xGU10 R50, max 10W only LED



MONO 7812



MONO

painted steel, plastic ABS

7812 7843

7776 7768

4xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7784

4xGU10 R50, max 10W only LED

MONO CORNER 2X150
7721

MONO 7708

Visualisation by Iwona Ligęza

MONO

painted steel, plastic ABS

7813 7844

7777 7770

6xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7785

6xGU10 R50, max 10W only LED

MONO 7770



MONO 2X150

painted steel, plastic ABS

7750 7720

7694 7698

8xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7754

8xGU10 R50, max 10W only LED

MONO 2X150 7698





MONO 2X200 7701



MONO 2X200

painted steel, plastic ABS

7752 7722

7696 7701

8xGU10 R50, max 10W only LED

MONO CORNER 2X150 7700





MONO CORNER 2X150

painted steel, plastic ABS

7751 7721

7695 7700

8xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7755

8xGU10 R50, max 10W only LED

MONO CORNER 2X200 7702





MONO CORNER 2X200

painted steel, plastic ABS

7753 7723

7697 7702

8xGU10 R50, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS GOLD P021

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS GOLD P021



MONO LONG 7728



MONO LONG M

painted steel, plastic ABS

7725 7728

7671 7674

1xGU10 R50, max 10W only LED







MONO 7786

MONO

painted steel, plastic ABS

7787 7786

1xGU10 R50, max 10W only LED



MONO LONG 7730



MONO LONG

painted steel, plastic ABS

7726 7730

7672 7675

2xGU10 R50, max 10W only LED







MONO 7840

MONO

painted steel, plastic ABS

7808 7840

7772 7764

1xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7780

1xGU10 R50, max 10W only LED

MONO SURFACE 7833



MONO SURFACE

painted steel, plastic ABS

☐ 7827 ■ 7833

◪ 7683 ◪ 7688

1xGU10 R50, max 10W only LED

cut out ø 35 mm





MONO SURFACE 7834



MONO SURFACE

painted steel, painted aluminum, plastic ABS

☐ 7828 ■ 7834

2xGU10 R50, max 10W only LED

cut out 160×31 mm





MONO SURFACE 7635







MONO SURFACE

painted steel, painted aluminum, plastic ABS

☐ 7830 ■ 7835

3xGU10 R50, max 10W only LED

cut out 690×31 mm

MONO SURFACE 7836





MONO SURFACE

painted steel, painted aluminum, plastic ABS

☐ 7831 ■ 7836

4xGU10 R50, max 10W only LED

cut out 1170×31 mm

MONO SURFACE 7837





MONO SURFACE

painted steel, painted aluminum, plastic ABS

☐ 7832 ■ 7837

6xGU10 R50, max 10W only LED

cut out 1990×31 mm



MONO DEEP 10460





MONO DEEP

painted steel, plastic PC

☐ 10465 ■ 10460

2xGU10 R50, max 10W only LED

cut out 64×268 mm

MONO DEEP 10463







MONO DEEP

painted steel, plastic PC

☐ 10468 ■ 10463

6xGU10 R50, max 10W only LED

cut out 64×2002 mm



MONO SLIDE 10796



MONO SLIDE TRIMLESS 10803







MONO SLIDE

painted steel, plastic PA

☐ 10795 ◪ 10796 ◪ 10797
◪ 10798 ■ 10799 ◪ 10800
◪ 10801

1xGU10 R50, max 10W only LED

cut out ø 76 mm



MONO SLIDE TRIMLESS

painted steel, plastic PA, plastic ABS

☐ 10802 ◪ 10803 ◪ 10804
◪ 10805 ◪ 10806 ◪ 10807

1xGU10 R50, max 10W only LED

cut out ø 76 mm

WHITE P004 RAL 9003 BLACK P013 RAL 9005

WHITE P004 RAL 9003 BLACK P013 RAL 9005 GOLD P021 SATINE GOLD P023 SATINE CHOCOLATE P025 RAL 8017 SATINE COPPER P024

Nowodvorski LIGHTING



MONO 7712



MONO

painted steel, plastic ABS

7705 7708

7715 7718

2xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7712

2xGU10 R50, max 10W only LED



MONO 7710



MONO

painted steel, plastic ABS

7703 7706

7713 7716

1xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7710

1xGU10 R50, max 10W only LED



MONO 7711



MONO

painted steel, plastic ABS

7704 7707

7714 7717

1xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7711

1xGU10 R50, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS GOLD P021

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS GOLD P021



EYE M 5397

EYE L 6841

EYE L 8800



EYE M

painted steel

5397 6840

1xGU10 R50, max 10W only LED

solid brass, painted steel

8914

1xGU10 R50, max 10W only LED



EYE L

painted steel

5455 6841

1xGU10 R50, max 10W only LED

solid brass, painted steel

8800

1xGU10 R50, max 10W only LED



EYE 7863



EYE

painted steel

6481 7862

3xGU10 R50, max 10W only LED

solid brass, painted steel

7863

3xGU10 R50, max 10W only LED



EYE L 8916



EYE L
painted steel

8916 8917

3xGU10 R50, max 10W only LED

solid brass, painted steel

8915

3xGU10 R50, max 10W only LED

EYE L 8915



BATON 7852



BATON 7851



BATON
painted steel

7852

1xE27, max 10W only LED

solid brass, painted steel

7851

1xE27, max 10W only LED

BATON 7856



BATON
painted steel

7856

3xE27, max 10W only LED

solid brass, painted steel

7855

3xE27, max 10W only LED



CYLINDER M 7865

CYLINDER L 7864



CYLINDER M

glass, painted steel

7865

1xGU10 R50, max 10W only LED

glass, solid brass, painted steel

7868

1xGU10 R50, max 10W only LED



CYLINDER L

glass, painted steel

7864

1xGU10 R50, max 10W only LED

glass, solid brass, painted steel

7867

1xGU10 R50, max 10W only LED



EYE S

painted steel

5255 6836

1xGU10 R50, max 10W only LED

solid brass

8911

1xGU10 R50, max 10W only LED



EYE M

painted steel

5463 6837

1xGU10 R50, max 10W only LED

solid brass

8912

1xGU10 R50, max 10W only LED



EYE L

painted steel

5471 6838

1xGU10 R50, max 10W only LED

solid brass

8913

1xGU10 R50, max 10W only LED



EYE M 5463



EYE L 6838

TRANSPARENT BLACK P013 RAL 9005 BRASS

WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS

Nowodvorski LIGHTING



EYE 6842



EYE

painted steel

5654 6842

1xGU10 R50, max 10W only LED

EYE FLEX S

painted steel, flexible stem

9070 9068

1xGU10 R50, max 10W only LED

solid brass, flexible stem, painted steel

9067

1xGU10 R50, max 10W only LED





EYE FLEX S 9067



EYE WALL 8072



EYE WALL

painted steel

8073 8072

2xGU10 R50, max 10W only LED

solid brass, painted steel

8074

2xGU10 R50, max 10W only LED



EYE WALL CUT 7995



EYE WALL CUT

painted steel

7993 7994

2xGU10 R50, max 10W only LED

solid brass, painted steel

7995

2xGU10 R50, max 10W only LED

EYE FLEX 8935



EYE FLEX

painted steel, flexible stem

8934 8935

1xGU10 R50, max 10W only LED



WHITE P004 RAL 9003 BLACK P013 RAL 9005 BRASS

BRASS WHITE P004 RAL 9003 BLACK P013 RAL 9005

Nowodvorski LIGHTING



EYE SPOT 6018



EYE SPOT

painted steel, chrome

6014 6018

1xGU10 R50, max 10W only LED

solid brass, painted steel

8816

1xGU10 R50, max 10W only LED





EYE SPOT 6020

EYE SPOT

painted steel, chrome

6015 6020

2xGU10 R50, max 10W only LED

solid brass, painted steel

8817

2xGU10 R50, max 10W only LED



EYE SPOT 6021



EYE SPOT

painted steel, chrome

6016 6021

3xGU10 R50, max 10W only LED

solid brass, painted steel

8818

3xGU10 R50, max 10W only LED



EYE SPOT 6611



EYE SPOT

painted steel, chrome

6607 6611

6xGU10 R50, max 10W only LED

solid brass, painted steel

8819

6xGU10 R50, max 10W only LED



EYE SPOT 6022



EYE SPOT

painted steel, chrome

6017 6022

4xGU10 R50, max 10W only LED

solid brass, painted steel

8820

4xGU10 R50, max 10W only LED

EYE SUPER 6506





EYE SUPER

painted steel

6493 6506

1xGU10 R50, max 10W only LED



EYE SUPER B 6490



EYE SUPER A

painted steel

6488 6502

1xGU10 R50, max 10W only LED



EYE SUPER B

painted steel

6490 6503

1xGU10 R50, max 10W only LED



EYE SUPER 6501



EYE SUPER

painted steel, chrome

6487 6501

1xGU10 R50, max 10W only LED

EYE SUPER 6491









EYE SUPER

painted steel, chrome

6491 6504

3xGU10 R50, max 10W only LED

EYE SUPER 6505









EYE SUPER

painted steel, chrome

6492 6505

6xGU10 R50, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005

WHITE P004 RAL 9003 BLACK P013 RAL 9005



MORE EYE 7825



MORE TONE 7817









MORE EYE
painted steel

7822

4xGU10 R50, max 10W only LED

MORE EYE
painted steel

7825

5xGU10 R50, max 10W only LED

MORE TONE
painted steel, plastic ABS

7814

4xGU10 R50, max 10W only LED

MORE TONE
painted steel, plastic ABS

7817

5xGU10 R50, max 10W only LED

BLACK P013 RAL 9005

BLACK P013 RAL 9005 GOLD P021



IMBRAIA 9675



IMBRIA
painted steel, braided cable

9677

6xGU10, max 10W only LED



IMBRIA
painted steel, braided cable

9680

10xGU10 R50, max 10W only LED



IMBRIA
painted steel, braided cable

9192

4xGU10, max 10W only LED



IMBRIA
painted steel, braided cable

9675

6xGU10 R50, max 10W only LED



SLING 10355



SLING
glass, painted steel

10354

4xG9, max 12W only LED



SLING
glass, painted steel

10355

5xG9, max 12W only LED

BLACK P013 RAL 9005

BLACK P013 RAL 9005 WHITE



KARO 10304





KARO

painted steel, glass

10304

3xG9, max 12W only LED

BULB LED G9, 4W

☐ 7503 3000K ☐ 7504 4000K



KARO

painted steel, glass

10305

1xG9, max 12W only LED

BULB LED G9, 4W

☐ 7503 3000K ☐ 7504 4000K



KARO

painted steel, glass

10303

5xG9, max 12W only LED

BULB LED G9, 4W

☐ 7503 3000K ☐ 7504 4000K

KARO 10934





KARO

painted steel, glass

10934

8xG9, max 12W only LED

BULB LED G9, 4W

☐ 7503 3000K ☐ 7504 4000K

BLACK P013 RAL 9005 SATINE GOLD P023 WHITE

WHITE BLACK P013 RAL 9005 SATINE GOLD P023

Nowodvorski LIGHTING

SNOWBALL 11408

Visualisation by Iwona Ligęza

SNOWBALL
11408





SNOWBALL
painted steel, glass

11408

14xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

KIER M 10307



KIER L 10308



KIER S
painted steel, glass

10302 10623

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



KIER M
painted steel, glass

10307 10306

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



KIER L
painted steel, glass

10310 10308

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

BLACK P013 RAL 9005 WHITE

WHITE BLACK P013 RAL 9005 SATINE GOLD P023



PIK 10301



GLOBE PLUS S 7605

GLOBE PLUS M 7606



GLOBE PLUS 7607



PIK
painted aluminum, glass

10299

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



PIK
painted aluminum, glass

10300

2xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



PIK
painted aluminum, glass

10301

3xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

BLACK P013 RAL 9005 WHITE



GLOBE PLUS M
metallized glass, painted steel

7606

1xE27, max 25W only LED



GLOBE PLUS S
metallized glass, painted steel

7605

1xE27, max 25W only LED



GLOBE PLUS
metallized glass, painted steel

7607

3xE27, max 25W only LED

CHROME BLACK P013 RAL 9005

Nowodvorski LIGHTING

SPHERE S 7847

SPHERE M 7848

SPHERE L 7850

SPHERE XL 7846



SPHERE S

glass, painted steel

7847

1xG9, max 10W LED



SPHERE M

glass, painted steel

7848

1xE27, max 25W only LED



SPHERE L

glass, painted steel

7850

1xE27, max 25W only LED



SPHERE XL

glass, painted steel

7846

1xE27, max 25W only LED

SPHERE 7788





SPHERE

glass, painted steel

7788

3xE27, max 25W only LED

TRANSPARENT BLACK P013 RAL 9005

TRANSPARENT BLACK P013 RAL 9005

Nowodvorski LIGHTING



PEAR S 8673



PEAR S

glass, brass-plated steel, painted steel

8673

1xE27, max 25W only LED

glass, painted steel

7800

1xE27, max 25W only LED



PEAR M 8672



PEAR M

glass, brass-plated steel, painted steel

8672

1xE27, max 25W only LED

glass, painted steel

7798

1xE27, max 25W only LED



PEAR L 8671



PEAR L

glass, brass-plated steel, painted steel

8671

1xE27, max 25W only LED

glass, painted steel

7797

1xE27, max 25W only LED

PEAR 7794





PEAR

glass, brass-plated steel, painted steel

7794

3xE27, max 25W only LED

TRANSPARENT BRASS BLACK P013 RAL 9005

TRANSPARENT BRASS BLACK P013 RAL 9005



LUXORA LED
11705



LUXORA LED
11707











LUXORA LED
crystal, nickel

☐ 11705

LUXORA LED
crystal, nickel

☐ 11706

LUXORA LED
crystal, nickel

☐ 11708

LUXORA LED
crystal, nickel

☐ 11707

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11705	30W LED	3000K	2700 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11706	38W LED	3000K	3400 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11707	40W LED	3000K	3600 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11708	20W LED	3000K	1800 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h

☐ TRANSPARENT ▒ NICKEL

☐ TRANSPARENT ▒ NICKEL



CRISTAL M 7627



CRISTAL 7633



CRISTAL

crystal, painted steel

7633

2xE14, max 25W only LED



CRISTAL M

crystal, painted steel

7627

9xE14, max 25W only LED



CRISTAL M

crystal, painted steel

7616

9xE14, max 25W only LED



CRISTAL L

crystal, painted steel

7630

12xE14, max 25W only LED



CRISTAL L

crystal, painted steel

7614

12xE14, max 25W only LED

TRANSPARENT BLACK P013 RAL 9005

TRANSPARENT BLACK P013 RAL 9005

Nowodvorski LIGHTING



HAMPTON 8154



HAMPTON

chrome plated steel, glass

8154

6xE14, max 10W only LED



HAMPTON 8155



HAMPTON

chrome plated steel, glass

8155

2xE14, max 10W only LED



NEWPORT 8156



NEWPORT

glass, fabric, chrome plated steel

8157

1xE14, max 10W only LED



NEWPORT

glass, fabric, chrome plated steel

8156

6xE14, max 10W only LED

CHROME TRANSPARENT

WHITE CHROME

Nowodvorski LIGHTING



CERAMIC LED 11702





CERAMIC LED
glass, ceramic housing

11704



CERAMIC LED
glass, ceramic housing

11702



CERAMIC LED
glass, ceramic housing

11701

CERAMIC LED 11700





CERAMIC LED
glass, ceramic housing

11703



CERAMIC LED
glass, ceramic housing

11699



CERAMIC LED
glass, ceramic housing

11700

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11699	26W LED	3000K	2000 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11700	22W LED	3000K	1750 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11701	19W LED	3000K	1500 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11702	12W LED	3000K	950 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11703	8W LED	3000K	650 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h
11704	34W LED	3000K	2700 lm	360°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	25000h

GRAY BROWN WHITE

GRAY BROWN WHITE

Nowodvorski LIGHTING



CLAY M 11746



CLAY S 11750



CLAY S 11746

CLAY S 11750





CLAY S

ceramic housing, glass

11748 11750

1xG9, max 12W only LED

CLAY M

ceramic housing, glass

11746 11747

1xG9, max 12W only LED

WHITE GRAY BROWN

Nowodvorski LIGHTING



POLARIS 9058



POLARIS 9057



POLARIS 9056



POLARIS 9060

POLARIS

metallized glass, painted steel

9060

1xE27, max 25W only LED

POLARIS

metallized glass, painted steel

9056 9057 9058

1xE27, max 25W only LED



AMALFI 9154



AMALFI

metallized glass, steel, solid brass

9154 9155

1xE27, max 25W only LED



AMALFI L 8381



AMALFI M

metallized glass, steel, solid brass

9153 9152

1xE27, max 25W only LED



AMALFI L

metallized glass, steel, solid brass

8381

1xE27, max 25W only LED

SMOKED GOLD COPPER CHROME BLACK P013 RAL 9005

GOLD SILVER BLACK



MONACO 9363



MONACO

glass, braided cable, painted steel

9363

2xE27, max 25W only LED



MONACO

glass, painted steel

9362

2xE27, max 25W only LED

BLACK P013 RAL 9005 SMOKED



MONACO 9364



MONACO

glass, braided cable, painted steel

9364

1xE27, max 25W only LED



MONACO

painted steel, glass

8794

1xE27, max 25W only LED

BLACK P013 RAL 9005 SMOKED

Nowodvorski LIGHTING



VETRO 7641



VETRO 7642



VETRO 9131



VETRO

glass, painted steel

7641

3xE27, max 25W only LED



VETRO

glass, painted steel

7642

5xE27, max 25W only LED



VETRO

glass, painted steel

9132

1xE27, max 25W only LED



VETRO

glass, painted steel

9131

7xE27, max 25W only LED

SMOKED BLACK P013 RAL 9005

BLACK P013 RAL 9005 SMOKED





SANTANA S 11650



SANTANA M 11651



SANTANA M 11652



SANTANA S

fabric, painted steel, plastic

11650

1xE27, max 15W only LED



SANTANA M

fabric, painted steel, plastic

11651

1xE27, max 25W only LED



SANTANA M

fabric, painted steel, plastic

11652

1xE27, max 25W only LED



SANTANA L

fabric, painted steel, plastic

11653

1xE27, max 25W only LED

CREAM T032 GOLD

CREAM T032 GOLD

Nowodvorski LIGHTING



SANTANA A 11654



SANTANA A

fabric, painted steel

11654

1xE27, 1x GU10 R35 max 10W only LED



SANTANA B 11655



SANTANA B

fabric, painted steel

11655

2xG9, max 10W only LED



SANTANA

fabric, painted steel, plastic

11656

1xE27, max 25W only LED



SANTANA 11656

CREAM T032 SILK GRAY P026 RAL 7044 GOLD P035 RAL 2095

CREAM T032 GOLD P035 RAL 2095



AMARELA S 11657



AMARELA M 11658



AMARELA L 11660



AMARELA S

fabric, painted steel, plastic

11657

1xE27, max 15W only LED



AMARELA M

fabric, painted steel, plastic

11658

1xE27, max 25W only LED



AMARELA M

fabric, painted steel, plastic

11659

1xE27, max 25W only LED



AMARELA L

fabric, painted steel, plastic

11660

1xE27, max 25W only LED

BLACK MELANGE T033 SATINE CHOCOLATE

BLACK MELANGE T033 SATINE CHOCOLATE



AMARELA A 11661



AMARELA A

fabric, painted steel

11661

1xE27, 1x GU10 R35 max 10W only LED



AMARELA B 11662



AMARELA B

fabric, painted steel

11662

2xG9, max 10W only LED



AMARELA

fabric, painted steel, plastic

11663

1xE27, max 25W only LED



AMARELA 11663

BLACK MELANGE T033 SATINE CHOCOLATE P025 RAL 8017

BLACK MELANGE T033 SATINE CHOCOLATE P025 RAL 8017

CEDRO M 11665

AMY LED 11533

CEDRO B 11669

Visualisation by Iwona Ligęza



Ballerina included



CEDRO M 11665



CEDRO S 11670



CEDRO M 11671









CEDRO S
fabric, painted steel, plastic

11664

1xE27, max 15W only LED

CEDRO M
fabric, painted steel, plastic

11665

1xE27, max 25W only LED

CEDRO L
fabric, painted steel, plastic

11666

1xE27, max 25W only LED

CEDRO S
fabric, plastic

11670

2xE27, max 15W only LED

CEDRO M
fabric, plastic

11671

4xE27, max 15W only LED

CEDRO L
fabric, plastic

11672

7xE27, max 15W only LED

BEIGE T034 SILK GRAY

BEIGE T034

Nowodvorski LIGHTING



CEDRO A 11668



CEDRO A

fabric, painted steel

11668

1xE27, 1x GU10 R35 max 10W only LED



CEDRO B 11669



CEDRO B

fabric, painted steel

11669

2xG9, max 10W only LED



CEDRO

fabric, painted steel

11667

1xE27, max 25W only LED



CEDRO 11667

BEIGE T034 SILK GRAY P026 RAL 7044

BEIGET034 SILK GRAY P026 RAL 7044

Nowodvorski LIGHTING

LAGO L 11681

CEDRO S 11670

LAGO 11676

Visualisation by Iwona Ligęza



Acrobat included



LAGO S 11673



LAGO M 11674

LAGO M 11680



LAGO L 11681





LAGO S

fabric, painted steel, plastic

11673

1xE27, max 15W only LED



LAGO M

fabric, painted steel, plastic

11674

1xE27, max 25W only LED



LAGO L

fabric, painted steel, plastic

11675

1xE27, max 25W only LED



LAGO S

fabric, plastic

11679

2xE27, max 15W only LED



LAGO M

fabric, plastic

11680

4xE27, max 15W only LED



LAGO L

fabric, plastic

11681

7xE27, max 15W only LED

GRAY T035 UMBRA GRAY

GRAY T035



LAGO A 11677



LAGO A

fabric, painted steel

11677

1xE27, 1x GU10 R35 max 10W only LED



LAGO B 11678



LAGO B

fabric, painted steel

11678

2xG9, max 10W only LED



LAGO

fabric, painted steel

11676

1xE27, max 25W only LED



LAGO 11676



TUTOIA 11684



TUTOIA

fabric, painted steel

11684

1xE27, 1x GU10 R35 max 10W only LED



TUTOIA 11682

TUTOIA 11683





TUTOIA

fabric, painted steel

11683

1xE27, max 25W only LED



TUTOIA

fabric, painted steel, plastic

11682

1xE27, max 25W only LED

BEIGE T036

SILK GRAY P026 RAL 7044

Nowodvorski LIGHTING



POISE B 11430

Acrobat included





POISE A

fabric, painted steel, plastic

11686 11767 11768

1xE27, max 25W only LED

POISE B

fabric, painted steel, plastic

11430 11685

1xE27, max 25W only LED

NAVY BLUE T039 RED P033 RAL 3020 YELLOW P032 RAL 1021 BEIGE T034 GRAY T035 BLACK T011

BLACK P013 RAL 9005 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022

POISE A 11767

TURDA 8802

TURDA 8802

Visualisation by Iwona Ligęza



TURDA 8952



TURDA 8958



TURDA 8955



TURDA 8802



TURDA

fabric, plastic, painted steel

8945

3xE27, max 15W only LED



TURDA

fabric, plastic, painted steel

8952

3xE27, max 15W only LED



TURDA

fabric, plastic, painted steel

8958

7xE27, max 15W only LED



TURDA

fabric, plastic, painted steel

8950

3xE27, max 15W only LED



TURDA

fabric, plastic, painted steel

8955

4xE27, max 15W only LED



TURDA

fabric, plastic, painted steel

8802

7xE27, max 15W only LED

CREAM T023

GOLD T025



TURDA 8946



TURDA 8947



LAGUNA 8962



LAGUNA 8954



TURDA
fabric, plastic, painted steel

8946

3xE27, max 15W only LED



TURDA
fabric, plastic, painted steel

8947

3xE27, max 15W only LED



TURDA
fabric, plastic, painted steel

8953

3xE27, max 15W only LED



TURDA
fabric, plastic, painted steel

8960

7xE27, max 15W only LED



LAGUNA
velvet, plastic, painted steel

8954

3xE27, max 15W only LED



LAGUNA
velvet, plastic, painted steel

8957

4xE27, max 15W only LED



LAGUNA
velvet, plastic, painted steel

8962

9xE27, max 15W only LED

GRAY T024

CREAM T026

CADILAC 7988



CADILAC 8190



CADILAC 7991



CADILAC 8191





CADILAC

fabric, painted steel, plastic

7988 8190

3xE27, max 25W only LED

BLACK T011 CREAM T023 GRAY T024 BLACK P013 RAL 9005 WHITE P004 RAL 9003



CADILAC

fabric, painted steel

7991 8191

1xE27, max 25W only LED

GRAY T022 BLACK-GOLD T013 WHITE T004 WHITE P004 RAL 9003 BLACK P013 RAL 9005

Nowodvorski LIGHTING

MIST 8943

MIST 8944



MIST 8942



FORM M 9673



FORM L 9672



MIST
fabric, plastic, painted steel

8943

3xE27, max 15W only LED



MIST
fabric, plastic, painted steel

8944

7xE27, max 15W only LED



MIST
fabric, plastic, painted steel

8942

3xE27, max 15W only LED



FORM L
fabric, painted steel

9672

4xE27, max 25W only LED



FORM M
fabric, painted steel

9673

2xE27, max 25W only LED

WHITE T003

WHITE



CAMERON 9606



CAMERON 9605



CAMERON 9687



CAMERON 9682



CAMERON

fabric, plastic, painted steel

9605

2xE27, max 15W only LED



CAMERON

fabric, plastic, painted steel

9606

4xE27, max 15W only LED



CAMERON

fabric, plastic, painted steel

9682

4xE27, max 15W only LED



CAMERON

fabric, plastic, painted steel

9687

2xE27, max 15W only LED

WHITE T005

GRAY T008



VIVIANE 6772



VIVIANE 6773



VIVIANE 6390



VIOLET 7958



VIOLET 7960



VIOLET 7961



VIVIANE

fabric, glass, chrome

6772 6773 6774

3xE27, max 25W only LED



VIVIANE

fabric, glass, chrome

6391 6532 6390

3xE27, max 25W only LED



VIOLET

fabric, plastic, painted steel

7958 7960 7961

3xE27, max 25W only LED

WHITE T004 GRAY T022 BLACK T012

WHITE T004 GRAY T022 BLACK T012



VIPER 6640



VIPER

fabric, painted steel

6640 6641

1xE27, max 25W only LED





VIPER 6513

VIPER

fabric, painted steel, chrome

6512 6513

1xE14, max 10W only LED



FALCON 7950



FALCON

fabric, plastic, painted steel

7951 7950

6xE27, max 25W only LED



ALICE 9091



ALICE

fabric, painted steel

9091

1xE27, max 10W only LED

ALICE 4963







ALICE L

fabric, painted steel

4961

1xE27, max 25W only LED



ALICE

fabric, painted steel

9084

1xE27, max 10W only LED

ALICE L

painted steel, fabric

4963

1xE27, max 25W only LED

BLACK-GOLD T013 BLACK P013 RAL 9005

BLACK P013 RAL 9005 BLACK-GOLD T013

Nowodvorski LIGHTING



HOTEL MOOD 11788



HOTEL MOOD

fabric, chrome plated steel

11781 11788

1xE14, max 10W only LED



HOTEL MOOD

fabric, chrome plated steel

11780 11787

1xE27, max 25W only LED



HOTEL MOOD 11787



HOTEL MOOD LED
11793



HOTEL MOOD LED

fabric, chrome plated steel

11785 11793

1xE27, max 25W only LED, 1x2.2W LED



HOTEL MOOD

fabric, chrome plated steel

11784 11792

2xE27, max 25W only LED



HOTEL MOOD 11792

CREAM T037 GRAY T038 CHROME

CREAM T037 GRAY T038 CHROME



HOTEL MOOD
11783



HOTEL MOOD
11778



HOTEL MOOD
11782



HOTEL MOOD

fabric, chrome plated steel, plastic

11783 11791

1xE27, max 25W only LED



HOTEL MOOD

fabric, painted steel

11778 11786

1xE27, max 10W only LED



HOTEL MOOD

fabric, painted steel, plastic

11782 11790

1xE27, max 25W only LED

GRAY T038 CREAM T037 CHROME

HOTEL MOOD 11791

HOTEL PLUS
9071





HOTEL PLUS

fabric, painted steel, flexible stem

9071

1xE27, max 25W only LED, 1xG9, max 10W only LED



HOTEL PLUS
9072



HOTEL PLUS

fabric, painted steel, flexible stem

9072

1xE27, max 25W only LED, 1xG9, max 10W only LED



MOSS 9737



MOSS

fabric, plywood, painted steel

9736

3xE27, max 25W only LED



MOSS

fabric, painted steel

9737

3xE27, max 25W only LED

GRAY T022 BLACK P013 RAL 9005

BLACK T012 BLACK P013 RAL 9005

CHILLIN 8197



CHILLIN 8213



CHILLIN 8201











CHILLIN

fabric, painted steel, flexible stem

8216

1xE27, max 10W only LED, 1xG9, max 10W only LED

fabric, painted steel, solid brass, flexible stem

8213

1xE27, max 10W only LED, 1xG9, max 10W only LED

CHILLIN

fabric, painted steel

8201 8197

1xE27, max 10W only LED



LUSSO 11521



LUSSO

fabric, painted steel

11520 11521

1xE27, 1x GU10 R35 max 10W only LED

WHITE T004 GREEN-GOLD T029 BLACK-GOLD T013 BRASS WHITE P004 RAL 9003 BLACK P013 RAL 9005

WHITE P004 RAL 9003 WHITE T004 BLACK P013 RAL 9005 BLACK T011

Nowodvorski LIGHTING





DROPS WOOD C
11175

DROPS WOOD C
plywood, painted steel

11175

1xE27, max 25W only LED





DROPS WOOD E
plywood, painted steel

11177

1xE27, max 25W only LED



DROPS WOOD E
11177

DROPS WOOD F
11180



DROPS WOOD D
plywood, painted steel

11176

1xE27, max 25W only LED



DROPS WOOD F
plywood, painted steel

11180

1xE27, max 25W only LED

DARK WOOD
BLACK P013 RAL 9005

BLACK P013 RAL 9005
GOLD



DROPS WOOD A
11173

DROPS WOOD B
11174



DROPS WOOD A

plywood, glass, painted steel

11173

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

DROPS WOOD A
11173

DROPS WOOD B

plywood, glass, painted steel

11174

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K

WHITE NATURAL WOOD BLACK P013 RAL 9005

Nowodvorski LIGHTING

SUNSET B
7655

SUNSET C
7654

Visualisation by Iwona Ligęza



SUNSET C 7654



SUNSET C

plywood, painted steel

7654

2xGX53, max 12W only LED



SUNSET NATURAL B

plywood, painted steel

10577

2xGX53, max 12W only LED



SUNSET NATURAL B
10577



SUNSET B 7655



SUNSET B

plywood, painted steel

7655

2xGX53, max 12W only LED



SUNSET NATURAL C

plywood, painted steel

10578

2xGX53, max 12W only LED



SUNSET NATURAL C
10578



SUNSET A 7653



SUNSET A

plywood, painted steel

7653

2xGX53, max 12W only LED



SUNSET NATURAL A

plywood, painted steel

10576

2xGX53, max 12W only LED



SUNSET NATURAL A
10576

DARK WOOD BLACK P013 RAL 9005

NATURAL WOOD BLACK P013 RAL 9005



SUNSET LED D
11432



SUNSET LED D

plywood, painted aluminum, painted steel

11432



SUN LED 7651



SUN LED

plywood, painted steel

7651



SUNRISE LED
7652



SUNRISE LED

plywood, painted steel

7652



SUNSET 7647



SUNSET

plywood, painted steel

7647

2xGX53, max 12W only LED

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
7652	14W LED	3000K	340 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
11432	7W LED	3000K	65 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h

DARK WOOD BLACK P013 RAL 9005

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
7651	15W LED	3000K	610 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h

DARK WOOD BLACK P013 RAL 9005 GOLD



RING TIMBER LED M
11290



RING TIMBER LED XXL

plywood, painted aluminum, painted steel

11178



RING TIMBER LED XL

plywood, painted aluminum, painted steel

11292



RING TIMBER LED L

plywood, painted steel

11291





RING TIMBER LED S

plywood, painted steel

11288



RING TIMBER LED M

plywood, painted steel

11290



RING TIMBER LED XXL 11178

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11288	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11290	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11291	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11292	16W LED	3000K	290 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
11178	22W LED	3000K	400 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

DARK WOOD



WHEEL 9028



WHEEL

plywood, painted steel

9028 9033

1xE27, max 10W only LED





WHEEL LUX 7646



WHEEL LUX 8430



WHEEL LUX

plywood, painted steel

8430

1xG9, max 10W only LED

WHEEL LUX

plywood, painted steel

7646

2xGX53, max 12W only LED

GOLD BLACK P013 RAL 9005

GOLD BLACK P013 RAL 9005



RING WOOD LED M
10281



RING WOOD LED L

plywood, painted steel

10282



RING WOOD LED S

plywood, painted steel

10280



RING WOOD LED M

plywood, painted steel

10281

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10280	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10281	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10282	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

GOLD

RING WOOD LED M
10281

RING WOOD LED S
10280



DISK 7644



HEFT 10356







DISK
painted steel, plywood

7644

3xGX53, max 12W only LED

DISK
painted steel, plywood

7645

1xGX53, max 12W only LED

HEFT
painted steel, plywood

10356

2xGX53, max 12W only LED

BLACK P013 RAL 9005 DARK WOOD

BLACK P013 RAL 9005 DARK WOOD

KYMI B 10571

KYMI A 10570

Visualisation by Iwona Ligęza

KYMI A 10573





KYMI C

plywood, painted steel, braided cable

10572 10575

1xE27, max 25W only LED



IKA A 4171



IKA D 4174



KYMI B 10571



KYMI A

plywood, painted steel, braided cable

10570 10573

1xE27, max 25W only LED



KYMI B

plywood, painted steel, braided cable

10571 10574

1xE27, max 25W only LED



IKA A

plywood, painted steel

4171

1xE27, max 25W only LED



IKA D

plywood, painted steel

4174

1xE27, max 25W only LED

NATURAL WOOD BLACK P013 RAL 9005 WHITE P004 RAL 9003

NATURAL WOOD

Nowodvorski LIGHTING

DOVER 9263

DOVER 9263





DOVER

plywood, braided cable, painted steel

9264

1xGU10 R50, max 10W only LED



DOVER

plywood, braided cable, painted steel

9263

2xGU10 R50, max 10W only LED

DOVER 9261



DOVER 9266





DOVER

plywood, painted steel

9261 9266

1xGU10 R50, max 10W only LED

BLACK P013 RAL 9005 BRASS

NATURAL WOOD BLACK P013 RAL 9005 WHITE P004 RAL 9003

MINIMAL 9377





MINIMAL

wood, painted steel

9377

1xG9, max 10W only LED

OSLO 30 9700





OSLO 30

wood, painted steel

9700

1xE14, max 15W only LED



OSLO LED 7522



OSLO LED 90

wood, painted steel

7522 7520

1xLED TUBE T8, max 16W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	LED driver	Lifetime	Material
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	INCL	30000h	CLEAR GLASS

OAK WHITE P004 RAL 9003

OAK SMOKED OAK WHITE P004 RAL 9003

Nowodvorski LIGHTING



RATTAN M
11154



RATTAN S
11153



PUKET M
11161



PUKET L
11162



RATTAN L
rattan, painted steel

11155

1xE27, max 25W only LED

RATTAN M
rattan, painted steel

11154

1xE27, max 25W only LED

RATTAN S
rattan, painted steel

11153

1xE27, max 25W only LED

PUKET L
bamboo, painted steel

11162

1xE27, max 25W only LED

PUKET M
bamboo, painted steel

11161

1xE27, max 25W only LED

PUKET S
bamboo, painted steel

11160

1xE27, max 25W only LED

NATURAL WOOD WHITE P004 RAL 9003

NATURAL WOOD WHITE P004 RAL 9003



HAVANA S 11170



HAVANA M
11396



HAVANA S
bamboo, painted steel, plastic ABS

11170

1xE27, max 25W only LED



HAVANA M
bamboo, painted steel, plastic ABS

11171

1xE27, max 25W only LED



HAVANA L
bamboo, painted steel, plastic ABS

11172

1xE27, max 25W only LED



HAVANA S
bamboo, painted steel

11395

1xE27, max 25W only LED



HAVANA M
bamboo, painted steel

11396

1xE27, max 25W only LED



HAVANA L
bamboo, painted steel

11397

1xE27, max 25W only LED

NATURAL WOOD WHITE P003 RAL 9003

NATURAL WOOD WHITE P004 RAL 9003



HAITI S
11166



HAITI L
11168



BOHO S
11150



HAITI S

bamboo, painted steel

11163 11166

1xE27, max 25W only LED



HAITI M

bamboo, painted steel

11164 11167

1xE27, max 25W only LED



HAITI L

bamboo, painted steel

11165 11168

1xE27, max 25W only LED



BOHO S

rattan, painted steel

11150

1xE27, max 25W only LED



BOHO M

rattan, painted steel

11151

1xE27, max 25W only LED



BOHO L

rattan, painted steel

11152

1xE27, max 25W only LED

NATURAL WOOD WHITE P004 RAL 9003 BLACK P013 RAL 9005

NATURAL WOOD WHITE P004 RAL 9003

Nowodvorski LIGHTING





JAPANDI S

paper rope, painted steel

11156

1xE27, max 25W only LED



JAPANDI M

paper rope, painted steel

11157

1xE27, max 25W only LED





KRABI

bamboo, painted steel

11158

1xE27, max 25W only LED

NATURAL WOOD WHITE P004 RAL 9003

NATURAL WOOD WHITE P004 RAL 9003

Nowodvorski LIGHTING



PUMPKIN S
11496



PUMPKIN S
11242



PUMPKIN L
11252





PUMPKIN S

painted steel

11242 11243 11496

1xGU10 R50, max 10W only LED



PUMPKIN M

painted steel

11244 11245 11495

1xGU10 R50, max 10W only LED



PUMPKIN L

painted steel

11251 11252 11494

1xGU10 R50, max 10W only LED

SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022 TERRACOTTA P028

TERRACOTTA P028 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022



WAVE S 8858



WAVE S

painted steel

8858

1xE27, max 25W only LED



LUKSOR S

painted steel

8851

1xE27, max 25W only LED



LUKSOR S 8851



NESS 6768



NESS

painted steel

6768

1xE27, max 25W only LED



ABI L

painted steel, fabric

8864

1xE27, max 25W only LED



ABI L 8864

BLACK P013 RAL 9005

BLACK P013 RAL 9005

Nowodvorski LIGHTING





SIMONE
11412



SIMONE
11413



SIMONE
11414



SIMONE

painted steel

11410 11411 11412
11413 11414

1xGX53, max 12W only LED

BLACK P013 RAL 9005 WHITE P004 RAL 9003 TERRACOTTA P028 SAGE GREEN P029 UMBRA BLUE P030

SIMONE 11413



POINT DUO 11510

POINT DUO 11513

POINT DUO 11511

POINT DUO 11512



POINT DUO

painted steel, plastic ABS

11510 11511

11512 11513

1xGU10 R50, max 10W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 GOLD P021 SILK GRAY P026 RAL 7044





Visualisation by Iwona Ligęza



ZENITH XS 11456



ZENITH M
11486



ZENITH L
11482



ZENITH XS

painted steel

11452 11453 11454
11455 11456 11492
11493

1xGU10 R50, max 10W only LED
GU10 R35, max 10W only LED



ZENITH S

painted steel

10880 10881 11491
11488 11490

1xGU10, max 10W only LED
1xGU10 ES111, max 20W only LED



ZENITH M

painted steel

10878 10879 11487
11485 11486

1xGU10, max 10W only LED
1xGU10 ES111, max 20W only LED



ZENITH L

painted steel

10872 10873 11484
11482 11483

1xGU10, max 10W only LED
1xGU10 ES111, max 20W only LED

BLACK P013 RAL 9005 · WHITE P004 RAL 9003 · UMBRA GRAY P027 RAL 7022 · SILK GRAY P026 RAL 7044 · TERRACOTTA P028
SAGE GREEN P029 · UMBRA BLUE P030

SILK GRAY P026 RAL 7044 · UMBRA GRAY P027 RAL 7022 · SAGE GREEN P029 · UMBRA BLUE P030 · TERRACOTTA P028

Nowodvorski LIGHTING





ZENITH L

painted steel, solid brass

8005 8006 8007

1xGU10, max 10W only LED

1xGU10 ES111, max 20W only LED



ZENITH M

painted steel, solid brass

8001 8002 8003

1xGU10, max 10W only LED

1xGU10 ES111, max 20W only LED



ZENITH S

painted steel, solid brass

7996 7997 7998

1xGU10, max 10W only LED

1xGU10 ES111, max 20W only LED

BLACK P013 RAL 9005 WHITE P004 RAL 9003 GREEN P022 BRASS

SATELLITE M
11232

Visualisation by Iwona Ligęza



SATELLITE M
11232



SATELLITE S

painted steel, plastic

11225 11228

11226 11227

3xE27, max 25W only LED



SATELLITE M

painted steel, plastic

11230 11233

11231 11232

7xE27, max 25W only LED



SATELLITE M 8018



SATELLITE S SENSOR
8011



SATELLITE S

painted steel, plastic

8013 8012

8014 8015

3xE27, max 25W only LED



SATELLITE M

painted steel, plastic

8017 8016

8018 8020

7xE27, max 25W only LED



SATELLITE S SENSOR

painted steel, plastic

8011 8010

3xE27, max 25W only LED



SATELLITE L

painted steel, plastic

8022 8021

8023 8024

10xE27, max 25W only LED

BLACK P013 RAL 9005 SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022 WHITE P004 RAL 9003

SILK GRAY P026 RAL 7044 UMBRA GRAY P027 RAL 7022 BLACK P013 RAL 9005 WHITE P004 RAL 9003



HERMANOS C 8192



HERMANOS C

painted steel, solid brass

8194

1xGU10 R50, max 10W only LED

painted steel

8192

1xGU10 R50, max 10W only LED



HERMANOS B 8102



HERMANOS B

painted steel, solid brass

8100

1xGU10 R50, max 10W only LED

painted steel

8102

1xGU10 R50, max 10W only LED



HERMANOS A 8105



HERMANOS A

painted steel, solid brass

8103

1xGU10 R50, max 10W only LED

painted steel

8105

1xGU10 R50, max 10W only LED

HERMANOS

painted steel, solid brass

8030

3xGU10 R50, max 10W only LED

painted steel

10905

3xGU10 R50, max 10W only LED





HERMANOS 8032



HERMANOS

painted steel, solid brass

8032

5xGU10 R50, max 10W only LED

painted steel

10906

5xGU10 R50, max 10W only LED

BLACK P013 RAL 9005 BRASS

BLACK P013 RAL 9005 BRASS

Nowodvorski LIGHTING



Visualisation by Iwona Ligęza





ORBIT
painted steel

7941 7945

4xGX53, max 12W only LED



ORBIT
painted steel

7942 7946

6xGX53, max 12W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005

Nowodvorski LIGHTING



ORBIT 7938



ORBIT

painted steel

☐ 7938 ■ 7943

2xGX53, max 12W only LED



ORBIT 7805





ORBIT

painted steel

☐ 7802 ■ 7805

1xGX53, max 12W only LED

ORBIT 7806





ORBIT

painted steel

☐ 7803 ■ 7806

1xGX53, max 12W only LED



ORBIT

painted steel

☐ 7801 ■ 7804

2xGX53, max 12W only LED



ORBIT

painted steel

☐ 10637 ■ 10638

2xGX53, max 12W only LED

☐ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005

☐ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005

Nowodvorski LIGHTING



PILLS 8265



PILLS

painted aluminum, painted steel

■ 8265

1xGX53, max 12W only LED



PILLS 8263



PILLS

painted aluminum, painted steel

□ 8268 ■ 8263

3xGX53, max 12W only LED



PILLS 8266



PILLS

painted aluminum, painted steel

■ 8266

1xGX53, max 12W only LED



PILLS 8262



PILLS 8264



PILLS

painted aluminum, painted steel

□ 8270 ■ 8264

2xGX53, max 12W only LED



PILLS

painted aluminum, painted steel

□ 8267 ■ 8262

5xGX53, max 12W only LED



MALMO 10457

BERGEN 10455



HAGA 10456



HAGA

aluminum

10456

2xG9, max 10W only LED

painted steel

9708 9710

2xG9, max 10W only LED



BERGEN

aluminum

10455

2xGU10 R50, max 10W only LED

painted steel

9706 9707

2xGU10 R50, max 10W only LED



MALMO

aluminum

10457

2xGU10 R50, max 10W only LED

painted steel

9705

2xGU10 R50, max 10W only LED

GRAPHITE P010 RAL 7016 WHITE P004 RAL 9003 BLACK P013 RAL 9005 GOLD

Nowodvorski LIGHTING

RING MIRROR LED L
10278

RING MIRROR LED M
10277



RING MIRROR LED S 10276



RING MIRROR LED L

glass, painted steel

10278





RING MIRROR LED S

glass, painted steel

10276



RING MIRROR LED M

glass, painted steel

10277

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10276	7W LED	3000K	30 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10277	10W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10278	13W LED	3000K	90 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

MIRROR



RING LED S 7634



RING LED S 7637



RING LED S 10317



RING LED S 10315



RING LED S
painted steel

7634 7637

RING LED M
painted steel

7635 7638

RING LED L
painted steel

7636 7640

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
7634	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
7637	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
7635	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
7638	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
7636	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h
7640	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	IP20	30000h

WHITE P004 RAL 9003 BLACK P013 RAL 9005

RING LED S
painted steel

10315 10316 10317

RING LED M
painted steel

10352 10347 10350

RING LED L
painted steel

10353 10348 10351

Item No.	Power	Colour temp.	Luminous flux	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10315	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10316	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10317	7W LED	3000K	60 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10347	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10350	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10352	10W LED	3000K	130 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10348	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10351	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
10353	13W LED	3000K	160 lm	>90	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

SATINE CHOCOLATE P025 SATINE COPPER P024 SATINE GOLD P023



COMMA LED M 11877



COMMA LED S

painted steel, plastic PC

■ 11876 □ 11884

COMMA LED M

painted steel, plastic PC

■ 11877 □ 11883

COMMA LED L

painted steel, plastic PC

■ 11878 □ 11882

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11876	19W LED	3000K	500 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11884	19W LED	3000K	850 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11877	25W LED	3000K	650 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11883	25W LED	3000K	1200 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11878	34W LED	3000K	950 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
11882	34W LED	3000K	1650 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h

WHITE P004 RAL 9003 BLACK P013 RAL 9005



RADIUS 7762



RADIUS
painted steel

7762

1xE27, max 25W only LED



RADIUS 7932



RADIUS
painted steel

7931

4xE27, max 25W only LED



RADIUS
painted steel

7932

6xE27, max 25W only LED

BLACK P013 RAL 9005

BLACK P013 RAL 9005



WORKSHOP B 6336



WORKSHOP A 6337



WORKSHOP

painted steel, copper-clad steel

6605

1xE27, max 25W only LED



WORKSHOP B

painted steel, copper-clad steel

6336

1xE27, max 25W only LED



WORKSHOP A

painted steel, copper-clad steel

6337

1xE27, max 25W only LED



SILICONE 6403



SILICONE 6404



SILICONE

silicone, painted steel

6404 6403

1xE27, max 25W only LED

BLACK P013 RAL 9005 COPPER

WHITE BLACK GRAY

Nowodvorski LIGHTING



SPIDER 6785



SPIDER

braided cable, painted steel

■ 6792

1xE27, max 25W only LED

SPIDER

braided cable, painted steel

□ 9744 ■ 6788

5xE27, max 25W only LED



SPIDER

braided cable, painted steel

□ 9743 ■ 6785

7xE27, max 25W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005



TWIG 9138



TWIG

painted steel

■ 9138

6xE27, max 25W only LED



TWIG

painted steel

■ 9140

4xE27, max 25W only LED

BLACK P013 RAL 9005

Nowodvorski LIGHTING



CRATE 9046



CRATE 9045



CRATE 9047



PLANT 9381



PLANT 9382



CRATE
painted steel

■ 9046

1xE27, max 25W only LED



CRATE
painted steel

■ 9045

1xE27, max 25W only LED



CRATE
painted steel

■ 9047

5xE27, max 25W only LED



PLANT
painted steel, steel

□ 9382 ■ 9381

4xGU10 R50, max 10W only LED

■ BLACK P013 RAL 9005

■ BLACK P013 RAL 9005 □ WHITE P004 RAL 9003

TECHNO 9145





TECHNO

painted steel

9145

1xE27, max 25W only LED



TECHNO 9142



HARMONY 9890



HARMONY

painted steel, chrome

9890

1xE27, max 25W only LED



TECHNO

painted steel

9142

3xE27, max 25W only LED

BLACK P013 RAL 9005 WHITE P001 RAL 9003

BLACK P013 RAL 9005 WHITE P001 RAL 9003

Nowodvorski LIGHTING



PANTOGRAPH 9126











PANTOGRAPH 9126

PANTOGRAPH
painted steel

9126

1xE27, max 25W only LED

BLACK P013 RAL 9005 WHITE P001 RAL 9003



CRAFT 9150

CRAFT 9151





CRAFT
painted steel

9151

1xE27, max 25W only LED



CRAFT
painted steel

9150

3xE27, max 25W only LED

BLACK P013 RAL 9005 WHITE P001 RAL 9003

Nowodvorski LIGHTING

HIGH-BAY 5067





HIGH-BAY
painted steel

5067

1xE27, max 25W only LED

GARRET 6442





GARRET
painted steel

6442

1xE27, max 25W only LED

GARRET M 6444





GARRET S
painted steel

6443

1xE27, max 25W only LED



GARRET M
painted steel

6444

1xE27, max 25W only LED

BLACK P013 RAL 9005 WHITE P001 RAL 9003

CHOCOLATE P015 COPPER P020



HEMISPHERE RUST L
6368



HEMISPHERE SUPER S
10618



HEMISPHERE RUST S

painted steel

6367

1xE27, max 25W only LED



HEMISPHERE RUST L

painted steel

6368

1xE27, max 25W only LED



HEMISPHERE SUPER L

painted steel, braided cable

10296

4xGX53, max 12W only LED



HEMISPHERE SUPER S

painted steel, braided cable

10618

1xGX53, max 12W only LED

RUST EFFECT

SATINE CHOCOLATE PO25 RAL 8017

Nowodvorski LIGHTING



HEMISPHERE HIT L 10703



HEMISPHERE SUPER S
10701

HEMISPHERE SUPER L
10696



HEMISPHERE HIT S

painted steel

10702

1xE27, max 25W only LED



HEMISPHERE HIT L

painted steel

10703

1xE27, max 25W only LED



HEMISPHERE SUPER S

painted steel, braided cable

10695 10701

1xGX53, max 12W only LED



HEMISPHERE SUPER L

painted steel, braided cable

10696 10700

4xGX53, max 12W only LED

BLACK P013 RAL 9005 SATINE GOLD P023

SATINE GOLD P023 WHITE P001 RAL 9003



CANOE 7927



CANOE

composite, painted steel, steel

7926 7927

5xE27, max 25W only LED



EGG L 9023



EGG M

composite, painted steel

9022 9021

1xE27, max 25W only LED



EGG XL 9026



EGG L

composite, painted steel, steel

9024 9023

5xE27, max 25W only LED



EGG XL

composite, painted steel, steel

9026 9025

7xE27, max 25W only LED

BLACK P014 RAL 9005 WHITE P003 RAL 9003 GOLD P018

WHITE P003 RAL 9003 BLACK P014 RAL 9005 GOLD P018



ARES 206



GIOTTO LED M 8170







ARES
painted steel

203

2xE14, max 10W only LED

ARES
painted steel

205

5xE14, max 10W only LED

ARES
painted steel

206

10xE14, max 10W only LED



GIOTTO LED S
brass plated steel

8168



GIOTTO LED M
brass plated steel

8170

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8168	9W LED	3000K	600 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
8170	13W LED	3000K	900 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

BLACK WITH A GOLDEN PATINA

ANTIQUE BRASS



ORGANIC 8304



ORGANIC 8305



ORGANIC 8302



ORGANIC 8303





ORGANIC

painted steel

☐ 8304 ■ 8302

3xGX53, max 12W





ORGANIC

painted steel

☐ 8305 ■ 8303

1xGX53, max 12W



IRIS LED

painted aluminum, plastic

☐ 8993 ■ 8994



IRIS LED 8993



LIA LED

painted aluminum

☐ 6913



LIA LED 6913



TUBE

painted aluminum

☐ 9317 ■ 9320

2xGU10 ES111, max 15W only LED



TUBE 9317

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8993	7W LED	3000K	550 lm	30°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
8994	7W LED	3000K	530 lm	30°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
6913	7W LED	3000K	460 lm	89°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	10000h

☐ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005

☐ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005



STRAIGHT CEILING LED L 7551



STRAIGHT CEILING LED M 7558



STRAIGHT CEILING LED S 7597



STRAIGHT WALL LED M 7561



STRAIGHT WALL LED S 7568



STRAIGHT WALL XS 7601



STRAIGHT CEILING LED L

painted steel, plastic PMMA

7551 7556 7600

1xLED TUBE T8, max 22W, included



STRAIGHT CEILING LED M

painted steel, plastic PMMA

7553 7558 7598

1xLED TUBE T8, max 16W, included



STRAIGHT CEILING LED S

painted steel, plastic PMMA

7552 7557 7597

1xLED TUBE T8, max 11W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS

GRAPHITE P010 RAL 7016 WHITE P004 RAL 9003 BLACK P013 RAL 9005



STRAIGHT WALL XS

painted steel, plastic PMMA

6345 6350 7601

1xE14, max 10W only LED



STRAIGHT WALL LED S

painted steel, plastic PMMA

7568 7562 7596

1xLED TUBE T8, max 11W, included



STRAIGHT WALL LED M

painted steel, plastic PMMA

7567 7561 7594

1xLED TUBE T8, max 16W, included



STRAIGHT WALL LED L

painted steel, plastic PMMA

7566 7560 7595

1xLED TUBE T8, max 22W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120°	≥80	~220-230 V, 50/60 Hz	›0,5	30000h	CLEAR GLASS

WHITE P004 RAL 9003 GRAPHITE P010 RAL 7016 BLACK P013 RAL 9005

SOFT WALL LED 60X6 7528





SOFT WALL LED 60X6

painted aluminum, plastic PMMA

7541 7528

1xLED TUBE T8, max 11W, included



SOFT LED 90X6 7535



SOFT LED 90X6

painted aluminum, plastic PMMA

7547 7535

1xLED TUBE T8, max 16W, included

SOFT WALL LED 90X6 7534





SOFT WALL LED 90X6

painted aluminum, plastic PMMA

7548 7534

1xLED TUBE T8, max 16W, included



SOFT LED 120X6 7525



SOFT LED 120X6

painted aluminum, plastic PMMA

7537 7525

1xLED TUBE T8, max 22W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS

WHITE P004 RAL 9003 GRAPHITE P010 RAL 7016

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120 °	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS

WHITE P004 RAL 9003 GRAPHITE P010 RAL 7016

SOFT CEILING LED 60X6 7527





SOFT CEILING LED 60X6

painted aluminum, plastic PMMA

7540 7527

1xLED TUBE T8, max 11W, included

SOFT CEILING LED 60X20 7526





SOFT CEILING LED 60X20

painted aluminum, plastic PMMA

7538 7526

2xLED TUBE T8, max 11W, included

ION LED M 8171





ION LED M

glass, chrome plated steel

8171

SOFT CEILING LED 90X6 7533





SOFT CEILING LED 90X6

painted aluminum, plastic PMMA

7546 7533

1xLED TUBE T8, max 16W, included

SOFT CEILING LED 90X20 7531





SOFT CEILING LED 90X20

painted aluminum, plastic PMMA

7542 7531

2xLED TUBE T8, max 16W, included

ION LED L 8172



SOFT CEILING LED 120X6 7524





SOFT CEILING LED 120X6

painted aluminum, plastic PMMA

7536 7524

1xLED TUBE T8, max 22W, included

SOFT CEILING LED 60X60 7530





SOFT CEILING LED 60X60

painted aluminum, plastic PMMA

7544 7530

5xLED TUBE T8, max 11W, included



ION LED L

glass, chrome plated steel

8172

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8171	12W LED	3000K	870 lm	130°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h
8172	18W LED	3000K	1300 lm	130°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	30000h

WHITE P004 RAL 9003 GRAPHITE P010 RAL 7016

CHROME

Nowodvorski LIGHTING



CL OFFICE LED PRO 120
10212



CL OFFICE LED PRO 120

painted aluminum, plastic PMMA

■ 10208 3000K ■ 10210 4000K

□ 10212 4000K







CL OFFICE PRO/HALL PRO SUSPENSION KIT

steel, painted steel

□ 8291 ■ 8250

CL OFFICE PRO/ HALL PRO POWER SUPPLY KIT

painted steel

□ 8290 ■ 8288

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	LED brand	Driver brand	Ingress protection	Lifetime	Warranty
10212	31W LED	4000K	4160 lm	90°	≥ 80	~220-230 V, 50/60 Hz	PHILIPS	PHILIPS	IP20	50000h	5 YEARS
10208	31W LED	3000K	3490 lm	90°	≥ 80	~220-230 V, 50/60 Hz	PHILIPS	PHILIPS	IP20	50000h	5 YEARS
10210	31W LED	4000K	3610 lm	90°	≥ 80	~220-230 V, 50/60 Hz	PHILIPS	PHILIPS	IP20	50000h	5 YEARS

□ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005



CL OFFICE LED PRO 150
10213



CL OFFICE LED PRO 150

chrome plated aluminum, plastic PMMA

■ 10213 3000K ■ 10214 4000K







CL OFFICE PRO/HALL PRO SUSPENSION KIT

steel, painted steel

■ 8250

CL OFFICE PRO/ HALL PRO POWER SUPPLY KIT

painted steel

■ 8288

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	LED brand	Driver brand	Ingress protection	Lifetime	Warranty
10213	40W LED	3000K	4540 lm	83°	≥ 80	~220-230 V, 50/60 Hz	PHILIPS	PHILIPS	IP20	50000h	5 YEARS
10214	40W LED	4000K	4710 lm	83°	≥ 80	~220-230 V, 50/60 Hz	PHILIPS	PHILIPS	IP20	50000h	5 YEARS

■ BLACK P013 RAL 9005

Nowodvorski LIGHTING

MULTI LED 11357



MULTI LED

plastic, aluminium

☐ 11357

MULTI LED 11358



MULTI LED

plastic, aluminium

☐ 11358

Sposoby montażu / Installation methods

1. Natynkowy
1. Surface-mounted



2. Podtynkowy
2. Flush-mounted









Możliwość zmiany mocy oprawy oświetleniowej (W)
Selectable luminaire wattage (W)



11358 - 18W



11358 - 24W



11358 - 30W

Możliwość zmiany temperatury barwowej (K)
Selectable colour temperature (K)



11358 - 6000K



11358 - 4000K



11358 - 3000K

Możliwość wyboru temperatury barwowej (K) oraz mocy (W)
Selectable colour temperature (K) and wattage (W)



Możliwość wyboru temperatury barwowej (K) oraz mocy (W)
Selectable colour temperature (K) and wattage (W)



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11357	9W/12W/18W LED	CCT CHANGE 3000-6000K	900/1200/1600 lm	110°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
11358	18W/24W/30W LED	CCT CHANGE 3000-6000K	1800/2400/2900 lm	110°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

☐ WHITE



NIKKI ROUND LED 48W
11207







NIKKI ROUND LED
painted steel, plastic PMMA

☐ 11200 3000K ☐ 11203 4000K
■ 11206 3000K ■ 11210 4000K

NIKKI ROUND LED
painted steel, plastic PMMA

☐ 11201 3000K ☐ 11204 4000K
■ 11207 3000K ■ 11211 4000K

NIKKI ROUND LED
painted steel, plastic PMMA

☐ 11202 3000K ☐ 11205 4000K
■ 11208 3000K ■ 11212 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
11200	32W LED	3000K	2700 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11201	48W LED	3000K	4200 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11202	60W LED	3000K	5400 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11203	32W LED	4000K	2800 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11204	48W LED	4000K	4300 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11205	60W LED	4000K	5600 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11206	32W LED	3000K	2600 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11207	48W LED	3000K	4000 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11208	60W LED	3000K	5200 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11210	32W LED	4000K	2700 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11211	48W LED	4000K	4200 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h
11212	60W LED	4000K	5400 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	IP20	40000h

☐ WHITE ■ BLACK



NIKKI ROUND LED 60W 11202



LID ROUND LED 10408



LID ROUND LED 15W

plastic

☐ 10402 3000K ☐ 10411 4000K

■ 10406 3000K ■ 10415 4000K



LID ROUND LED 35W

plastic

☐ 10404 3000K ☐ 10413 4000K

■ 10408 3000K ■ 10417 4000K



LID ROUND LED 25W

plastic

☐ 10403 3000K ☐ 10412 4000K

■ 10407 3000K ■ 10416 4000K



LID ROUND LED 50W

plastic

■ 10410 3000K ■ 10418 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10402	15W LED	3000K	1500 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10411	15W LED	4000K	1600 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10406	15W LED	3000K	1200 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10415	15W LED	4000K	1300 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10403	25W LED	3000K	1900 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10412	25W LED	4000K	2100 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10407	25W LED	3000K	1600 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10416	25W LED	4000K	1800 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10404	35W LED	3000K	3100 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10413	35W LED	4000K	3400 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10408	35W LED	3000K	2700 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10417	35W LED	4000K	3000 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10410	50W LED	3000K	4300 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10418	50W LED	4000K	4500 lm	120°	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

☐ WHITE ■ BLACK



LID SQUARE LED 15W

plastic

☐ 10420 3000K ☐ 10428 4000K

■ 10424 3000K



LID SQUARE LED 25W

plastic

☐ 10421 3000K ☐ 10430 4000K



LID SQUARE LED 35W

plastic

☐ 10422 3000K ☐ 10431 4000K

■ 10426 3000K



LID SQUARE LED 50W

plastic

☐ 10423 3000K ☐ 10432 4000K

■ 10427 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10420	15W LED	3000K	1500 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10428	15W LED	4000K	1600 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10424	15W LED	3000K	1200 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.7	IP20	30000h
10421	25W LED	3000K	1900 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10430	25W LED	4000K	2100 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10422	35W LED	3000K	3100 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10431	35W LED	4000K	3400 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10426	35W LED	3000K	2700 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10423	50W LED	3000K	4600 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10432	50W LED	4000K	5000 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10427	50W LED	3000K	4300 lm	120 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h



LID SQUARE LED 10421

☐ WHITE ■ BLACK

ARENA LED 10176





ARENA LED

painted steel, plastic PMMA

☐ 10185 ■ 10176



KASAI 9490



KASAI 7952



ARENA SENSOR

painted steel, plastic PMMA

☐ 10186 ■ 10177

3xE14, max 10W only LED



ARENA

painted steel, plastic PMMA

☐ 10184 ■ 10175

3xE14, max 10W only LED



KASAI

chrome plated steel, glass

9490

2xE27, max 10W only LED

brushed stainless steel, glass

9491

2xE27, max 10W only LED

painted steel, glass

■ 7952

2xE27, max 10W only LED

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10185	20W LED	4000K	2200 lm	100 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	50000h
10176	20W LED	4000K	2200 lm	100 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	50000h

☐ WHITE P004 RAL 9003 ■ BLACK P013 RAL 9005

☐ WHITE ■ BLACK CHROME SATINE SILVER



SMART LED 8358







SMART LED 8358

- Możliwość wyboru temperatury barwowej światła w przedziałach 3000K - 6000K
- Włącznik dotykowy z funkcją ściemniania
- Port USB umożliwiające ładowanie telefonu

- Possibility to choose the colour temperature of light in the range from 3000K to 6000K
- Touch switch with dimming function
- USB port for charging mobile phones



SMART LED

painted aluminum, plastic ABS

8358

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8358	8W LED	CCT CHANGE 3000-6000K	400 lm	120°	≥ 80	~220-230 V, 50/60 Hz		>0.5	IP20	25000h

BLACK

Downlights

COBBLE 7791

COBBLE 7790





COBBLE

painted aluminum

7791 7790

1xGU10 ES111, max 15 only LED

GROOVE 7793

GROOVE 7792





GROOVE

painted aluminum

7793 7792

1xGU10 ES111, max 15W only LED



GROOVE 9383



GROOVE 9316

OVAL 9241



OVAL 9240

GAP 9385

GAP 9384





GAP

painted aluminum

9385 9384

2xGU10 R50, max 10W only LED

PAG 9387





PAG

painted aluminum

9387

2xGU10, max 10W only LED



GROOVE

painted aluminum

9383 9316

2xGU10 ES111, max 15W only LED



OVAL

painted aluminum

9241 9240

2xGU10 ES111, max 15W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005

WHITE P004 RAL 9003 BLACK P013 RAL 9005



MIDI LED 10048



MIDI LED

painted aluminum

10048 3000K
10052 4000K
10055 3000K
10058 4000K



MIDI LED 10060



MIDI LED

painted aluminum

10050 3000K
10053 4000K
10056 3000K
10060 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10048	20W LED	3000K	1700 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10052	20W LED	4000K	1700 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10055	20W LED	3000K	1700 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10050	40W LED	3000K	3500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10053	40W LED	4000K	3500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10056	40W LED	3000K	3500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10058	20W LED	4000K	1700 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10060	40W LED	4000K	3500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

WHITE BLACK



MIDI LED 10051



MIDI LED 10054



MIDI LED

painted aluminum

10054 3000K
10057 4000K
10047 3000K
10051 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10047	16W LED	3000K	1500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10051	16W LED	4000K	1500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10054	16W LED	3000K	1500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10057	16W LED	4000K	1500 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h

WHITE BLACK

Nowodvorski LIGHTING



MIDI LED RECESSED
10064



MIDI LED RECESSED

painted aluminum

■ 10064 4000K

cut out 85×85 mm

MIDI LED RECESSED
10062





MIDI LED RECESSED
10063



MIDI LED RECESSED

painted aluminum

■ 10062 3000K ■ 10065 4000K

cut out 200×45 mm

MIDI LED RECESSED

painted aluminum

■ 10063 3000K

cut out 390×45 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10064	16W LED	4000K	1400 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10062	20W LED	3000K	1800 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10065	20W LED	4000K	1800 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.5	IP20	30000h
10063	40W LED	3000K	3300 lm	36 °	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

■ BLACK

MIDI LED RECESSED
10063





MINI LED RECESSED
10043



MINI LED RECESSED

painted aluminum

10042 3000K 10043 4000K

cut out 140×35 mm



MINI LED RECESSED
10045



MINI LED RECESSED

painted aluminum

10045 3000K 10046 4000K

cut out 275×35 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10042	10W LED	3000K	600 lm	30 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10043	10W LED	4000K	660 lm	30 °	>90	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10045	20W LED	3000K	1220 lm	30 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h
10046	20W LED	4000K	1280 lm	30 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h

WHITE BLACK



FOCUS MINI LED
10067



FOCUS MINI LED
10071



FOCUS MINI LED

painted aluminum

10067 3000K
10070 4000K
10068 3000K
10071 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10067	10W LED	3000K	600 lm	36 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h
10070	10W LED	4000K	600 lm	36 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h
10068	10W LED	3000K	600 lm	36 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h
10071	10W LED	4000K	600 lm	36 °	>90	~220-230 V, 50/60 Hz		>0.9	IP20	30000h

WHITE BLACK



FOCUS MINI LED 10071

CL IOS LED 20W, ANGLE 60
8742



CL IOS LED 20W, ANGLE 36

zinc aluminum alloy

☐ 8740 3000K ☐ 8738 4000K



CL IOS LED 20W, ANGLE 60

zinc aluminum alloy

■ 8742 3000K ■ 8741 4000K

☐ 8743 4000K

CL IOS LED 30W, ANGLE 36
8731





CL IOS LED 30W, ANGLE 36

zinc aluminum alloy

☐ 8731 3000K ■ 8727 4000K

CL IOS LED 30W, ANGLE 60

zinc aluminum alloy

■ 8732 4000K

CL IOS LED 40W, ANGLE 60
8724





CL IOS LED 40W, ANGLE 60

zinc aluminum alloy

■ 8724 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8740	20W LED	3000K	1600 lm	36 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8738	20W LED	4000K	1600 lm	36 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8743	20W LED	4000K	1600 lm	60 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8742	20W LED	3000K	1600 lm	60 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8741	20W LED	4000K	1600 lm	60 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8731	30W LED	3000K	2700 lm	36 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8727	30W LED	4000K	2700 lm	36 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8732	30W LED	4000K	2700 lm	60 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years
8724	40W LED	3000K	3200 lm	60 °	≥ 90	IP20	Brightlux	Osram	50000h	5 years



HALO 8196



POINT TONE 8222



INDIA 7858



FLEA 8202



HALO 8195



POINT TONE 8225



INDIA 7860



FLEA 8203









HALO

painted steel, plastic ABS

8195 8196

1xGU10 R50, max 10W only LED

POINT TONE

plastic ABS

8222 8221 8225

8224 8223

1xGU10 R50, max 10W only LED

INDIA

painted aluminum

7858 7860

1xGU10 R50, max 15W only LED

FLEA

painted steel

8202 8203

1xGX53, max 12W only LED

WHITE P004 RAL 9003 BLACK P013 RAL 9005 GOLD P021 SILVER

WHITE BLACK



SET 8895



SET

painted steel

8895 8900

1xGU10 R50, max 10W only LED



EYE TONE 8932



EYE TONE 8928



EYE TONE

painted steel, plastic ABS

8932 8928

1xGU10 R50, max 10W only LED



SET 8901



SET

painted steel

8901 8896

1xGU10 R50, max 10W only LED



EYE TONE 8931



EYE TONE 8926



EYE TONE

painted steel, plastic ABS

8931 8926

1xGU10 R50, max 10W only LED



SET 8898



SET

painted steel

8898

1xGU10 R50, max 10W only LED



EYE TONE 8930



EYE TONE 8925



EYE TONE

painted steel, plastic ABS

8930 8925

1xGU10 R50, max 10W only LED

BLACK P013 RAL 9005 WHITE P004 RAL 9003 SILVER P005 GOLD P021

BLACK P013 RAL 9005 WHITE P004 RAL 9003 SILVER P005 GOLD P021

Nowodvorski LIGHTING



EYE TONE 8087



EYE TONE

painted steel, plastic ABS

8086 8087

8088 7665

2xGU10 R50, max 10W only LED

POINT PLEXI L 6528



POINT PLEXI L

painted steel, plastic PMMA

6528 6530

1xE27, max 20W

POINT PLEXI M 6526



POINT PLEXI M

painted steel, plastic PMMA

6525 6526

1xGU10 R50, max 10W only LED



EYE TONE 8092



EYE TONE

painted steel, plastic ABS

8091 8092

8093 7666

3xGU10 R50, max 10W only LED

BIT S 9486



BIT S

painted steel

9482 9486

1xGU10 ES111, max 15W only LED

POINT S 7603



POINT S

painted steel

7603 6000

1xGU10 R50, max 10W only LED

BLACK P013 RAL 9005 WHITE P004 RAL 9003 GOLD P021

WHITE P004 RAL 9003 BLACK P013 RAL 9005 GRAPHITE P010 RAL 7016



SILBA 10476



SILBA

painted aluminum

10476 10477

1xGX53, max 12W only LED



CRES 10478

CRES

painted aluminum

10478 10480

1xGX53, max 12W only LED



MURTER 10490



MURTER

painted aluminum

10490 10489

1xGX53, max 12W only LED

cut out ø 65 mm



MLJET 10494



MLJET

painted aluminum

10494 10493

1xGU10 R50, max 10W only LED

cut out ø 67 mm

VIS

painted aluminum

10486 10485

1xGX53, max 12W only LED

cut out ø 65 mm





VIS 10485

HVAR

painted aluminum

10488 10487

1xGX53, max 12W only LED

cut out ø 65 mm





HVAR 10487

SOLTA

painted aluminum

10492 10491

1xGU10 R50, max 10W only LED

cut out ø 67 mm





SOLTA 10491

SHINE

aluminum

11350 11348

1xGU10 R50, max 15W only LED

cut out ø 68 mm





SHINE 11348

WHITE BLACK

WHITE BLACK



UNO S 10841



UNO S

painted steel

10840 10841

1xGX53, max 15 W only LED

cut out ø 83 mm



UNO M 10843



UNO M

painted steel

10842 10843

1xGX53, max 15 W only LED

cut out ø 102 mm



UNO L 10845



UNO L

painted steel

10844 10845

1xGX53, max 15 W only LED

cut out ø 127 mm



CUP 10789





CUP 10789

CUP

plastic ABS

10788 10789 10790

10791 10792

1xGU10 R50, max 10W only LED

cut out ø 64 mm



CUP 10794

CUP 3 PC SET

plastic ABS

10793 10794

3xGU10 R50, max 10W only LED

cut out ø 64 mm

WHITE P004 RAL 9003 BLACK P004 RAL 9003

WHITE BLACK SATINE CHOCOLATE P025 RAL 8017 SATINE GOLD P023 SATINE COPPER P024



MYKONOS LED 18W
10542



MYKONOS LED 10W

plastic

☐ 10537 3000K ☐ 10538 4000K

cut out 125 mm



MYKONOS LED 18W

plastic

☐ 10542 3000K ☐ 10543 4000K

cut out 175 mm



MYKONOS LED 6W

plastic

☐ 10535 3000K ☐ 10536 4000K

cut out 100 mm



MYKONOS LED 15W

plastic

☐ 10540 3000K ☐ 10541 4000K

cut out 150 mm



MYKONOS LED 24W

plastic

☐ 10544 3000K ☐ 10545 4000K

cut out 200 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10535	6W LED	3000K	360 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10536	6W LED	4000K	390 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10537	10W LED	3000K	900 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10538	10W LED	4000K	950 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10540	15W LED	3000K	1450 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10541	15W LED	4000K	1500 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10542	18W LED	3000K	1700 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10543	18W LED	4000K	1800 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10544	24W LED	3000K	2400 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10545	24W LED	4000K	2500 lm	110°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

☐ WHITE



EGINA LED 5W

plastic

☐ 10546 3000K ☐ 10547 4000K

■ 10548 3000K ■ 10550 4000K

cut out 75 mm



EGINA LED 10W

plastic

☐ 10551 3000K ☐ 10552 4000K

■ 10553 3000K ■ 10554 4000K

cut out 100 mm



EGINA LED 10W
10553



EGINA LED 15W

plastic

☐ 10555 3000K ☐ 10556 4000K

■ 10557 3000K ■ 10558 4000K

cut out 125 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10546	5W LED	3000K	350 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10547	5W LED	4000K	370 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10548	5W LED	3000K	330 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10550	5W LED	4000K	350 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10551	10W LED	3000K	700 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10552	10W LED	4000K	750 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10553	10W LED	3000K	650 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10554	10W LED	4000K	700 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10555	15W LED	3000K	1100 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10556	15W LED	4000K	1200 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10557	15W LED	3000K	1000 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
10558	15W LED	4000K	1100 lm	30°	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

☐ WHITE ■ BLACK

Nowodvorski LIGHTING

5 YEARS WARRANTY



CL KOS LED 8W

plastic

☐ 8782 3000K ☐ 8781 4000K

cut out ø 100 mm



CL KOS LED 10W

plastic

☐ 8780 3000K ☐ 8778 4000K

cut out ø 125 mm



CL KOS LED 16W

plastic

☐ 8777 3000K ☐ 8776 4000K

cut out ø 150 mm



CL KOS LED 24W

plastic

☐ 8775 3000K ☐ 8774 4000K

cut out ø 200 mm



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8782	8W LED	3000K	650 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8781	8W LED	4000K	670 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8780	10W LED	3000K	1000 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8778	10W LED	4000K	1100 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8777	16W LED	3000K	1500 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8776	16W LED	4000K	1600 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8775	24W LED	3000K	2300 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years
8774	24W LED	4000K	2600 lm	100°	≥ 80	IP44/20	Sanan	Driver on board	50000h	5 years

☐ WHITE

Can be used in the bathroom

Nowodvorski LIGHTING

CL DIA LED 18W
8722





cut out 131x131 mm

CL DIA LED 18W

zinc aluminum alloy

8722 3000K



cut out 163x163 mm

CL DIA LED 30W

zinc aluminum alloy

8720 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8720	30W LED	3000K	2250 lm	40°	≥ 90	IP20	Cree	Osram	50000h	5 years
8722	18W LED	3000K	1500 lm	40°	≥ 90	IP20	Cree	Osram	50000h	5 years

WHITE BLACK





CL KEA LED 40W
8767



cut out ø 95 mm

CL KEA LED 20W

plastic

8773 3000K 8772 4000K



cut out ø 190 mm

CL KEA LED 40W

plastic

8767 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8773	20W LED	3000K	1150 lm	65°	≥ 90	IP44/20	Samsung	Osram	50000h	5 years
8772	20W LED	4000K	1150 lm	65°	≥ 90	IP44/20	Samsung	Osram	50000h	5 years
8767	40W LED	4000K	2700 lm	65°	≥ 90	IP44/20	Samsung	Osram	50000h	5 years

Can be used in the bathroom

WHITE CHROME

MOD 9412





MOD
painted steel

■ 9417 □ 9413

1xGU10 ES111, max 15W only LED

cut out 120×120 mm



MOD
painted steel

■ 9416 □ 9412

2xGU10 ES111, max 15W only LED

cut out 230×120 mm

DOWNLIGHT ES111 9570





DOWNLIGHT ES111
painted steel

■ 9570 □ 9574

2xGU10 ES111, max 15W only LED

cut out 320×165 mm

MOD PLUS 9404





MOD PLUS
painted steel

■ 9404 □ 9408

1xGU10 ES111, max 15W only LED

cut out 120×120 mm



MOD PLUS
painted steel

■ 9403 □ 9407

2xGU10 ES111, max 15W only LED

cut out 230×120 mm

DOWNLIGHT ES111 9575





DOWNLIGHT ES111
painted steel

■ 9571 □ 9575

1xGU10 ES111, max 15W only LED

cut out 165×165 mm

WHITE P004 RAL 9003 BLACK P013 RAL 9005

WHITE BLACK

Nowodvorski LIGHTING



EYE MOD 8937



EYE MOD

painted steel

8937

1xGU10 R50, max 10W only LED

cut out 95×90 mm



EYE MOD 8938



EYE MOD

painted steel

8938 8940

2xGU10 R50, max 10W only LED

cut out 175×90 mm

DOT 9378





DOT 9378



DOT

painted steel

9378 8826

1xGU10 R50, max 10W only LED

cut out ø 129 mm



Track Light Systems

TRACK LIGHT SYSTEMS

	NANO LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 24V	ULTRA THIN LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 48V	LVM LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 48V	CTLS COMMERCIAL TRACK LIGHT SYSTEM	PROFILE TRACK LIGHT SYSTEM
Sposoby montażu Installation methods					
System szynoprzewodowy Track light system	 1 obwodowy system szynoprzewodowy 1 circuit track light system	 1 obwodowy system szynoprzewodowy 1 circuit track light system	 1 obwodowy system szynoprzewodowy 1 circuit track light system	 3 obwodowy system szynoprzewodowy 3 circuits track light system	 1 obwodowy system szynoprzewodowy 1 circuit track light system
Zastosowanie Work position	**Sufit / Ceiling** • Natynkowy / Surface • Podtynkowy / Recessed • Wiszący / Hanging **Ściana / Wall** • Natynkowy / Surface • Podtynkowy / Recessed	**Sufit / Ceiling** • Natynkowy / Surface **Ściana / Wall** • Natynkowy / Surface	**Sufit / Ceiling** • Natynkowy / Surface • Podtynkowy / Recessed • Wiszący / Hanging **Ściana / Wall** • Natynkowy / Surface • Podtynkowy / Recessed	**Sufit / Ceiling** • Natynkowy / Surface • Podtynkowy / Recessed • Wiszący / Hanging	**Sufit / Ceiling** • Natynkowy / Surface • Podtynkowy / Recessed • Wiszący / Hanging
Źródło światła Source of light	Zintegrowane źródło światła LED integrated	Zintegrowane źródło światła LED integrated	Zintegrowane źródło światła LED integrated	• Wymienne źródło światła, • zintegrowane źródło światła • Exchangable source of light, • LED integrated	• Wymienne źródło światła, • zintegrowane źródło światła • Exchangable source of light, • LED integrated
Napięcie Voltage	⎓ 24V	⎓ 48V	⎓ 48V	~ 230V	~ 230V
Zastosuj z Cameleon System Works with Cameleon System	No	No	No	Yes	Yes

Nowodvorski LIGHTING

NANO LVM Track Light System 24V

Visualisation by Iwona Ligęza



NANO - LVM FOCUS OUT LED 10W 11720





NANO - LVM FOCUS OUT LED 10W

painted aluminum, plastic

11720

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11720	10W LED	3000K	450 lm	24°	>90	24V	III	IP20	30000h

BLACK



NANO - LVM FOCUS OUT LED 5W 11718





NANO - LVM FOCUS OUT LED 5W

painted aluminum, plastic

11718

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11718	5W LED	3000K	290 lm	24°	>90	24V	III	IP20	30000h

BLACK



NANO - LVM LINE OUT LED 20W 11721



NANO - LVM LINE OUT LED 20W

painted aluminum, plastic

11721

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11721	20W LED	3000K	610 lm	100 °	>90	24V	III	IP20	30000h

BLACK



NANO - LVM LINE OUT LED 10W 11743



NANO - LVM LINE OUT LED 10W

painted aluminum, plastic

11743

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11743	10W LED	3000K	400 lm	100 °	>90	24V	III	IP20	30000h

BLACK



NANO - LVM LINE IN LED 6W 11717



NANO - LVM LINE OUT LED 6W 11723



NANO - LVM LINE IN LED 6W

painted aluminum, plastic

11717

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11717	6W LED	3000K	100 lm	100°	>90	24V	III	IP20	30000h

BLACK



NANO - LVM FLEX LINE LED 6W

silicone, plastic

11723

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11723	6W LED	3000K	180 lm	100°	>90	24V	III	IP20	30000h

WHITE BLACK


NANO - LVM SPOT LED 1W 11712


NANO - LVM MUG LED 7W 11722







NANO - LVM SPOT LED 1W

painted aluminum, plastic

11712





NANO - LVM MUG LED 7W

painted aluminum, plastic

11722

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11712	1W LED	3000K	65 lm	38°	>90	24V		IP20	30000h

BLACK

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11722	7W LED	3000K	460 lm	24°	>90	24V		IP20	30000h

BLACK



NANO - LVM SPOT ZOOM LED 5W 11714



NANO - LVM SPOT ZOOM LED 15W 11716



NANO - LVM SPOT ZOOM LED 2W
11713



NANO - LVM SPOT ZOOM LED 7W
11715









NANO - LVM SPOT ZOOM LED 2W

painted aluminum, plastic

11713

NANO - LVM SPOT ZOOM LED 5W

painted aluminum, plastic

11714

NANO - LVM SPOT ZOOM LED 7W

painted aluminum, plastic

11715

NANO - LVM SPOT ZOOM LED 15W

painted aluminum, plastic

11716

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11713	2W LED	3000K	120 lm	15-45°	>90	24V		IP20	30000h
11714	5W LED	3000K	290 lm	15-45°	>90	24V		IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11715	7W LED	3000K	300 lm	15-45°	>90	24V		IP20	30000h
11716	15W LED	3000K	500 lm	15-45°	>90	24V		IP20	30000h

BLACK

BLACK

SPOSOBY MONTAŻU / INSTALLATION METHODS

1



SURFACE CONNECTION



NANO - LVM TRACK



NANO - LVM TRACK



NANO - LVM INSIDE CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

2



RECESSED CONNECTION



NANO - LVM RECESSED TRACK



NANO - LVM RECESSED TRACK



NANO - LVM RECESSED INSIDE CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

3



SURFACE CONNECTION



NANO - LVM TRACK



NANO - LVM INSIDE CORNER



NANO - LVM HORIZONTAL CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

4



SURFACE CONNECTION



NANO - LVM TRACK



NANO - LVM INSIDE CORNER



NANO - LVM CURVE TRACK R400



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

5



RECESSED CONNECTION



NANO - LVM RECESSED TRACK



NANO - LVM RECESSED INSIDE CORNER



NANO - LVM RECESSED HORIZONTAL CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

6



SURFACE CONNECTION



NANO - LVM TRACK



NANO - LVM TRACK



NANO - LVM INSIDE CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

7



RECESSED CONNECTION



NANO - LVM RECESSED TRACK



NANO - LVM RECESSED TRACK



NANO - LVM RECESSED INSIDE CORNER



ELECTRICAL CONNECTION NANO - LVM CORNER CONDUCTIVE MODULE

8



SUSPENDED CONNECTION



NANO - LVM SUSPENSION KIT



NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE FOR SUSPENSION TRACK



NANO LVM - LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 24V



Zestaw zawiera listwę maskującą i zatyczkę
Set includes a masking strip and a plug



1 NANO - LVM TRACK 1M
aluminum
■ 11724

2 NANO - LVM TRACK 2M
aluminum
■ 11725

3 NANO - LVM CURVE TRACK R400
aluminum
■ 11737

Schemat zasilania / Power supply circuit diagram



System szynoprzewodowy (NANO LVM) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
Maksymalna długość systemu szynoprzewodowego z jednego źródła zasilania - 5 m.

The track light system (NANO LVM) should be evenly electrically loaded and the fittings should be evenly placed along its length.
The recommended fastening distance is max. 1000 mm.
Maximum length of track light system with a single power source is 5 m.

■ BLACK

Sposób montażu / Installation methods

1. Zwieszenie na linkach
1. Suspended on steel wires



4 NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE FOR SUSPENSION TRACK
plastic
■ 11740



5 NANO - LVM RECESSED OUTSIDE POWER SUPPLY CONDUCTIVE MODULE FOR SUSPENSION TRACK
plastic
■ 11738



6 NANO - LVM SUSPENSION KIT
steel
■ 11744





Sposób montażu / Installation method

2. Montaż bezpośredni
2. Surface mounting





* Konieczność zastosowania zasilacza zewnętrznego 24V DC.
Zaleca się aby suma watażu użytych opraw nie przekraczała 90% mocy znamionowej zasilacza.
* Need for of using an external 24V DC power supply.
It is recommended that the total wattage of the luminaires used does not exceed 90% of the power supply's rated power.



7 NANO - LVM STRAIGHT CONDUCTIVE MODULE
plastic
■ 11734



8 NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE
plastic
■ 11736



9 NANO - LVM CORNER CONDUCTIVE MODULE
plastic
■ 11735



10 NANO - LVM HORIZONTAL CORNER
aluminum
■ 11727



11 NANO - LVM INSIDE CORNER
aluminum
■ 11728



12 NANO - LVM TRACK BUCKLE CONNECTOR
aluminum
■ 11726



13 24V DC, 75W, POWER SUPPLY
plastic
11875



14 24V DC, 150W, POWER SUPPLY
plastic
11874



15 POWER SUPPLY COVER
painted steel
■ 11893 □ 11894

■ BLACK P013 RAL 9005 □ WHITE P004 RAL 9003

NANO LVM - RECESSED LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM 24V



Zestaw zawiera listwę maskującą
Set includes a masking strip

1 NANO - LVM RECESSED TRACK 1M

aluminum

■ 11730

2 NANO - LVM RECESSED TRACK 2M

aluminum

■ 11731

Schemat zasilania / Power supply circuit diagram



System szynoprzewodowy (NANO LVM) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.
Zalecany dystans pomiędzy mocowaniami 1000 mm.
Maksymalna długość systemu szynoprzewodowego z jednego źródła zasilania - 5 m.

The track light system (NANO LVM) should be evenly electrically loaded and the fittings should be evenly placed along its length.
The recommended fastening distance is 1000 mm.
Maximum length of track light system with a single power source is 5 m.

Sposób montażu / Installation method

1. Montaż podtynkowy
1. Recessed mounting



* Konieczność zastosowania zasilacza zewnętrznego 24V DC.
  Zaleca się aby suma watażu użytych opraw nie przekraczała 90% mocy znamionowej zasilacza.
* Need for of using an external 24V DC power supply.
  It is recommended that the total wattage of the luminaires used does not exceed 90% of the power supply's rated power.



3 NANO - LVM RECESSED HORIZONTAL CORNER

aluminum

11732



4 NANO - LVM RECESSED INSIDE CORNER

aluminum

11733



5 NANO - LVM STRAIGHT CONDUCTIVE MODULE

plastic

11734



6 NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE

plastic

11736



7 NANO - LVM CORNER CONDUCTIVE MODULE

plastic

11735



8 NANO - LVM TRACK BUCKLE CONNECTOR

aluminum

11726



9 24V DC, 75W, POWER SUPPLY

plastic

11875



10 24V DC, 150W, POWER SUPPLY

plastic

11874

BLACK

BLACK

Nowodvorski LIGHTING



Visualisation by Iwona Ligęza

UT-LVM Track Light System 48V


UT-LVM FOCUS LED 18W 11306


UT-LVM FOCUS LED 12W 11305



UT-LVM FOCUS LED 18W
11332



UT-LVM FOCUS LED 12W
11331

UT-LVM FOCUS LED 18W

aluminum

■ 11306 3000K ■ 11332 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11306	18W LED	3000K	1500 lm	30°	≥90	48V	III	IP20	40000h
11332	18W LED	4000K	1500 lm	30°	≥90	48V	III	IP20	40000h

■ BLACK

UT-LVM FOCUS LED 12W

aluminum

■ 11305 3000K ■ 11331 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11305	12W LED	3000K	1000 lm	30°	≥90	48V	III	IP20	40000h
11331	12W LED	4000K	1000 lm	30°	≥90	48V	III	IP20	40000h

■ BLACK



UT-LVM LINE LED 18W 11308



UT-LVM LINE LED 18W
11334

UT-LVM LINE LED 18W

aluminum

11308 3000K 11334 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Power factor	Lifetime
11308	18W LED	3000K	1500 lm	110 °	≥90	48V	III	IP20	40000h
11334	18W LED	4000K	1500 lm	110 °	≥90	48V	III	IP20	40000h

BLACK



UT-LVM LINE LED 12W 11307



UT-LVM LINE LED 12W
11333

UT-LVM LINE LED 12W

aluminum

11307 3000K 11333 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Power factor	Lifetime
11307	12W LED	3000K	1000 lm	110 °	≥90	48V	III	IP20	40000h
11333	12W LED	4000K	1000 lm	110 °	≥90	48V	III	IP20	40000h

BLACK







UT-LVM FOCUS OUT LED 12W
11338



UT-LVM FOCUS OUT LED 12W

aluminum

■ 11313 3000K ■ 11338 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11313	12W LED	3000K	1000 lm	30°	≥90	48V	III	IP20	40000h
11338	12W LED	4000K	1000 lm	30°	≥90	48V	III	IP20	40000h

■ BLACK



UT-LVM FOCUS OUT LED 6W
11337



UT-LVM FOCUS OUT LED 6W

aluminum

■ 11312 3000K ■ 11337 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11312	6W LED	3000K	500 lm	30°	≥90	48V	III	IP20	40000h
11337	6W LED	4000K	500 lm	30°	≥90	48V	III	IP20	40000h

■ BLACK







UT-LVM FOCUS SWING LED 12W
11336



UT-LVM FOCUS SWING LED 12W

aluminum

■ 11311 3000K ■ 11336 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11311	12W LED	3000K	1000 lm	30°	≥90	48V		IP20	40000h
11336	12W LED	4000K	1000 lm	30°	≥90	48V		IP20	40000h

■ BLACK



UT-LVM FOCUS SWING LED 6W
11335



UT-LVM FOCUS SWING LED 6W

aluminum

■ 11310 3000K ■ 11335 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11310	6W LED	3000K	500 lm	30°	≥90	48V		IP20	40000h
11335	6W LED	4000K	500 lm	30°	≥90	48V		IP20	40000h

■ BLACK



UT-LVM SPOT LED 5W 11314



UT-LVM SPOT LED 9W 11315



UT-LVM SPOT LED 5W
11340



UT-LVM SPOT LED 5W

aluminum

■ 11314 3000K ■ 11340 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11314	5W LED	3000K	450 lm	36°	≥90	48V	III	IP20	40000h
11340	5W LED	4000K	450 lm	36°	≥90	48V	III	IP20	40000h

■ BLACK



UT-LVM SPOT LED 9W
11341



UT-LVM SPOT LED 9W

aluminum

■ 11315 3000K ■ 11341 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11315	9W LED	3000K	850 lm	36°	≥90	48V	III	IP20	40000h
11341	9W LED	4000K	850 lm	36°	≥90	48V	III	IP20	40000h

■ BLACK

Nowodvorski LIGHTING


UT-LVM SPOT LED 12W 11316


UT-LVM SPOT LED 12W
11342



UT-LVM SPOT LED 12W

aluminum

11316 3000K 11342 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11316	12W LED	3000K	1200 lm	36°	≥90	48V	III	IP20	40000h
11342	12W LED	4000K	1200 lm	36°	≥90	48V	III	IP20	40000h

BLACK



UT-LVM ROLLER LED 10W

aluminum

11317 3000K 11343 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11317	10W LED	3000K	1000 lm	36°	≥90	48V	III	IP20	40000h
11343	10W LED	4000K	1000 lm	36°	≥90	48V	III	IP20	40000h

BLACK


UT-LVM ROLLER LED 10W 11317

SPOSOBY MONTAŻU / INSTALLATION METHODS

1



SURFACE CONNECTION

2



SURFACE CONNECTION

3



SURFACE CONNECTION



UT-LVM TRACK



UT-LVM TRACK



UT-LVM TRACK



UT-LVM TRACK



UT-LVM VERTICAL CONNECTOR



UT-LVM TRACK



UT-LVM VERTICAL CONNECTOR



UT-LVM L CONNECTOR



UT-LVM VERTICAL CONNECTOR



UT-LVM END CAP



UT-LVM END CAP



UT-LVM END CAP

UT-LVM TRACK LIGHT SYSTEM 48V



Zestaw zawiera listwę maskującą
Set includes a masking strip

1 UT-LVM TRACK 1M

aluminum

■ 11320

2 UT-LVM TRACK 2M

aluminum

■ 11318

Schemat zasilania / Power supply circuit diagram





System szynoprzewodowy (UT-LVM) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
Maksymalna długość systemu szynoprzewodowego z jednego źródła zasilania - 20 m.

The track light system (UT-LVM) should be evenly electrically loaded and the fittings should be evenly placed along its length.
The recommended fastening distance is max. 1000 mm.
Maximum length of track light system with a single power source is 20 m.

SPOSOBY MONTAŻU / INSTALLATION METHODS

1. Montaż bezpośredni
1. Surface mounting





3 UT-LVM 48V, 100W INSIDE POWER SUPPLY
aluminum
■ 11328



4 UT-LVM 48V, 200W INSIDE POWER SUPPLY
aluminum
■ 11330



5 UT-LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE
plastic, copper
■ 11321



6 UT-LVM VERTICAL CONNECTOR
plastic, copper
■ 11326



7 UT-LVM STRAIGHT CONNECTOR
plastic, copper
■ 11322



8 UT-LVM L CONNECTOR
plastic, copper
■ 11325



9 UT-LVM END CAP
plastic
■ 11327

■ BLACK

LVM Track Light System 48V

Visualisation by Iwona Ligęza



LVM FOCUS LED 15W 10150



LVM FOCUS LED 9W 10144



LVM FOCUS LED 15W
10643



LVM FOCUS LED 15W

painted aluminum, plastic

■ 10150 3000K ■ 10643 4000K

□ 11630 3000K □ 11631 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10150	15W LED	3000K	1300 lm	30°	>90	48V		IP20	30000h
10643	15W LED	4000K	1400 lm	30°	>90	48V		IP20	30000h
11630	15W LED	3000K	1300 lm	30°	>90	48V		IP20	30000h
11631	15W LED	4000K	1400 lm	30°	>90	48V		IP20	30000h

BLACK WHITE



LVM FOCUS LED 9W
11632



LVM FOCUS LED 9W

painted aluminum, plastic

■ 10144 3000K ■ 10644 4000K

□ 11632 3000K □ 11633 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10144	9W LED	3000K	800 lm	30°	>90	48V		IP20	30000h
10644	9W LED	4000K	880 lm	30°	>90	48V		IP20	30000h
11632	9W LED	3000K	800 lm	30°	>90	48V		IP20	30000h
11633	9W LED	4000K	880 lm	30°	>90	48V		IP20	30000h

WHITE BLACK



LVM FOCUS OUT LED 15W 10151



LVM FOCUS OUT LED 9W 10145



LVM FOCUS OUT LED 15W
10645



LVM FOCUS OUT LED 15W

painted aluminum, plastic

■ 10151 3000K ■ 10645 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10151	15W LED	3000K	1300 lm	30°	>90	48V	III	IP20	30000h
10645	15W LED	4000K	1400 lm	30°	>90	48V	III	IP20	30000h

■ BLACK □ WHITE



LVM FOCUS OUT LED 9W
11634



LVM FOCUS OUT LED 9W

painted aluminum, plastic

■ 10145 3000K ■ 10646 4000K

□ 11634 3000K □ 11635 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10145	9W LED	3000K	800 lm	30°	>90	48V	III	IP20	30000h
10646	9W LED	4000K	880 lm	30°	>90	48V	III	IP20	30000h
11634	9W LED	3000K	800 lm	30°	>90	48V	III	IP20	30000h
11635	9W LED	4000K	880 lm	30°	>90	48V	III	IP20	30000h

□ WHITE ■ BLACK



LVM LINE LED 15W 10148



LVM LINE LED 9W 10143



LVM LINE LED 15W
10650



LVM LINE LED 15W

painted aluminum, plastic

■ 10148 3000K ■ 10650 4000K

□ 11636 3000K □ 11637 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10148	15W LED	3000K	700 lm	110 °	>90	48V		IP20	30000h
10650	15W LED	4000K	770 lm	110 °	>90	48V		IP20	30000h
11636	15W LED	3000K	700 lm	110 °	>90	48V		IP20	30000h
11637	15W LED	4000K	770 lm	110 °	>90	48V		IP20	30000h

■ BLACK □ WHITE



LVM LINE LED 9W
10651



LVM LINE LED 9W

painted aluminum, plastic

■ 10143 3000K ■ 10651 4000K

□ 11638 3000K □ 11639 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10143	9W LED	3000K	400 lm	110 °	>90	48V		IP20	30000h
10651	9W LED	4000K	440 lm	110 °	>90	48V		IP20	30000h
11638	9W LED	3000K	400 lm	110 °	>90	48V		IP20	30000h
11639	9W LED	4000K	440 lm	110 °	>90	48V		IP20	30000h

□ WHITE ■ BLACK

Nowodvorski LIGHTING



LVM SPOT LED 15W 10147



LVM SPOT LED 9W 10142



LVM SPOT LED 15W
10655



LVM SPOT LED 15W

painted aluminum, plastic

- 10147 3000K
- 10655 4000K
- 11642 3000K
- 11643 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10147	15W LED	3000K	1020 lm	30°	>90	48V		IP20	30000h
10655	15W LED	4000K	1100 lm	30°	>90	48V		IP20	30000h
11642	15W LED	3000K	1020 lm	30°	>90	48V		IP20	30000h
11643	15W LED	4000K	1100 lm	30°	>90	48V		IP20	30000h

BLACK WHITE



LVM SPOT LED 9W
10656



LVM SPOT LED 9W

painted aluminum, plastic

- 10142 3000K
- 10656 4000K
- 11644 3000K
- 11645 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10142	9W LED	3000K	780 lm	30°	>90	48V		IP20	30000h
10656	9W LED	4000K	850 lm	30°	>90	48V		IP20	30000h
11644	9W LED	3000K	780 lm	30°	>90	48V		IP20	30000h
11645	9W LED	4000K	850 lm	30°	>90	48V		IP20	30000h

WHITE BLACK

LVM ROLLER LED 9W
10652





LVM ROLLER LED 9W

painted aluminum, plastic

■ 10146 3000K ■ 10652 4000K

□ 11640 3000K □ 11641 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10146	9W LED	3000K	620 lm	36 °	>90	48V		IP20	30000h
10652	9W LED	4000K	680 lm	36 °	>90	48V		IP20	30000h
11640	9W LED	3000K	620 lm	36 °	>90	48V		IP20	30000h
11641	9W LED	4000K	680 lm	36 °	>90	48V		IP20	30000h

■ BLACK □ WHITE



Visualisation by Iwona Ligęza



LVM LID LED 8W
10647



LVM LID LED 8W

painted aluminum, plastic PMMA

■ 10152 3000K ■ 10647 4000K



LVM LID LED 8W
10648



LVM LID LED 8W

painted aluminum, plastic PMMA

■ 10153 3000K ■ 10648 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10152	8W LED	3000K	650 lm	160 °	>90	48V	III	IP20	30000h
10647	8W LED	4000K	650 lm	160 °	>90	48V	III	IP20	30000h
10153	8W LED	3000K	650 lm	160 °	>90	48V	III	IP20	30000h
10648	8W LED	4000K	650 lm	160 °	>90	48V	III	IP20	30000h

■ BLACK



LVM SLOT LED 5W
10653



LVM SLOT LED 5W

painted aluminum, plastic PMMA

■ 10154 3000K ■ 10653 4000K



LVM SLOT LED 8W
10654



LVM SLOT LED 8W

painted aluminum, plastic PMMA

■ 10155 3000K ■ 10654 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
10154	5W LED	3000K	210 lm	100 °	>90	48V	III	IP20	30000h
10653	5W LED	4000K	250 lm	100 °	>90	48V	III	IP20	30000h
10155	8W LED	3000K	370 lm	100 °	>90	48V	III	IP20	30000h
10654	8W LED	4000K	400 lm	100 °	>90	48V	III	IP20	30000h

■ BLACK

SPOSOBY MONTAŻU / INSTALLATION METHODS

1



SURFACE CONNECTION



LVM TRACK



LVM TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

2



RECESSED - SURFACE
CONNECTION



LVM RECESSED TRACK



LVM TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

3



SURFACE - RECESSED
CONNECTION



LVM TRACK



LVM RECESSED TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

4



RECESSED CONNECTION



LVM RECESSED TRACK



LVM RECESSED TRACK



LVM RECESSED
INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

5



SURFACE CONNECTION



LVM TRACK



LVM INSIDE CORNER



LVM HORIZONTAL
CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

6



RECESSED CONNECTION



LVM RECESSED TRACK



LVM RECESSED
HORIZONTAL CORNER



LVM RECESSED
INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

7



SUSPENDED CONNECTION



LVM TRACK



LVM POWER SUPPLY KIT

LVM SUSPENSION
KIT

SPOSOBY MONTAŻU / INSTALLATION METHODS

8



SURFACE CONNECTION



LVM TRACK



LVM TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

9



RECESSED - SURFACE
CONNECTION



LVM TRACK



LVM RECESSED TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

10



SURFACE - RECESSED
CONNECTION



LVM RECESSED TRACK



LVM TRACK



LVM INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

11



RECESSED CONNECTION



LVM RECESSED TRACK



LVM RECESSED TRACK



LVM RECESSED
INSIDE CORNER



ELECTRICAL CONNECTION
LVM CORNER CONDUCTIVE
MODULE

LVM - LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM



Zestaw zawiera listwę maskującą i zatyczkę
Set includes a masking strip and a plug

1 LVM TRACK 1M

aluminum

■ 10162 □ 11626

2 LVM TRACK 2M

aluminum

■ 10163 □ 11627

Schemat zasilania / Power supply circuit diagram



System szynoprzewodowy (LVM) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
Maksymalna długość systemu szynoprzewodowego z jednego źródła zasilania - 20 m.

The track light system (LVM) should be evenly electrically loaded and the fittings should be evenly placed along its length.
The recommended fastening distance is max. 1000 mm.
Maximum length of track light system with a single power source is 20 m.

■ BLACK □ WHITE

Sposób montażu / Installation method

1. Zwieszenie na linkach
1. Suspended on steel wires





3 LVM POWER SUPPLY KIT

plastic, painted steel

■ 10597 □ 11803

4 LVM SUSPENSION KIT

steel

▒ 10170





□ WHITE ▒ SILVER ■ BLACK

Nowodvorski LIGHTING

Sposób montażu / Installation method

2. Montaż bezpośredni
2. Surface mounting





5 LVM 48V, 150W, INSIDE POWER SUPPLY

aluminum

■ 10161 □ 11616



6 LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE

plastic

■ 10168 □ 11621



7 LVM STRAIGHT CONDUCTIVE MODULE

plastic

■ 10167 □ 11628



8 LVM CORNER CONDUCTIVE MODULE

plastic

■ 10166 □ 11617



9 LVM INSIDE CORNER

aluminum

■ 10165 □ 11620

includes 2xLVM TRACK BUCKLE CONNECTOR



10 LVM HORIZONTAL CORNER

aluminum

■ 10164 □ 11618

includes 2xLVM TRACK BUCKLE CONNECTOR



11 LVM TRACK BUCKLE CONNECTOR

steel

▨ 10171

BLACK WHITE

WHITE SILVER BLACK

Nowodvorski LIGHTING

LVM - RECESSED LOW VOLTAGE MAGNETIC TRACK LIGHT SYSTEM



Zestaw zawiera listwę maskującą
Set includes a masking strip

1 LVM RECESSED TRACK 1M

aluminum

■ 10156 □ 11624

2 LVM RECESSED TRACK 2M

aluminum

■ 10157 □ 11625

Schemat zasilania / Power supply circuit diagram





Konstrukcja szynoprzewodów umożliwia dostosowanie wysokości skrzydełek do rożnych grubości płyt gipsowo-kartonowych.
Możliwa regulacja to: 3, 6, 9 i 12 mm.
System szynoprzewodowy (LVM) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
Maksymalna długość systemu szynoprzewodowego z jednego źródła zasilania - 20 m.

The design of the track light system makes it possible to adjust the height of the wings for different thicknesses of drywall.
Possible adjustments are: 3, 6, 9 and 12 mm.
The track light system (LVM) should be evenly electrically loaded and the fittings should be evenly placed along its length.
The recommended fastening distance is max. 1000 mm.
Maximum length of track light system with a single power source is 20 m.

■ BLACK □ WHITE

Sposób montażu / Installation method

1. Montaż podtynkowy
1. Recessed mounting



* Zasilacz zewnętrzny 48V DC
* External power supply 48V DC

* Możliwość zastosowania zasilacza zewnętrznego 48V DC.
  Zaleca się aby suma watażu użytych opraw nie przekraczała 90% mocy znamionowej zasilacza.
* Possibility of using an external 48V DC power supply.
  It is recommended that the total wattage of the luminaires used does not exceed 90% of the power supply's rated power.

□ WHITE ■ BLACK

Nowodvorski LIGHTING



3 LVM 48V, 150W, INSIDE POWER SUPPLY

aluminium

■ 10161 □ 11616



4 LVM CORNER CONDUCTIVE MODULE

plastic

■ 10166 □ 11617



5 LVM STRAIGHT CONDUCTIVE MODULE

plastic

■ 10167 □ 11628



6 LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE

plastic

■ 10168 □ 11621



7 LVM TRACK BUCKLE CONNECTOR

steel

▒ 10171



8 LVM RECESSED INSIDE CORNER

aluminum

■ 10160 □ 11623

includes 2xLVM TRACK BUCKLE CONNECTOR



9 LVM RECESSED HORIZONTAL CORNER

aluminum

■ 10158 □ 11622

includes 2xLVM TRACK BUCKLE CONNECTOR



10 48V DC, 80W, POWER SUPPLY

plastic

11301



11 48V DC, 200W, POWER SUPPLY

plastic

11287



12 48V DC, 320W, POWER SUPPLY

plastic

11278

■ BLACK □ WHITE ▒ SILVER

□ WHITE ■ BLACK

CTLS - Commercial Track Light System

Visualisation by Iwona Ligęza



CTLS MILO LED 15W
8766

Zestaw zawiera 3 soczewki
3 lenses included



CTLS MILO LED 15W

zinc aluminum alloy

- 8766 3000K
- 8765 4000K
- 8764 3000K
- 8763 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8766	15W LED	3000K	1300 lm	15/24/50 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years
8765	15W LED	4000K	1300 lm	15/24/50 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years
8764	15W LED	3000K	1300 lm	15/24/50 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years
8763	15W LED	4000K	1300 lm	15/24/50 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years

WHITE BLACK



CTLS MILO LED 25W
8762

Zestaw zawiera 3 soczewki
3 lenses included



CTLS MILO LED 25W

zinc aluminum alloy

- 8762 3000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8762	25W LED	3000K	1900 lm	15/24/40 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years

WHITE

Nowodvorski LIGHTING





CTLS NEA LED 20W
8757



Zestaw zawiera 3 soczewki i filtr przeciwolśnieniowy
"plaster miodu"
3 lenses and anti-glare "honeycomb" included



CTLS NEA LED 20W

zinc aluminum alloy

☐ 8757 3000K ☐ 8756 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8757	20W LED	3000K	1600 lm	15/23/36 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years
8756	20W LED	4000K	1600 lm	15/23/36 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years

☐ WHITE





CTLS NEA LED 30W
8752



Zestaw zawiera 3 soczewki i filtr przeciwolśnieniowy
"plaster miodu"
3 lenses and anti-glare "honeycomb" included



CTLS NEA LED 30W

zinc aluminum alloy

☐ 8752 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8752	30W LED	4000K	2600 lm	20/25/37 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years

☐ WHITE

Nowodvorski LIGHTING



CTLS NEA LED 40W
8747

Zestaw zawiera 3 soczewki i filtr przeciwolśnieniowy
"plaster miodu"
3 lenses and anti-glare "honeycomb" included



CTLS NEA LED 40W

zinc aluminum alloy

8747 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Ingress protection	LED brand	Driver brand	Lifetime	Warranty
8747	40W LED	4000K	3600 lm	20/25/37 °	≥ 90	IP20	Samsung	Ostram	50000h	5 years

WHITE


CTLS NEA LED 40W 8747



CTLS TINOS LED 10W
10396



CTLS TINOS LED 20W
10391



CTLS TINOS LED 30W
10398







CTLS TINOS LED 10W

painted aluminum, plastic

☐ 10390 3000K ☐ 10393 4000K

■ 10396 3000K ■ 10399 4000K

CTLS TINOS LED 20W

painted aluminum, plastic

☐ 10391 3000K ☐ 10394 4000K

■ 10397 3000K ■ 10400 4000K

CTLS TINOS LED 30W

painted aluminum, plastic

■ 10398 3000K ■ 10401 4000K

☐ 10395 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10390	10W LED	3000K	950 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10393	10W LED	4000K	1000 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10396	10W LED	3000K	880 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10399	10W LED	4000K	980 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10391	20W LED	3000K	1800 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10394	20W LED	4000K	2000 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10397	20W LED	3000K	1700 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10400	20W LED	4000K	1900 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10398	30W LED	3000K	2600 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10401	30W LED	4000K	2900 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h
10395	30W LED	4000K	3000 lm	36 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP20	30000h

☐ WHITE ■ BLACK

☐ WHITE ■ BLACK



CTLS SNOWBALL
11296



CTLS SNOWBALL

plastic PC, glass, painted steel

11296

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



CTLS MONO

painted steel, plastic ABS

10235 10236

10238 10239

1xGU10 R50, max 10W only LED

solid brass, plastic ABS

10237

1xGU10 R50, max 10W only LED



CTLS MONO 10239



CTLS SNOWBALL
11295



CTLS SNOWBALL

plastic PC, glass, painted steel

11295

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K



CAMELEON ADAPTER CTLS

plastic

8281 8282



CAMELEON ADAPTER CTLS
8281

WHITE BLACK

Scan QR code to get know
Cameleon System offer

BRASS GOLD P021 BLACK P013 RAL 9005 WHITE P004 RAL 9003

Nowodvorski LIGHTING

CTLS - COMMERCIAL TRACK LIGHT SYSTEM, 3 CIRCUIT



1 CTLS TRACK 3 CIRCUIT 1M

aluminum

☐ 8715 ■ 8714

2 CTLS TRACK 3 CIRCUIT 2M

aluminum

☐ 8717 ■ 8716

Schematy zasilania / Power supply circuit diagrams



1 faza, 3 obwody
1-phase, 3-circuit

230 V AC, 16 A, 3.7 kVA, THD ≤ 15%



3 fazy, 3 obwody
3-phase, 3-circuit

230/400 V AC, 16 A, 3 x 3.7 kVA, THD ≤ 15%



3 fazy, 3 obwody
3-phase, 3-circuit

230/400 V AC, 16 A, 11.1 kVA, THD ≤ 15%



Maksymalna długość systemu szynoprzewodowego - 100 m.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
System szynoprzewodowy (CTLS) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.

Maximum length of track lights system - 100 m.
The recommended fastening distance is max. 1000 mm.
The track light system (CTLS) should be evenly electrically loaded and the fittings should be evenly placed along its length.

☐ WHITE ■ BLACK

Sposoby montażu / Installation methods



3 CTLS SUSPENSION KIT 3 CIRCUIT

plastic, steel

☐ 8696 ■ 8697



4 CTLS POWER SUPPLY KIT 3 CIRCUIT

painted steel, painted steel, plastic

☐ 8284 ■ 8283

1. Zwieszenie na linkach
1. Suspended on steel wires



Krawędzie ustalające polaryzację (pozycje) oprawy oświetleniowej.
Ridges setting polarity (position) of the lighting fixture.

2. Montaż bezpośredni
2. Surface mounting



Krawędzie ustalające polaryzację (pozycje) oprawy oświetleniowej.
Ridges setting polarity (position) of the lighting fixture.

☐ WHITE ■ BLACK

CTLS - POLARITY IN COMMERCIAL TRACK LIGHT SYSTEM



Czerwona linia wskazuje biegunowość systemu (obserwuj styk uziemiający)
The red line indicates polarity of the system (observe earth contact)



Widok z dołu
Bottom view
Вид снизу





5 CTLS POWER END CAP, RIGHT (PE-R)

plastic, copper

☐ 8712 ■ 8713





6 CTLS POWER END CAP, LEFT (PE-L)

plastic, copper

☐ 8232 ■ 8233





7 CTLS POWER STRAIGHT CONNECTOR

plastic, copper

☐ 8707 ■ 8708





8 CTLS POWER L CONNECTOR, RIGHT (L-R)

plastic, copper

☐ 8227 ■ 8228





9 CTLS POWER L CONNECTOR, LEFT (L-L)

plastic, copper

☐ 8705 ■ 8706





10 CTLS POWER T CONNECTOR, LEFT 2 (T-L2)

plastic, copper

☐ 8236 ■ 8237





11 CTLS POWER T CONNECTOR, LEFT 1 (T-L1)

plastic, copper

☐ 8243 ■ 8244





12 CTLS POWER T CONNECTOR, RIGHT 2 (T-R2)

plastic, copper

☐ 8703 ■ 8704





13 CTLS POWER T CONNECTOR, RIGHT 1 (T-R1)

plastic, copper

☐ 8241 ■ 8242





14 CTLS POWER X CONNECTOR

plastic, copper

☐ 8701 ■ 8702





15 CTLS POWER FLEX CONNECTOR

plastic, copper

☐ 8698 ■ 8700



16 CTLS DEAD END CAP

plastic

☐ 8710 ■ 8711



17 CTLS STRAIGHT CONNECTOR MINI

plastic, copper

☐ 8085 ■ 8084

☐ WHITE ■ BLACK

☐ WHITE ■ BLACK

Nowodvorski LIGHTING

CTLS - RECESSED COMMERCIAL TRACK LIGHT SYSTEM, 3 CIRCUIT



1 CTLS RECESSED TRACK 3 CIRCUIT 1M

aluminum

☐ 8693 ■ 8692

2 CTLS RECESSED TRACK 3 CIRCUIT 2M

aluminum

☐ 8695 ■ 8694

Schematy zasilania / Power supply circuit diagrams



1 faza, 3 obwody
1-phase, 3-circuit

230 V AC, 16 A, 3.7 kVA, THD ≤ 15%



3 fazy, 3 obwody
3-phase, 3-circuit

230/400 V AC, 16 A, 3 x 3.7 kVA, THD ≤ 15%



L1+L2+L3:I = max. 16 A

3 fazy, 3 obwody
3-phase, 3-circuit

230/400 V AC, 16 A, 11.1 kVA, THD ≤ 15%



N- conductor L=max.16 A

Maksymalna długość systemu szynoprzewodowego - 100 m.
Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
System szynoprzewodowy (CTLS) należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.

Maximum length of track lights system - 100 m.
The recommended fastening distance is max. 1000 mm.
The track light system (CTLS) should be evenly electrically loaded and the fittings should be evenly placed along its length.

☐ WHITE ■ BLACK

Sposób montażu / Installation method

1. Montaż podtynkowy
1. Recessed mounting





Krawędzie ustalające polaryzację (pozycje) oprawy oświetleniowej.
Ridges setting polarity (position) of the lighting fixture.



Krawędzie ustalające polaryzację (pozycje) oprawy oświetleniowej.
Ridges setting polarity (position) of the lighting fixture.

☐ WHITE ■ BLACK

Nowodvorski LIGHTING

CTLS - POLARITY IN RECESSED COMMERCIAL TRACK LIGHT SYSTEM



Czerwona linia wskazuje biegunowość systemu (obserwuj styk uziemiający)
The red line indicates polarity of the system (observe earth contact)



Widok z dołu
Bottom view





3 CTLS RECESSED POWER END CAP, RIGHT (PE-R)

plastic, copper

☐ 8691 ■ 8690





4 CTLS RECESSED POWER END CAP, LEFT (PE-L)

plastic, copper

☐ 8234 ■ 8235





5 CTLS RECESSED POWER STRAIGHT CONNECTOR

plastic, copper

☐ 8686 ■ 8685





6 CTLS RECESSED POWER L CONNECTOR, RIGHT (L-R)

plastic, copper

☐ 8230 ■ 8231





7 CTLS RECESSED POWER L CONNECTOR, LEFT (L-L)

plastic, copper

☐ 8684 ■ 8683





8 CTLS RECESSED POWER T CONNECTOR, LEFT 2 (T-L2)

plastic, copper

☐ 8238 ■ 8240





9 CTLS RECESSED POWER T CONNECTOR, LEFT 1 (T-L1)

plastic, copper

☐ 8247 ■ 8248





10 CTLS RECESSED POWER T CONNECTOR, RIGHT 2 (T-R2)

plastic, copper

☐ 8681 ■ 8682





11 CTLS RECESSED POWER T CONNECTOR, RIGHT 1 (T-R1)

plastic, copper

☐ 8245 ■ 8246





12 CTLS RECESSED POWER X CONNECTOR

plastic, copper

☐ 8678 ■ 8680





13 CTLS RECESSED POWER FLEX CONNECTOR

plastic, copper

☐ 8676 ■ 8677



14 CTLS RECESSED DEAD END CAP

plastic

☐ 8688 ■ 8687



15 CTLS RECESSED FIXING SET

steel

▒ 8306

WHITE BLACK

SILVER WHITE BLACK

Nowodvorski LIGHTING

Profile Track Light System

Visualisation by Iwona Ligęza



PROFILE TINOS LED 7W 10385



PROFILE TINOS LED 10W 10373



PROFILE TINOS LED 20W 10383



PROFILE TINOS LED 30W 10375









PROFILE TINOS LED 7W

painted aluminum, plastic

☐ 10372 3000K ☐ 10376 4000K

■ 10381 3000K ■ 10385 4000K

PROFILE TINOS LED 10W

painted aluminum, plastic

☐ 10373 3000K ☐ 10377 4000K

■ 10382 3000K ■ 10386 4000K

PROFILE TINOS LED 20W

painted aluminum, plastic

☐ 10374 3000K ☐ 10378 4000K

■ 10383 3000K ■ 10387 4000K

PROFILE TINOS LED 30W

painted aluminum, plastic

☐ 10375 3000K ☐ 10380 4000K

■ 10384 3000K ■ 10388 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10372	7W LED	3000K	550 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10376	7W LED	4000K	570 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10381	7W LED	3000K	530 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10385	7W LED	4000K	550 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10373	10W LED	3000K	950 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10377	10W LED	4000K	1000 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10382	10W LED	3000K	880 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10386	10W LED	4000K	980 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10374	20W LED	3000K	1800 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10378	20W LED	4000K	2000 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10383	20W LED	3000K	1700 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10387	20W LED	4000K	1900 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10375	30W LED	3000K	2800 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10380	30W LED	4000K	3000 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10384	30W LED	3000K	2600 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h
10388	30W LED	4000K	2900 lm	36 °	>80	~220-230 V, 50/60 Hz	⧈	>0.9	IP20	30000h

☐ WHITE ■ BLACK

☐ WHITE ■ BLACK



PROFILE IRIS LED 7W 8996



PROFILE IRIS LED 7W

painted aluminum, plastic PC

- 8995 3000K
- 8997 4000K
- 8996 3000K
- 8998 4000K



PROFILE IRIS LED 20W 9005



PROFILE IRIS LED 12W 9002



PROFILE IRIS LED 12W

painted aluminum, plastic PC

- 9000 3000K
- 9002 4000K
- 9001 3000K
- 9003 4000K



PROFILE IRIS LED 20W

painted aluminum, plastic PC

- 9004 3000K
- 9006 4000K
- 9005 3000K
- 9007 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8995	7W LED	3000K	550 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
8996	7W LED	3000K	530 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
8997	7W LED	4000K	560 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
8998	7W LED	4000K	550 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9000	12W LED	3000K	1000 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9001	12W LED	3000K	950 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9002	12W LED	4000K	1100 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9003	12W LED	4000K	1000 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9004	20W LED	3000K	1500 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9005	20W LED	3000K	1400 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9006	20W LED	4000K	1600 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h
9007	20W LED	4000K	1500 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP20	30000h

WHITE BLACK

WHITE BLACK



PROFILE MIKE 7661



PROFILE MIKE

painted aluminum, plastic

■ 7661

1xGU10 R50, max 15W only LED



PROFILE ZOOM LED 7625





PROFILE INDIA 7657



PROFILE INDIA

painted aluminum, plastic

■ 7657

1xGU10 R50, max 15W only LED



BEAM CONE

BEAM ANGLE 15°

BEAM ANGLE 50°

PROFILE ZOOM LED

painted aluminum, plastic

☐ 7623 3000K ☐ 7624 4000K

■ 7625 3000K ■ 7626 4000K



PROFILE FOCUS 7621



PROFILE FOCUS LED

painted aluminum, plastic

☐ 7618 3000K ☐ 7620 4000K

■ 7621 3000K ■ 7622 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection
7618	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7620	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7621	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7622	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7623	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7624	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7625	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20
7626	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	⧈	>0.9	IP20

☐ WHITE ■ BLACK

☐ WHITE ■ BLACK

Nowodvorski LIGHTING



PROFILE EYE SUPER C 9244



PROFILE EYE SUPER C

painted steel, plastic PC

☐ 9245 ■ 9244

1xGU10 R50, max 10W only LED

PROFILE BIT PLUS

painted steel, plastic PC

■ 9018

1xGU10 ES111, max 15W only LED





PROFILE BIT PLUS 9018



PROFILE EYE SUPER A 9325



PROFILE EYE SUPER A

painted steel, plastic PC

☐ 9324 ■ 9325

1xGU10 R50, max 10W only LED

PROFILE BIT

painted steel, plastic PC

■ 8823

1xGU10 ES111, max 15W only LED





PROFILE BIT 8823



PROFILE SNOWBALL
11297



PROFILE SNOWBALL

plastic PC, glass, painted steel

■ 11297

1xG9, max 12W only LED

BULB LED G9, 4W

☐ 7503 3000K ☐ 7504 4000K

PROFILE EYE

painted steel, plastic PC

☐ 9337 ■ 9338

1xGU10 R50, max 10W only LED





PROFILE EYE 9338



PROFILE EYE SPOT 9322



PROFILE EYE SPOT

painted steel, plastic PC, chrome

9321 9322

1xGU10 R50, max 10W only LED

PROFILE SNOWBALL

plastic PC, glass, painted steel

11298

1xG9, max 12W only LED

BULB LED G9, 4W

7503 3000K 7504 4000K





PROFILE SNOWBALL
11298



PROFILE MONO 7583



PROFILE MONO

painted steel, plastic ABS

7581 7582

7584 7585

1xGU10 R50, max 10W only LED

solid brass, painted steel, plastic ABS

7583

1xGU10 R50, max 10W only LED

PROFILE VESPA

painted steel, plastic PC, chrome

8824 8825

1xGU10 ES111, max 15W only LED





PROFILE VESPA 8825



PROFILE PUCK 10358



PROFILE PUCK

painted steel, plastic PC

10358

1xGX53, max 12W only LED

CAMELEON ADAPTER PROFILE

plastic

8360 8361





CAMELEON ADAPTER PROFILE
8360

BLACK P013 RAL 9005 GOLD P021 BRASS WHITE P004 RAL 9003

Scan QR code to get know
Cameleon System offer

WHITE P004 RAL 9003 BLACK P013 RAL 9005

PROFILE TRACK LIGHT SYSTEM



1 PROFILE TRACK 1 M
painted aluminum

☐ 9450 ■ 9448

2 PROFILE TRACK 2 M
painted aluminum

☐ 9451 ■ 9452

Schemat zasilania / Power supply circuit diagram

Zalecany dystans pomiędzy mocowaniami max. 1000 mm
Maksymalna długość jednego obwodu systemu szynoprzewodowego PROFILE - 20 m, a maksymalne obciążenie elektryczne - 1500W
System szynoprzewodowy należy równomiernie obciążyć elektrycznie oraz równomiernie rozmieścić oprawy na jego długości.

The recommended fastening distance is max. 1000 mm
The maximum length of one circuit of PROFILE track light system -20 m, and the maximum circuit power load - 1500W
The track light system should be evenly electrically loaded and the fittings should be evenly placed along its length.

☐ WHITE ■ BLACK

Sposoby montażu / Installation methods





3 PROFILE POWER SUPPLY KIT
painted steel

☐ 9237 ■ 9238

4 PROFILE SUSPENSION KIT
painted steel, plastic

☐ 9461 ■ 9460

1. Zwieszenie na linkach stalowych
1. Suspended on steel wires



2. Montaż bezpośredni
2. Surface mounting



☐ WHITE ■ BLACK

PROFILE TRACK LIGHT SYSTEM





5 PROFILE POWER END CAP

plastic PC, steel, copper

☐ 9462 ■ 9463



6 PROFILE POWER STRAIGHT CONNECTOR

plastic PC, steel

☐ 10225 ■ 10226



7 PROFILE STRAIGHT CONNECTOR

plastic PC, steel, copper

☐ 9454 ■ 9453



8 PROFILE L CONNECTOR

plastic PC, steel, copper

☐ 9456 ■ 9455



9 PROFILE T CONNECTOR

plastic PC, steel, copper

☐ 9187 ■ 9186



10 PROFILE X CONNECTOR

plastic PC, steel, copper

☐ 9190 ■ 9188



11 PROFILE FLEX CONNECTOR

plastic PC, steel, copper

☐ 8382 ■ 8383



12 PROFILE DEAD END CAP

plastic PC

☐ 9457 ■ 9458

☐ WHITE ■ BLACK

☐ WHITE ■ BLACK

Nowodvorski LIGHTING

PROFILE RECESSED TRACK LIGHT SYSTEM



1 PROFILE RECESSED TRACK 1 METER

painted aluminum

☐ 9012 ■ 9013

2 PROFILE RECESSED TRACK 2 METERS

painted aluminum

☐ 9014 ■ 9015

Sposób montażu / Installation method

1. Montaż podtynkowy
1. Recessed mounting



Schemat zasilania / Power supply circuit diagram

1 faza, 1 obwód
1-phase, 1-circuit





Zalecany dystans pomiędzy mocowaniami max. 1000 mm.
Maksymalna długość jednego obwodu systemu szynoprzewodowego PROFILE - 20 m, a maksymalne obciążenie elektryczne - 1500W.
System szynoprzewodowy należy rownomiernie obciążyć elektrycznie oraz rownomiernie rozmieścić oprawy na jego długości.

The recommended fastening distance is max. 1000 mm.
The maximum length of one circuit of track light system PROFILE -20 m, and the maximum circuit power load - 1500W.
The track light system should be evenly electrically loaded and the fittings should be evenly placed along its length.

☐ WHITE ■ BLACK

PROFILE RECESSED TRACK LIGHTS SYSTEM





3 PROFILE RECESSED POWER END CAP

plastic PC, steel, copper

☐ 8972 ■ 8973



4 PROFILE RECESSED POWER STRAIGHT CONNECTOR

plastic PC, steel

☐ 10227 ■ 10228



5 PROFILE RECESSED STRAIGHT CONNECTOR

plastic PC, steel, copper

☐ 8967 ■ 8968



6 PROFILE RECESSED L CONNECTOR

plastic PC, steel, copper

☐ 8970 ■ 8971



7 PROFILE RECESSED T CONNECTOR

plastic PC, steel, copper

☐ 8834 ■ 8835



8 PROFILE RECESSED X CONNECTOR

plastic PC, steel, copper

☐ 8836 ■ 8837



9 PROFILE RECESSED FLEX CONNECTOR

plastic PC, steel, copper

☐ 8384 ■ 8385



10 PROFILE RECESSED DEAD END CAP

plastic PC

☐ 8974 ■ 8975



11 PROFILE RECESSED FIXING SET

steel

▥ 8805





ICE BALL 8126



ICE BALL

brass-plated steel, glass

8126

1xG9, max 10W only LED

IP44

ARALIA

brass-plated steel, glass

10527

1xG9, max 10W only LED

IP44





ARALIA 10527



ALOE 10525



ALOE

brass-plated steel, glass

10525

1xG9, max 10W only LED

IP44

AGAVE

brass-plated steel, glass

10526

1xG9, max 10W only LED

IP44





AGAVE 10526

BRASS WHITE

BRASS WHITE

Nowodvorski LIGHTING



NATALIE 10727



NATALIE 10727



NATALIE 10726



NATALIE 10724



NATALIE 10723



NATALIE

aluminum, glass

10726 10727 10728

2xG9, max 10W only LED

IP44



NATALIE

aluminum, glass

10723 10724 10725

1xG9, max 10W only LED

IP44

WHITE CHROME BRASS BLACK

Nowodvorski LIGHTING



ICE TUBE LED S 8121



ICE TUBE LED M 8122





ICE TUBE LED S

plastic PC, chrome plated steel

8121

ICE TUBE LED M

plastic PC, chrome plated steel

8122

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8121	5W LED	4000K	430 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	30000h
8122	8W LED	4000K	700 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	30000h

WHITE WHITE



ICE TUBE LED S 8118



ICE TUBE LED M 8120





ICE TUBE LED S

plastic PC, chrome plated steel

8118

ICE TUBE LED M

plastic PC, chrome plated steel

8120

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8118	12W LED	4000K	1200 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	30000h
8120	18W LED	4000K	1750 lm	120°	≥80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	30000h

WHITE CHROME



BRAZOS 6948



BRAZOS

glass, chrome plated steel

6948

1xG9, max 10W only LED

IP44



SIMI

painted steel, glass

8052

1xG9, max 10W only LED

IP44



SIMI 8052



BRAZOS 6950



BRAZOS

glass, chrome plated steel

6950

2xG9, max 10W only LED

IP44



BRAZOS

painted steel, glass

8057

1xG9, max 10W only LED

IP44



BRAZOS 8057



BRAZOS 6951



BRAZOS

glass, chrome plated steel

6951

3xG9, max 10W only LED

IP44



BRAZOS

glass, painted steel

8056

3xG9, max 10W only LED

IP44



BRAZOS 8056

WHITE CHROME

WHITE BLACK

ICE EGG A 8124





ICE EGG A

painted steel, glass

8124

1xG9, max 10W only LED

IP44

ICE EGG C 8132





ICE EGG C

painted aluminum, glass

8132

1xG9, max 10W only LED

IP44

SIS 8054





SIS

glass, painted steel

8054

1xG9, max 10W only LED

IP44

CAYO 9505





CAYO

glass, painted steel

8055

1xG9, max 10W only LED

IP44

glass, chrome plated steel

9505

1xG9, max 10W only LED

IP44

BLACK WHITE

WHITE BLACK CHROME

Nowodvorski LIGHTING



VISTA 8051



VISTA 8050



VISTA

chrome plated steel, glass

8051

1xG9, max 10W only LED

IP44



VISTA

chrome plated steel, glass

8050

3xG9, max 10W only LED

IP44



MALAKKA LED 9501



MALAKKA LED

chrome plated steel, glass

9501



PAN LED S 8173



PAN LED S

glass, chrome plated steel

8173



PAN LED M

glass, chrome plated steel

8174

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9501	18W LED	4000K	940 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP44	20000h
8173	12W LED	4000K	770 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP44	20000h
8174	17W LED	4000K	1000 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP44	20000h

WHITE CHROME TRANSPARENT

WHITE CHROME TRANSPARENT

Nowodvorski LIGHTING



TORCH 8123



TORCH

chrome plated steel, glass

8123

1xG9, max 10W only LED

IP44

CEARA 10713

CEARA

aluminum

10713 10714

10715 10716

1xGU10 R50, max 15W only LED

IP44



PALMAS LED

aluminum, glass, plastic PC

10729 10730



PALMAS LED 10729

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10729	15W LED	4000K	1000 lm	130°	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP44	30000h
10730	15W LED	4000K	1000 lm	130°	>90	~220-230 V, 50/60 Hz	⏚	>0.9	IP44	30000h

BLACK CHROME WHITE BRASS

CHROME BRASS



PARANA 10719



PARANA 10718



PARANA

aluminum

10717 10718

10719 10720

1xGU10 R50, max 15W only LED

IP44



BOL

painted aluminum

10483 10484

1xGX53, max 12W only LED

IP54



BOL 10483



MAUN

painted aluminum

10481 10482

1xGX53, max 12W only LED

IP54



MAUN 10481



BRAVO 8364



BRAVO 8365



BRAVO

painted aluminum, glass

8364 8365

1xGU10 R50, max 15W only LED

IP54



ALPHA

painted aluminum, glass

8362 8363

1xGU10 R50, max 15W only LED

IP54



ALPHA 8362

CHROME BLACK WHITE BRASS

BLACK WHITE

ZESTAW ZAWIERA 4 KOLOROWE NAKŁADKI.

THE SET INCLUDES FOUR COLOURED RINGS.



FOXTROT 8373



FOXTROT 8374







FOXTROT

painted aluminum, glass

8373 8374

1xGU10 R50, max 15W only LED

cut out ø 85 mm

IP54/20



WHITE BLACK

Can be used outdoor

CHARLIE 8367









CHARLIE 8366

CHARLIE

painted aluminum, glass

☐ 8366 ■ 8367

1xGU10 R50, max 15W only LED

cut out ø 75 mm

IP54/20





GOLF 8376



GOLF 8375



GOLF

painted aluminum, glass

☐ 8375 ■ 8376

1xGU10 R50, max 15W only LED

cut out ø 68 mm

IP54/20

DELTA 8370









DELTA 8368

DELTA

painted aluminum, glass

☐ 8368 ■ 8370

1xGU10 R50, max 15W only LED

cut out ø 75 mm

IP54/20





ECHO 8372





ECHO 8371

ECHO

painted aluminum, glass

☐ 8371 ■ 8372

1xGU10 R50, max 15W only LED

cut out ø 80 mm

IP54/20

☐ WHITE ■ BLACK

Can be used outdoor

Can be used outdoor

☐ WHITE ■ BLACK

Nowodvorski LIGHTING



JULIET 7663



JULIET 7664



JULIET

steel

7663 7664

1xGU10 R50, max 15W only LED

cut out ø 56 mm

IP54/20



ACRE

aluminum, glass

10711

1xGU10 R50, max 15W only LED

cut out ø 75 mm

IP44/20



ACRE 10711



HELIOS LED 8992



HELIOS LED

plastic PC

8991 3000K 8992 4000K

cut out ø 85 mm



BAHIA

aluminum, glass

10712

1xGU10 R50, max 15W only LED

cut out ø 75 mm

IP44/20



BAHIA 10712

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8991	5W LED	3000K	300 lm	100 °	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44/20	20000h
8992	5W LED	4000K	300 lm	100 °	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44/20	20000h

WHITE CHROME SILVER

BRASS



PIN LED S 8127



PIN LED S

painted aluminum, plastic PC

8127

PIN LED M

painted aluminum, plastic PC

8128



PIN LED L

painted aluminum, plastic PC

8130

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8127	6W LED	4000K	280 lm	120°	≥80	~220-230 V, 50/60 Hz		>0.9	IP44	30000h
8128	10W LED	4000K	500 lm	120°	≥80	~220-230 V, 50/60 Hz		>0.9	IP44	30000h
8130	15W LED	4000K	700 lm	120°	≥80	~220-230 V, 50/60 Hz		>0.9	IP44	30000h

BLACK



PICASSO LED 8131

PICASSO LED

chrome plated aluminum, plastic PC

8131





LATH LED 8175

LATH LED

chrome plated steel, plastic PC

8175



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8131	12W LED	4000K	900 lm	120°	≥80	~220-230 V, 50/60 Hz		>0.5	IP44	30000h
8175	16W LED	4000K	1000 lm	120°	≥80	~220-230 V, 50/60 Hz		>0.5	IP44	20000h

CHROME

Nowodvorski LIGHTING

Sposoby montażu / Installation methods

1



2



3



1. Na lustrze
1. On the mirror

2. Na szafce łazienkowej
2. On the bathroom cabinet

3. Na ścianie
3. On the wall



CEZANNE LED S

painted aluminum, plastic ABS, plastic PMMA

10668 3000K
10676 4000K
10665 3000K
10680 4000K
10672 3000K
10683 4000K



CEZANNE LED M

painted aluminum, plastic ABS, plastic PMMA

10670 3000K
10677 4000K
10666 3000K
10681 4000K
10673 3000K
10684 4000K



CEZANNE LED L

painted aluminum, plastic ABS, plastic PMMA

10671 3000K
10678 4000K
10667 3000K
10682 4000K
10674 3000K
10685 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10665	8W LED	3000K	600 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10668	8W LED	3000K	550 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10672	8W LED	3000K	600 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10676	8W LED	4000K	600 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10680	8W LED	4000K	650 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10683	8W LED	4000K	650 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10666	12W LED	3000K	900 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10670	12W LED	3000K	850 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10673	12W LED	3000K	900 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10681	12W LED	4000K	950 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10684	12W LED	4000K	950 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10677	12W LED	4000K	900 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10667	15W LED	3000K	1100 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10671	15W LED	3000K	1050 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10674	15W LED	3000K	1100 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10678	15W LED	4000K	1100 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10682	15W LED	4000K	1200 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h
10685	15W LED	4000K	1200 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⧈	>0.5	IP44	25000h

CHROME BLACK WHITE

CHROME BLACK WHITE

AGNES ROUND LED PRO
10980





AGNES ROUND LED PRO
painted steel, plastic PMMA

☐ 10977 3000K ☐ 10978 4000K

■ 10971 3000K ■ 10972 4000K



AGNES ROUND LED PRO
painted steel, plastic PMMA

☐ 10979 3000K ☐ 10980 4000K

■ 10973 3000K ■ 10974 4000K



AGNES ROUND LED PRO
painted steel, plastic PMMA

☐ 10981 3000K ☐ 10982 4000K

■ 10975 3000K ■ 10976 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
10971	22W LED	3000K	1600 lm	120 °	>80	~220-230 V, 50-60Hz Hz		IP44	40000h
10972	22W LED	4000K	1800 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10973	32W LED	3000K	2600 lm	120 °	>80	~220-230 V, 50-60 Hz		IP44	40000h
10974	32W LED	4000K	2700 lm	120 °	>80	~220-230 V, 50-60 Hz		IP44	40000h
10975	64W LED	3000K	5600 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10976	64W LED	4000K	5900 lm	120 °	>80	~220-230 V, 50-60 Hz		IP44	40000h
10977	22W LED	3000K	1800 lm	120 °	>80	~220-230 V, 50-60 Hz		IP44	40000h
10978	22W LED	4000K	2000 lm	120 °	>80	~220-230 V, 50-60 Hz		IP44	40000h
10979	32W LED	3000K	2800 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10980	32W LED	4000K	3000 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10981	64W LED	3000K	5800 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10982	64W LED	4000K	6200 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h

☐ WHITE ■ BLACK

AGNES SQUARE LED PRO
10987





AGNES SQUARE LED PRO
painted steel, plastic PMMA

☐ 10989 3000K ☐ 10990 4000K

■ 10983 3000K ■ 10984 4000K



AGNES SQUARE LED PRO
painted steel, plastic PMMA

☐ 10991 3000K ☐ 10992 4000K

■ 10985 3000K ■ 10986 4000K



AGNES SQUARE LED PRO
painted steel, plastic PMMA

☐ 10993 3000K ☐ 10994 4000K

■ 10987 3000K ■ 10988 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
10983	16W LED	3000K	1200 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10984	16W LED	4000K	1300 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10985	32W LED	3000K	2700 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10986	32W LED	4000K	2800 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10987	64W LED	3000K	5600 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10988	64W LED	4000K	6000 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10989	16W LED	3000K	1400 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10990	16W LED	4000K	1500 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10991	32W LED	3000K	2900 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10992	32W LED	4000K	3100 lm	120 °	>80	~220-230 V, 50/60Hz Hz		IP44	40000h
10993	64W LED	3000K	6100 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h
10994	64W LED	4000K	6500 lm	120 °	>80	~220-230 V, 50/60 Hz		IP44	40000h

☐ WHITE ■ BLACK



Outdoor lighting



STONE S 10579



STONE S

plastic PE

☐ 10579

1xE27, max 25W only LED

IP44



STONE M 10580



STONE M

plastic PE

☐ 10580

1xE27, max 25W only LED

IP44



STONE L 10581



STONE L

plastic PE

☐ 10581

1xE27, max 25W only LED

IP44



☐ WHITE

Nowodvorski LIGHTING





CUMULUS L 6978



CUMULUS S

plastic PE

6976

1xE27, max 25W only LED

IP44



CUMULUS M

plastic PE

6977

1xE27, max 25W only LED

IP44



CUMULUS XL

plastic PE

9714

1xE27, max 25W only LED

IP44



CUMULUS L

plastic PE

6978

1xE27, max 25W only LED

IP44





CUMULUS M 9715

CUMULUS S 9751



CUMULUS S

plastic PE, painted steel

9751

1xE27, max 25W only LED

IP65



CUMULUS M

plastic PE, painted steel

9715

1xE27, max 25W only LED

IP65



CUMULUS L

plastic PE, painted steel

9607

1xE27, max 25W only LED

IP65

WHITE

WHITE

Nowodvorski LIGHTING



FLOWERPOT S 9711



FLOWERPOT S

plastic PE

9711

1xE27, max 25W only LED

IP44



FLOWERPOT M 9712



FLOWERPOT M

plastic PE

9712

1xE27, max 25W only LED

IP44



FLOWERPOT L 9713



FLOWERPOT L

plastic PE

9713

2xE27, max 25W only LED

IP44

WHITE



CUMULUS CUBE M 8966



CUMULUS CUBE M

plastic PE

8966

1xE27, max 25W only LED

IP44



STAR

plastic PE

9426

1xE27, max 25W only LED

IP44



STAR 9426

CUMULUS CUBE L 8965



CUMULUS CUBE L

plastic PE

8965

1xE27, max 25W only LED

IP44



PATIO

painted steel, plastic LLDPE

10105

1xE27, max 25W only LED

IP44



PATIO 10105

WHITE

GRAPHITE P010 RAL 7016

WHITE







ZOLA LED

painted aluminum, plastic PC

11546



ZOLA LED

painted aluminum, plastic PC

11545



ZOLA LED

painted aluminum, plastic PC

11544

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	VOLTAGE DC	Safety type	Ingress protection	Lifetime
11544	3W LED	3000K	100 lm	360 °	>90	24V	III	IP54	30000h
11545	3W LED	3000K	100 lm	360 °	>90	24V	III	IP54	30000h
11546	3W LED	3000K	100 lm	360 °	>90	24V	III	IP54	30000h

BLACK



RUBY LED 11542



RUBY LED

painted aluminum, plastic PC

11542



LIV LED 11538

Visualisation by Iwona Ligęza



TESSA LED 11541



TESSA LED

painted aluminum, plastic PC

11541

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11542	7W LED	3000K	400 lm	24 °	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11541	7W LED	3000K	400 lm	70 °	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

BLACK



LIV LED

painted aluminum, plastic PC

11538

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11538	6W LED	3000K	200 lm	20 °	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

BLACK

Nowodvorski LIGHTING



MIA LED M
11374



MIA LED M

painted aluminum, plastic PC

11374



MIA LED L
11375

MIA LED L

painted aluminum, plastic PC

11375

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11374	30W LED	3000K	2500 lm	70 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	30000h
11375	100W LED	3000K	7800 lm	70 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	30000h

BLACK

IDA

painted aluminum, glass

11371

1xE27, max 10W LED

IP44



IDA
11371



IDA

painted aluminum, glass

11372

2xE27, max 10W LED

IP44



IDA
11372



IDA

painted aluminum, glass

11373

1xE27, max 10W LED

IP44



IDA
11373



BLACK

Nowodvorski LIGHTING



SLIT LED 11376



SLIT LED

painted aluminum, plastic PC

11376

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11376	12W LED	3000K	600 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

BLACK

SLIM LED 11540





SLIM LED

painted aluminum, plastic PC

11540

LHOTSE LED 4448





LHOTSE LED

painted aluminum, plastic PC

4448

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11540	7W LED	3000K	450 lm	120 °	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
4448	9W LED	3000K	169 lm	70 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.8	IP54	10000h

BLACK GRAPHITE

Nowodvorski LIGHTING





STRUCTURE LED

painted aluminum, plastic PC

8146

STRUCTURE LED 8146





STRUCTURE LED

painted aluminum, plastic PC

8145

STRUCTURE LED 8145

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8145	13W LED	3000K	820 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h
8146	13W LED	3000K	820 lm	120°	≥80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h

BLACK

SYMMETRY LED

painted aluminum, plastic PC

8176





SYMMETRY LED 8176



SYMMETRY LED

painted aluminum, plastic PC

8180



SYMMETRY LED 8180

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8176	7W LED	3000K	210 lm	70°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	30000h
8180	7W LED	3000K	380 lm	70°	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	30000h

GRAPHITE

TEPIC LED 9508





TEPIC LED

painted aluminum

■ 9508

MONTERREY LED 9507





MONTERREY LED

painted aluminum

■ 9507

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9508	9W LED	3000K	395 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.8	IP54	10000h
9507	9W LED	3000K	410 lm	40 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.8	IP54	10000h

■ BLACK

THIKA LED B 9120



THIKA LED B

painted aluminum, glass

■ 9120



THIKA LED 9118





THIKA LED

painted aluminum, glass

■ 9118

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9118	9W LED	3000K	550 lm	40 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	20000h
9120	15W LED	3000K	1200 lm	110 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h

■ BLACK





POLE LED

painted aluminum, plastic PC

9185



ZURI LED

painted aluminum, plastic PC

11547



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9185	15W LED	3000K	1000 lm	70 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	30000h

GRAPHITE

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11547	12W LED	3000K	850 lm	120 °	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

BLACK







OTTAWA

painted aluminum, glass

9562

1xGU10 R50, max 10W only LED

IP44

OTTAWA 9562



OTTAWA 9561



OTTAWA

painted aluminum, glass

9561

1xGU10 R50, max 10W only LED

IP44



OTTAWA 9563



OTTAWA

painted aluminum, glass

9563

1xGU10 R50, max 10W only LED

IP44



SOUL

painted aluminum, glass

9555

1xGU10 R50, max 10W only LED

IP44



SOUL 9555

SOUL

painted aluminum, glass

9557

1xGU10 R50, max 10W only LED

IP44



SOUL 9557

NORIN 4446





NORIN

painted aluminum, glass

4446

1xE27, max 10W only LED

IP44

TUBINGS S 8160



TUBINGS M 8161



TUBINGS 8158





HORN 4906



HORN

painted aluminum, glass

4906

1xE27, max 10W only LED

IP44







TUBINGS S

painted aluminum, glass

8160

1xGU10 R50, max 10W only LED

IP54

TUBINGS M

painted aluminum, glass, plastic

8161

1xGU10 R50, max 10W only LED

IP54

TUBINGS

painted aluminum, glass

8158

1xGU10 R50, max 10W only LED

IP54

GRAPHITE BROWN

BLACK



RIO 4424



RIO

painted aluminum, plastic PC

4424

2xE27, max 10W only LED

IP54



RIO SENSOR 7017



RIO

painted aluminum, plastic PC

4423

1xE27, max 10W only LED

IP54

RIO SENSOR

painted aluminum, plastic PC

7017

1xE27, max 10W only LED

IP54

OIR

painted aluminum, plastic PC

9158

1xE27, max 10W only LED

IP44



OIR 9158



RIO SENSOR

painted aluminum, plastic PC

9097

1xE27, max 10W only LED

IP54





RIO SENSOR 9097

BLACK

BLACK



MEKONG 4418



MEKONG
painted aluminum, glass

4418

1xE27, max 10W only LED

IP42



MEKONG 4420



MEKONG
painted aluminum, glass

4420

2xE27, max 10W only LED

IP42



MISTRAL
painted aluminum, plastic PC

3394

1xE27, max 10W only LED

IP44



MISTRAL 3394



MEKONG 4698



MEKONG
painted aluminum, glass

4698

1xE27, max 10W only LED

IP42

BLACK

GRAPHITE

Nowodvorski LIGHTING

PATHWAY LED PRO 10283



PATHWAY LED PRO

painted steel, painted aluminum, plastic

10283 3000K 10633 4000K



PATHWAY FOUNDATION KIT

steel

8795

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10283	60W LED	3000K	5700 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP65	30000h
10633	60W LED	4000K	5900 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP65	30000h

SILVER BLACK P013 RAL 9005



PATHWAY LED S

painted steel, painted aluminum, plastic

9420

PATHWAY LED S 9420





PATHWAY LED M

painted steel, painted aluminum, plastic

9252

PATHWAY LED M 9252



PATHWAY LED L

painted steel, painted aluminum, plastic

9125

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protect	Lifetime
9420	24W LED	3000K	2200 lm	100 °	≥ 70	~220-230 V, 50/60 Hz	⏚	>0.9	IP65	30000h
9252	24W LED	3000K	2200 lm	100 °	≥ 70	~220-230 V, 50/60 Hz	⏚	>0.9	IP65	30000h
9125	36W LED	3000K	3600 lm	100 °	≥ 70	~220-230 V, 50/60 Hz	⏚	>0.9	IP65	30000h

BLACK P013 RAL 9005





NEL LED

painted aluminum, glass

11368



NEL LED

painted aluminum, glass

11370

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11368	5W LED	3000K	500 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11370	2x5W LED	3000K	880 lm	120°	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

BLACK



ORLA LED S

painted aluminum, plastic PC

11548 11551



ORLA LED M

painted aluminum, plastic PC

11550 11552


ORLA LED M 11552

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11548	12W LED	3000K	750 lm	120°	>90	~220-230V V, 50/60 Hz	⏚	>0.7	IP54	30000h
11550	20W LED	3000K	1300 lm	120°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11551	12W LED	3000K	750 lm	120°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11552	20W LED	3000K	1300 lm	120°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

Can be used in the bathroom

BLACK SAND

Nowodvorski LIGHTING



ISLA LED 11554



ISLA LED

painted aluminum, plastic PMMA

11553 11554

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11553	22W LED	3000K	1200 lm	>90°	120	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11554	22W LED	3000K	1200 lm	>90°	120	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

BLACK SAND

Can be used in the bathroom



DEMI LED M

painted aluminum, plastic PC

11555 11556 11557



DEMI LED L

painted aluminum, plastic PC

11558 11560 11561

DEMI LED M 11557



DEMI LED L 11560

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11555	18W LED	3000K	1200 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11556	18W LED	3000K	1200 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11557	18W LED	3000K	1200 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11558	24W LED	3000K	1500 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11560	24W LED	3000K	1500 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h
11561	24W LED	3000K	1500 lm	110°	>90	~220-230 V, 50/60 Hz	⏚	>0.7	IP54	30000h

Can be used in the bathroom

BLACK SAND BRICK RED



ARIA LED S 11564





ARIA LED S

painted aluminum, plastic PC

11562 11563 11564

ARIA LED M 11566







ARIA LED M

painted aluminum, plastic PC

11565 11566 11567





ARIA LED L

painted aluminum, plastic PC

11568 11570 11571





ARIA LED XL

painted aluminum, plastic PC

11572 11573 11574

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11562	6W LED	3000K	370 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11563	6W LED	3000K	370 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11564	6W LED	3000K	370 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11565	9W LED	3000K	540 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11566	9W LED	3000K	540 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11567	9W LED	3000K	540 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11568	12W LED	3000K	750 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11570	12W LED	3000K	750 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11571	12W LED	3000K	750 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11572	15W LED	3000K	1100 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11573	15W LED	3000K	1100 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h
11574	15W LED	3000K	1100 lm	110°	>90	~220-230 V, 50/60 Hz		>0.7	IP54	30000h

Can be used in the bathroom

BLACK SAND BRICK RED



TRIANGLES LED 8141



TRIANGLES LED

painted aluminum, glass

8143 8142 8141



SEMI LED

painted aluminum, glass

6775 11363 11365



SEMI LED M 11366



ELLIPSES LED 8182



ELLIPSES LED

painted aluminum, glass

8140 8182



SEMI LED M

painted aluminum, glass

11364 11366

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8140	2x5W LED	3000K	800 lm	180 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
8141	2x5W LED	3000K	750 lm	180 °	≥80	~220-230 V, 50/60 Hz	⏚	> 0.5	IP54	10000h
8142	2x5W LED	3000K	700 lm	180 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
8143	2x5W LED	3000K	800 lm	180 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
8182	2x5W LED	3000K	700 lm	180 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
6775	2x3W LED	3000K	242 lm	40 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	8000h
11363	2x3W LED	3000K	300 lm	40 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11364	2x5W LED	3000K	500 lm	40 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11365	2x3W LED	3000K	300 lm	40 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11366	2x5W LED	3000K	500 lm	40 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

WHITE BLACK-GOLD BLACK

Can be used in the bathroom

GRAPHITE BLACK BRASS

Nowodvorski LIGHTING



MARGOT 10504



MARGOT

painted aluminum, glass

10504

1xE14, max 10W only LED

IP54



MARGOT 10503



MARGOT

painted aluminum, glass

10503

2xE14, max 10W only LED

IP54

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9112	2x2W LED	3000K	40 lm	10 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
9113	2x2W LED	3000K	59 lm	10 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h

GRAPHITE



LENS LED 9112



LENS LED

painted aluminum, glass

9112 9113

WHITE BLACK



LENS LED 9113



ASSOS 9123



ASSOS

painted aluminum, glass

9123

1xGU10 R50, max 10W only LED

IP54



ASSOS 9124



ASSOS

painted aluminum, glass

9124

2xGU10 R50, max 10W only LED

IP54



PRIMM 9551



PRIMM

painted aluminum, glass

9551

1xGU10 R50, max 10W only LED

IP54

ARRIS

painted aluminum, glass

9516

1xGU10 R50, max 10W only LED

IP54





ARRIS 9516

NICO

painted aluminum, glass

9518

1xGU10 R50, max 10W only LED

IP54





NICO 9518

NICO

painted aluminum, glass

9517

2xGU10 R50, max 10W only LED

IP54





NICO 9517

BLACK GRAPHITE

SILVER GRAPHITE

FOG 3403





FOG

painted aluminum, glass

3403

1xE27, max 25W only LED

IP44

FOG 3402





FOG

painted aluminum, glass

3402

1xE27, max 25W only LED

IP44

FOG 3404





FOG

painted aluminum, glass

3404

2xE27, max 25W only LED

IP44



NEGRO

painted aluminum, glass

4425

1xGU10 R50, max 10W only LED

IP54



NEGRO 4425



EXE

painted aluminum, glass

8331

1xGU10 R50, max 10W only LED

IP54



EXE 8331



EXE

painted aluminum, glass

8330

2xGU10 R50, max 10W only LED

IP54



EXE 8330

GRAPHITE

GRAY BLACK

Nowodvorski LIGHTING



ROCK PRO 10687



ROCK PRO

painted aluminum, plastic PC

10687

1xE27, max 25W only LED

IP44



ROCK PRO 10686



ROCK PRO

painted aluminum, plastic PC

10686

1xE27, max 25W only LED

IP44



ROCK PRO 10688



ROCK PRO

painted aluminum, plastic PC

10688

2xE27, max 25W only LED

IP44



SIERRA 4422



SIERRA

painted aluminum, plastic PC

4422

2xE27, max 25W only LED

IP54



HEXA 9565



HEXA

painted aluminum, glass

9564 9565

1xGU10 R50, max 10W only LED

IP44



EDESA LED M 9108



EDESA LED M

painted aluminum, glass

9108 9107



EDESA LED S 9111



EDESA LED S

painted aluminum, glass

9111

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9107	7W LED	3000K	530 lm	19°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
9108	7W LED	3000K	530 lm	19°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h
9111	3W LED	3000K	250 lm	30°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	10000h

GRAPHITE BLACK

Can be used in the bathroom

GRAPHITE WHITE BLACK

Nowodvorski LIGHTING

QUARTZ 3411





QUARTZ

painted aluminum, plastic PC

3411

1xE27, max 10W only LED

IP21



CABO LED

painted aluminum, plastic PC

11804 11805



CABO LED 11804



UNIT LED

painted aluminum, glass

9122



UNIT LED 9122

ORINOKO 4387





ORINOKO

painted aluminum, plastic PC

4387

1xE27, max 10W only LED

IP44



BRICK

painted aluminum, glass

3408

1xE27, max 25W only LED

IP65



BRICK 3408

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11804	10W LED	3000K	800 lm	120°	>90	220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11805	10W LED	3000K	900 lm	120°	>90	220/230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
9122	2x5W LED	3000K	727 lm	110°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h

GRAPHITE

SAND GRAPHITE BLACK



OSCAR 11347

OSCAR

painted aluminum

11346 11347

1xGU10 R50, max 15W only LED

IP54





KHUMBU

painted aluminum, glass

4443

1xG9, max 10W only LED

IP44



KHUMBU 4443



MUNO LED

painted aluminum, glass

6776



MUNO LED 6776

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
6776	6W LED	3000K	240 lm	120°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0.5	IP54	8000h

BLACK WHITE

GRAPHITE



PICNIC LED 8177





HANGING SET FOR PICNIC LED

aluminum, steel

8107 8106



PICNIC LED

painted aluminum, plastic PC

8178 8177

Lampa bezprzewodowa, przenośna, zewnętrzna
- Podstawa ładująca w komplecie
- Akumulator litowy 2×2200 mAh
- Czas pełnego ładowania 5-8 h
- Czas pracy 12 h
- Włącznik dotykowy
- Ściemniacz

Wireless lamp, portable, outdoor
- Charging base (set incl.)
- 2×2200 mAh lithium battery
- Full charge time 5-8h
- Work time 12 h
- Touch switch
- Dimmable

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
8177	2.2W LED	3000K	155 lm	46°	≥84	~220-230 V, 50/60 Hz	⧈	IP54	30000h
8178	2.2W LED	3000K	155 lm	46°	≥84	~220-230 V, 50/60 Hz	⧈	IP54	30000h

WHITE GRAPHITE

PICNIC LED 8178



AMY LED 11534



AMY LED 11535



AMY LED 11533



Lampa bezprzewodowa, przenośna, zewnętrzna
- Ładowarka USB C (w zestawie)
- Włącznik dotykowy
- Ściemniacz 10-100%

Wireless lamp, portable, outdoor
- Power adapter USB C (set incl.)
- Touch switch
- Dimmable 10-100%

AMY LED

painted aluminum, plastic PC

11531 11532 11533

11534 11535

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11531	2W LED	3000K	170 lm	45 °	>80	5V	III	IP54	30000h
11532	2W LED	3000K	170 lm	45 °	>80	5V	III	IP54	30000h
11533	2W LED	3000K	170 lm	45 °	>80	5V	III	IP54	30000h
11534	2W LED	3000K	170 lm	45 °	>80	5V	III	IP54	30000h
11535	2W LED	3000K	170 lm	45 °	>80	5V	III	IP54	30000h

WHITE BLACK SAND BRICK RED GREEN

AMY LED 11534



NALA LED 11536

Lampa bezprzewodowa, przenośna, zewnętrzna
- Ładowarka USB C (w zestawie)
- Włącznik dotykowy
- Ściemniacz 10-100%

Wireless lamp, portable, outdoor
- Power adapter USB C (set incl.)
- Touch switch
- Dimmable 10-100%



NALA LED

painted aluminum, plastic PC

■ 11536 □ 11537

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11536	4W LED	2700K	170 lm	45 °	>80	5V		IP54	30000h
11537	4W LED	2700K	170 lm	45 °	>80	5V		IP54	30000h

■ BLACK □ WHITE



MAHE LED 8398



Lampa bezprzewodowa, przenośna, zewnętrzna
- Ładowarka MICRO USB (w zestawie)
- Czas pełnego ładowania 5-7 h
- Czas pracy 9 h
- Włącznik dotykowy
- Ściemniacz

Wireless lamp, portable, outdoor
- Power adapter MICRO USB (set incl.)
- Full charge time 5-7 h
- Work time 9 h
- Touch switch
- Dimmable

MAHE LED

painted aluminum, plastic PC

□ 8397 ■ 8398

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Ingress protection	Lifetime
8397	2.2W LED	3000K	168 lm	46 °	≥ 84	~220-230 V, 50/60 Hz		IP54	25000h
8398	2.2W LED	3000K	168 lm	46 °	≥ 84	~220-230 V, 50/60 Hz		IP54	25000h

□ WHITE ■ BLACK



PUEBLA LED 9513



MERIDA LED 9514



PIX LED 11367



PUEBLA LED

painted aluminum, plastic PC

9513



MERIDA LED

painted aluminum, plastic PC

9514

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9513	12W LED	3000K	540 lm	110°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h
9514	12W LED	3000K	540 lm	110°	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.9	IP54	20000h

GRAPHITE

Can be used in the bathroom



PIX LED

painted aluminum, glass

11367

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11367	10W LED	3000K	500 lm	30°	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

BLACK

Nowodvorski LIGHTING



OUTLINE LED S
11360



OUTLINE LED S

painted aluminum, plastic PC

11360



OUTLINE LED M
11361



OUTLINE LED M

painted aluminum, plastic PC

11361



OUTLINE LED L
11362



OUTLINE LED L

painted aluminum, plastic PC

11362

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11360	20W LED	3000K	1200 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP44	30000h
11361	35W LED	3000K	1800 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP44	30000h
11362	50W LED	3000K	3000 lm	100 °	>80	~220-230 V, 50/60 Hz	⏚	>0.9	IP44	30000h

BLACK



OUTLINE LED S 11360



CLINE LED 11377



ABBY LED 11528



AVA LED 11530





CLINE LED
11377





CLINE LED

painted aluminum, glass

11377

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11377	3W LED	3000K	130 lm	80 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

BLACK



ABBY LED

painted aluminum, plastic PC

11528

cut out ø 58 mm



AVA LED

painted aluminum, plastic PC

11530

cut out ø 58 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
11528	3W LED	3000K	10 lm	20 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h
11530	3W LED	3000K	40 lm	40 °	>80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	30000h

BLACK



BAY LED 8164



BAY LED 8165



SIDEWALK SQUARE LED
8148



SIDEWALK ROUND LED
8147









BAY LED

painted aluminum, plastic PC

8164

BAY LED

painted aluminum, plastic PC

8165

SIDEWALK SQUARE LED

painted aluminum, plastic PC

8148

SIDEWALK ROUND LED

painted aluminum, plastic PC

8147

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8164	3W LED	3000K	200 lm	70 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP65	10000h
8165	5W LED	3000K	360 lm	70 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP65	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8147	3W LED	3000K	100 lm	120 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP54	20000h
8148	3W LED	3000K	100 lm	120 °	≥80	~220-230V V, 50/60 Hz	⏚	>0.5	IP54	20000h

BLACK

BLACK



BASALT 3412



BASALT

painted aluminum, plastic

3412

1xE14, max 10W only LED

IP44



ASSAM 4453



ASSAM

painted aluminum, glass, plastic

4453

1xE27, max 10W only LED

IP65



INA 4907



INA

painted aluminum, glass, plastic

4907

1xE27, max 10W only LED

IP65



STEP LED

painted aluminum, plastic

6907 6908

STEP LED 6907





OIA LED

painted aluminum, plastic

9102 9103

cut out ø 40 mm

OIA LED 9103



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9102 9103	2W LED	3000K	50 lm	50 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP20	10000h
6907	3W LED	3000K	120 lm	92 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP44	10000h
6908	3W LED	3000K	190 lm	92 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP44	10000h

GRAPHITE

GRAPHITE BLACK WHITE

Nowodvorski LIGHTING



BUSH 3401



BUSH

painted aluminum, glass

3401

1xGU10 R50, max 10W only LED

IP65



SPIKE LED S 9101



SPIKE LED S

painted aluminum, glass

9101



SPIKE LED M 9100



SPIKE LED M

painted aluminum, glass, plastic

9100

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9100	5W LED	3000K	300 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP54	10000h
9101	5W LED	3000K	300 lm	30 °	>80	~220-230 V, 50/60 Hz		>0.5	IP54	10000h

BLACK GRAPHITE



RUMI LED 11543





RUMI LED

painted aluminum, plastic PC

11543

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Voltage DC	Safety type	Ingress protection	Lifetime
11543	7W LED	3000K	320 lm	50 °	>90	24V		IP54	30000h

BLACK



PICCO LED S 9106



PICCO LED S

aluminum

9106

cut out ø 38 mm



PICCO LED M 9105



PICCO LED M

aluminum

9105

cut out ø 55 mm



PICCO LED L 9104



PICCO LED L

aluminum

9104

cut out ø 65 mm

PAOLI 9554





PAOLI

steel, glass

9554

1xGU10 R50, max 10W only LED

cut out ø 100 mm

IP67

MON LED 4454





MON LED

aluminum, glass

4454

cut out ø 64 mm

PAT LED 8162





PAT LED

painted aluminum, plastic PC

8162

cut out ø 56 mm

CIRCLET LED 8163





CIRCLET LED

painted aluminum, plastic PC

8163

cut out ø 57 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9106	2W LED	3000K	60 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP67	10000h
9105	2W LED	3000K	80 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP67	10000h
9104	3W LED	3000K	200 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP67	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
4454	2W LED	3000K	100 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	⏚	>0.5	IP67	10000h
8162	3W LED	3000K	12 lm	25 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP65	10000h
8163	3W LED	3000K	120 lm	50 °	≥80	~220-230 V, 50/60 Hz	⏚	>0.5	IP65	10000h

SILVER ■

SILVER ■ BLACK



ANA 10499



ANA 10500





AMELIA 10495



AMELIA 10496















ANA
painted aluminum, plastic PC

10499

1xE27, max 10W only LED

IP44

ANA
painted aluminum, plastic PC

10500

1xE27, max 10W only LED

IP44

ANA
painted aluminum, plastic PC

10501

1xE27, max 10W only LED

IP44

ANA
painted aluminum, plastic PC

10502

1xE27, max 10W only LED

IP44

AMELIA
painted aluminum, plastic PC

10495

1xE27, max 10W only LED

IP44

AMELIA BL
painted aluminum, plastic PC

10496

1xE27, max 10W only LED

IP44

AMELIA
painted aluminum, plastic PC

10497

1xE27, max 10W only LED

IP44

AMELIA
painted aluminum, plastic PC

10498

1xE27, max 10W only LED

IP44

BLACK

BLACK



AMUR 4692



AMUR

painted aluminum, glass

4692

1xE27, max 25W only LED

IP23



AMUR

painted aluminum, glass

4694

1xE27, max 25W only LED

IP44



TAY 5292



TAY

painted aluminum, glass

5292

1xE27, max 25W only LED

IP23



TAY

painted aluminum, glass

5294

1xE27, max 25W only LED

IP23



LANTERN

painted aluminum, plastic PC

6911

1xE27, max 25W only LED

IP23



LANTERN 6911



TYBR

painted aluminum, glass

4686

1xE27, max 25W only LED

IP44



TYBR 4686



DON

painted aluminum, glass

4687

1xE27, max 25W only LED

IP44



DON 4687

BLACK

BLACK WITH A COPPER PATINA

BLACK WITH A GOLDEN PATINA

BLACK WITH A COPPER PATINA

Nowodvorski LIGHTING



NOOK 7976



NOOK

plastic ABS, plastic PC

7972 7976 7978

1xE27, max 10W only LED

IP44



TAHOE II

plastic PC, plastic ABS

10035 10037 10038

2xE27, max 15W only LED

IP44



TAHOE II 10038



TAHOE SENSOR

plastic PC, plastic ABS

10040

2xE27, max 15W only LED

IP44



TAHOE SENSOR 10040

WHITE GOLD PO21 BLACK

WHITE CHROME BLACK

Nowodvorski LIGHTING

FESTOON LIGHTS 9 M 7872

FESTOON LIGHTS 6 M 7873







MAX 2000W MAX 80m CONNECTABLE







POWER CORD FOR FESTOON LIGHTS

rubber cable

7871

IP65

FESTOON LIGHTS 6M

rubber cable

7873

10xE27, max 15W

IP65

FESTOON LIGHTS 9M

rubber cable

7872

15xE27, max 15W

IP65



5 PC SET

BULB LED E27, A60 2W, 5 PC SET

glass

7487

BLACK

Nowodvorski LIGHTING

Light sources and accessories



BULB LED G9, 7W 9197



BULB LED G9, 7W

ceramic housing, plastic PC

☐ 9197 3000K ☐ 10933 4000K



BULB LED G9, 4W 7504



BULB LED G9, 4W

plastic PC

☐ 7503 3000K ☐ 7504 4000K



BULB LENS LED, G9, 3W 9173



BULB LENS LED, G9, 3W

ceramic housing, plastic PC

☐ 9173 3000K ☐ 8447 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9197	7W LED	3000K	750 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
10933	7W LED	4000K	900 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
7503	4W LED	3000K	380 lm	360 °	≥80	~220-230 V, 50/60 Hz	>0.5	25000h
7504	4W LED	4000K	390 lm	360 °	≥80	~220-230 V, 50/60 Hz	>0.5	25000h
9173	3W LED	3000K	330 lm	90 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
8447	3W LED	4000K	310 lm	90 °	>80	~220-230 V, 50/60 Hz	>0.5	25000h

☐ WHITE



REFLECTOR LED, GU10, R35, 4W 10230



REFLECTOR LED, GU10, R35, 4W

plastic PC

☐ 10230 3000K ☐ 10231 4000K



REFLECTOR LED, GU10, R50, 7W 8347



REFLECTOR LED, GU10, R50, 7W

plastic PC

☐ 9180 3000K ☐ 9178 4000K

■ 8348 3000K ■ 8347 4000K

DIMMABLE



REFLECTOR LED, GU10, R50, 7W, DIMMABLE 10995



REFLECTOR LED, GU10, R50, 7W, DIMMABLE

plastic PC

☐ 10996 3000K ☐ 10998 4000K

■ 10995 3000K ■ 10997 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9180	7W LED	3000K	600 lm	50 °	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
9178	7W LED	4000K	600 lm	50 °	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8348	7W LED	3000K	600 lm	50 °	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8347	7W LED	4000K	600 lm	50 °	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
10230	4W LED	3000K	370 lm	70 °	>80	~220-230 V, 50/60 Hz	>0.5	20000h
10231	4W LED	4000K	400 lm	70 °	>80	~220-230 V, 50/60 Hz	>0.5	20000h
10995	7W LED	3000K	600 lm	50 °	>80	~220-230 V, 50/60 Hz	>0.7	25000h
10996	7W LED	3000K	600 lm	50 °	>80	~220-230 V, 50/60 Hz	>0.7	25000h
10997	7W LED	4000K	600 lm	50 °	>80	~220-230 V, 50/60 Hz	>0.7	25000h
10998	7W LED	4000K	600 lm	50 °	>80	~220-230 V, 50/60 Hz	>0.7	25000h

☐ WHITE ■ BLACK

Nowodvorski LIGHTING



BULB GLASS BALL LED, E27, 8W
9177



BULB GLASS BALL LED, E27, 8W

glass

☐ 9177 3000K



BULB LED, E14, T25, 4W
11525



BULB LED E14, T25, 4W

glass

☐ 11525 3000K



BULB LED, GX53, 8W
8378



BULB LED GX53, 8W

plastic PC

☐ 8377 3000K ☐ 8378 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
8377	8W LED	3000K	680 lm	100 °	>80	~220-230 V, 50/60 Hz	>0.5	25000h
8378	8W LED	4000K	700 lm	100 °	>80	~220-230 V, 50/60 Hz	>0.5	25000h
9177	8W LED	3000K	840 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
11525	4W LED	3000K	400 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h

☐ WHITE



REFLECTOR LENS LED, GU10, ES111, 9W
9345



REFLECTOR LENS LED, GU10, ES111, 9W

plastic

■ 9343 3000K ■ 9213 4000K

☐ 9345 3000K ☐ 9214 4000K



REFLECTOR DIFFUSER LED, GU10, ES111, 9W
9211



REFLECTOR DIFFUSER LED, GU10, ES111, 9W

plastic

■ 9342 3000K ■ 9211 4000K

☐ 9344 3000K ☐ 9212 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9343	9W LED	3000K	770 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9213	9W LED	4000K	870 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9345	9W LED	3000K	870 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9214	9W LED	4000K	930 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9342	9W LED	3000K	790 lm	120 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9211	9W LED	4000K	900 lm	120 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9344	9W LED	3000K	790 lm	120 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9212	9W LED	4000K	900 lm	120 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h

☐ WHITE ■ BLACK

Nowodvorski LIGHTING



BULB VINTAGE LED E27, 6W

glass

10596



BULB VINTAGE LED E27, 6W

glass

10594



BULB VINTAGE LED E27, 6W

glass

10593



BULB VINTAGE LED E27, 6W

glass

10595



BULB LED E14, C35, 6W

glass

10589



BULB LED E27, A60, 7W

glass

10587



BULB LED E27, A60, 10W

glass

10588



5 PC SET

BULB LED E27, A60 2W, 5 PC SET

glass

7487

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
10596	6W LED	2200K	580 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
10594	6W LED	2200K	560 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
10593	6W LED	2200K	550 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
10595	6W LED	2200K	450 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
10589	6W LED	3000K	650 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
10587	7W LED	3000K	800 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
10588	10W LED	3000K	1100 lm	360 °	≥ 80	~220-230 V, 50/60 Hz	>0.5	15000h
7487	2W LED	2200K	160 lm	360 °	≥80	~220-230 V, 50/60 Hz	>0.5	15000h



TUBE LED T8, 11W

glass

☐ 7500



TUBE LED T8, 16W

glass

☐ 7501



TUBE LED T8, 22W

glass

☐ 7502

Item No.	Power	Colour temp.	Leds	Luminous flux	Beam angle	Colour Rendering Index (CRI ≥)	Input	Power factor	Lifetime
7500	11W LED	3000K	SMD2835	1700 lm	120°	≥80	~220-230 V, 50/60 Hz	>0.5	30000h
7501	16W LED	3000K	SMD2835	2300 lm	120°	≥80	~220-230 V, 50/60 Hz	>0.5	30000h
7502	22W LED	3000K	SMD2835	3200 lm	120°	≥80	~220-230 V, 50/60 Hz	>0.5	30000h





WATERPROOF CONNECTOR IP68

plastic PA

■ 8845

IP68





WATERPROOF „Y" CONNECTOR IP68

plastic PA

■ 8846

IP68





MICROWAVE SENSOR

plastic

☐ 8821





48V DC, 80W, POWER SUPPLY

plastic

11301





48V DC, 200W, POWER SUPPLY

plastic

11287





48V DC, 320W, POWER SUPPLY

plastic

11278





24V DC, 150W, POWER SUPPLY

plastic

11874





24V DC, 75W, POWER SUPPLY

plastic

11875



HONEY COMB

aluminum, plastic PA

■ 11427





Filtr przeciwolśnieniowy "plaster miodu".
Do zastosowania z kolekcją lamp MONO.

Anti-glare "honeycomb".
For use with the MONO lamp collection.

ACROBAT

painted steel

■ 11794 □ 11795

▒ 11796 ▓ 11797





BALLERINA

painted steel

■ 11798 □ 11800

▒ 11801 ▓ 11802





■ BLACK P013 RAL 9005 □ WHITE P004 RAL 9003 ▒ SILK GRAY P026 RAL 7044 ▓ UMBRA GRAYP027 RAL 7022

INFORMACJE DLA KLIENTA / CUSTOMER INFORMATION

Informacje ogólne / General information

Rzeczywiste parametry produktów mogą się różnić od wartości deklarowanych w katalogu o +/- 10%.

Zdjęcia prezentowanego asortymentu w niniejszym katalogu mają charakter poglądowy.
Rzeczywisty kolor produktów może nieznacznie odbiegać od prezentowanego na zdjęciach, ze względu na technologię druku.

The actual product parameters may differ from the values declared in the catalogue by +/- 10%.

Photos in this catalogue are for illustrative purposes only.
The actual color of the products may slightly differ from that shown in the photos, due to the printing technology.

Informacje techniczne / Technical information

Temperatura barwowa (K) - w potocznym rozumieniu, to „kolor" światła białego emitowanego przez źródło, np. źródło LED.
W uproszczeniu możemy podzielić je na światło o:
· barwie ciepłej
· barwie neutralnej
· barwie zimnej

Colour temperature (K) in common understanding is the colour of white light emitted by a source, for example such as an LED source.
In simple terms, we can divide them into:
· Warm white
· White
· Cool white



Strumień świetlny (lm/lumen) - w potocznym rozumieniu, to całkowita moc światła emitowanego z danego źródła światła.
Lumen (lm) – jednostka miary strumienia świetlnego w układzie SI
1 lm = 1 cd·sr

Luminous flux (lm / lumen) - the total power of light emitted from a light source.
Lumen (symbol: lm) - the unit of luminous flux in SI system.
1 lm = 1 cd·sr

Natężenie oświetlenia (lx/luks) – w potocznym rozumieniu, to gęstość strumienia świetlnego padającego na daną powierzchnię.
Luks (lx) – jednostka natężenia oświetlenia w układzie SI.
1 lx = 1 cd·sr / m^2

Illuminance (lx / lux) - in common understanding, it is the density of the luminous flux incident on a given surface.
Lux (lx) - a unit of illuminance in the SI system.
1 lx = 1 cd sr / m^2

CRI (od ang. colour rendering index), Ra – wskaźnik oddawania barw charakteryzujący źródło światła, który określa, jak dobrze postrzegane są barwy oświetlonych przedmiotów.
Im wskaźnik ten jest wyższy, tym barwy są lepiej oddawane, a oświetlane przedmioty wyglądają naturalniej.
Wyrażony jest liczbą z przedziału od 0 do 100, gdzie 100 to światło słoneczne.
Minimum wg przepisów w UE dla opraw wewnętrznych to 80.

CRI- is an index of a light source's ability to reveal colours. It determines how well illuminated colours are perceived.
The higher index, the better colour rendering and the illuminated objects look more natural.
It is expressed with a number from 0 to 100, where 100 is a sunlight.
The minimum according to EU regulations for indoor luminaires is 80.

Stopień ochrony IP / Degree of protection IP

Stopień ochrony jest wyrażony dwoma cyframi. Pierwsza oznacza ochronę przed ciałami stałymi. Druga to ochrona przed cieczami.

Degree of protection is expressed by two figures. The first one stands for protection against solid particles. The second one stands for protection against liquids.

1 cyfra / 1st figure	
IP0...	Brak ochrony / Not protected
IP1...	Ochrona przed ciałami stałymi większymi niż 50 mm / Protected against solid objects greater than 50 mm
IP2...	Ochrona przed ciałami stałymi większymi niż 12 mm / Protected against solid objects greater than 12 mm
IP3...	Ochrona przed ciałami stałymi większymi niż 2,5 mm / Protected against solid objects greater than 2,5 mm
IP4...	Ochrona przed ciałami stałymi większymi niż 1 mm / Protected against solid objects greater than 1 mm
IP5...	Ochrona przed pyłem / Protected against dust infiltration
IP6...	Ochrona pyłoszczelna / Totally protected against dust infiltration

2 cyfra / 2nd figure	
IP...0	Brak ochrony / Not protected
IP...1	Ochrona przed padającymi kroplami wody / Protected against vertically falling water drops
IP...2	Ochrona przed padającymi kroplami wody przy wychyleniu do 15° / Protected against falling water drops up to 15° from the vertica
IP...3	Ochrona przed natryskiwaną wodą / Protected against rain
IP...4	Ochrona przed bryzgami wody / Protected against splashing water
IP...5	Ochrona przed strugami wody / Protected against water jets
IP...6	Ochrona przed falami / Protected against powered water jets
IP...7	Ochrona przed zanurzeniem / Protected against temporary immersion
IP...8	Ochrona przed głębokim zanurzeniem / Protected against continuous immersion

IKONY / ICONS


Lampa wisząca /
Pendant lamp


Kinkiet /
Wall lamp


Kinkiet podtynkowy /
Recessed wall lamp


Lampa sufitowa /
Ceiling lamp


Oświetlenie punktowe /
Spotlight


Źródło światła /
Light source


Lampa biurkowa /
Table lamp


Podtynkowa lampa sufitowa /
Reccessed ceiling lamp

Tuba ledowa /
Led tube


Lampa podłogowa /
Floor lamp


Lampa najazdowa /
Overrun lamp


Wyciąć /
Cut out


Oprawy oznaczone tym symbolem nie wolno okrywać materiałem termoizolacyjnym.
Fittings marked with this symbol must not be covered with thermal insulation materials.


Klasa ochronna druga oznacza, że oprawa posiada podwójną izolację ochronną, a przewód ochronny (żyła żółto-zielona) nie może być podłączony do oprawy oświetleniowej.
Protection class II means that the fittings are equipped with a double protective insulation, and the green and yellow protective conductor must not be connected to the fitting.


Klasa ochronna pierwsza oznacza, że oprawa musi być podłączona za pomocą przewodu ochronnego (żyła żółto-zielona) do przewodu lub zacisku uziemiającego.
Protection class I means that the fitting must be connected with the yellow and green protective conductor to the grounding wire or terminal.


Klasa ochronna III oznacza, bezpieczeństwo elektryczne gwarantowane przez bardzo niskie zasilanie (poniżej 50 V). Bez uziemienia.
Protection class III means, that electrical safety is guaranteed by a very low power supply (less than 50 Volt). No grounding.


Oprawy oznaczone tym symbolem wolno instalować wyłącznie na podłożach niepalnych.
Fittings marked with this symbol are suitable for installation only on nonflammable surfaces.


Zgodność produktów z ukraińskimi normami.
Ukrainian standards compliant.


Zgodność z normami Unii Europejskiej.
EU standards compliant.


Zgodność produktów z normami Euroazjatyckiej Unii Gospodarczej.
EAEU standards compliant.


Do użytku zewnętrznego.
Exterior use only.


Do wewnętrznego użytku.
Interior use only.


Do stosowania wewnątrz i na zewnątrz.
Interior and exterior use.


Zużyte oprawy oświetleniowe są surowcami wtórnymi – nie wolno wyrzucać ich do pojemników na odpady domowe, mogą zawierać substancje niebezpieczne dla zdrowia i życia ludzkiego oraz środowiska. Zgodnie z dyrektywą WEEE 2012/19/UE użytkownik zobowiązany jest do oddania opraw do punktu zbierania zużytego sprzętu, co przyczyni się do ochrony środowiska naturalnego.
Used lighting fixtures are recyclable materials - they must not be disposed of in household waste containers as they may contain substances hazardous to human health or life as well as to the natural environment. In accordance with Regulation WEEE 2012/19 /EU, luminaire user is obliged to return a used lighting fixture to a waste appliance collection point, which will contribute to the protection of the natural environment.

Material	Materiał
Acrylic crystals	Kryształki akrylowe
Aluminum	Aluminium
Braided cable	Przewód w oplocie
Brass plated steel	Stal mosiądzowana
Brushed stainless steel	Stal nierdzewna szczotkowana
Ceramic housing	Ceramiczna oprawka
Chrome	Chrom
Chrome plated steel	Stal chromowana
Composite	Kompozyt
Concrete	Beton architektoniczny
Copper plated steel	Stal miedziowana
Crystal	Kryształ
Fabric	Tkanina
Flexible stem	Peszel
Glass	Szkło
Gypsum	Gips
Metallized glass	Szkło metalizowane
Painted aluminum	Aluminium lakierowane
Painted steel	Stal lakierowana
Plastic	Tworzywo sztuczne
Plastic ABS	Tworzywo sztuczne ABS
Plastic PA	Tworzywo sztuczne PA
Plastic PC	Tworzywo sztuczne PC
Plastic PP	Tworzywo sztuczne PP
Plastic PS	Tworzywo sztuczne PS
Plastic PC/ABS	Tworzywo sztuczne PC/ABS
Plastic PE	Tworzywo sztuczne PE
Plastic PMMA	Tworzywo sztuczne PMMA
Plywood	Sklejka
Rubber cable	Przewód gumowy
Silicone	Silikon
Solid brass	Lity mosiądz
Steel	Stal
Velvet	Aksamit
Wood	Drewno

KODY KOLORÓW / COLOUR CODES



P001 / RAL 9003

P003 / RAL 9003

P004 / RAL 9003



P005



P010 / RAL 7016



P013 / RAL 9005



P014 / RAL 9005



P015



P018



P020



P021



P022



P023



P024



P025



P026 / RAL 7044



P027 / RAL 7022



P028



P029



P030



P031



P032



P033



P034



P035



T003

T004

T005



T008



T011



T012



T013



T022



T023



T024



T025



T026



T029

T032



T033



T034



T035



T036



T037



T038



T039

A

ABBY LED ... 561
ABI L ... 243
ACRE ... 487
ACROBAT ... 589
AGAVE ... 467
AGNES ROUND LED PRO ... 492
AGNES SQUARE LED PRO ... 493
ALICE ... 190
ALICE L ... 190, 191
ALOE ... 466
ALPHA ... 481
AMALFI ... 143
AMALFI L ... 143
AMALFI M ... 143
AMARELA ... 157
AMARELA A ... 156
AMARELA B ... 156
AMARELA L ... 155
AMARELA M ... 154, 155
AMARELA S ... 154
AMELIA ... 571
AMUR ... 572
AMY LED ... 552
ANA ... 570
ARALIA ... 467
ARENA ... 316
ARENA LED ... 316
ARENA SENSOR ... 316
ARES ... 296
ARIA LED L ... 535
ARIA LED M ... 535
ARIA LED S ... 535
ARIA LED XL ... 535
ARM LED L ... 48
ARM LED M ... 48
ARRIS ... 541
ASSAM ... 564
ASSOS ... 540
AVA LED ... 561

B

BAHIA ... 487
BALLERINA ... 589
BAR LED L ... 41
BAR LED M ... 41
BAR LED S ... 40
BASALT ... 564
BATON ... 99
BAY LED ... 562
BERGEN ... 269
BIT S ... 339
BOHO L ... 235
BOHO M ... 235
BOHO S ... 235
BOL ... 481
BRAVO ... 480
BRAZOS ... 472,473
BRICK ... 547
BULB LED E27, A60, 10W ... 585
BULB LED E27, A60, 7W ... 585
BULB GLASS BALL LED, E27, 8W ... 582
BULB LED E14, C35, 6W ... 585
BULB LED E14, T25, 4W ... 582
BULB LED E27, A60 2W, 5 PC SET ... 585
BULB LED G9, 4W ... 580
BULB LED G9, 7W ... 580
BULB LED GX53, 8W ... 582
BULB LENS LED, G9, 3W ... 580
BULB VINTAGE LED E27, 6W ... 584
BUSH ... 566

C

CABO LED ... 547
CADILAC ... 180, 181
CAMELEON ADAPTER CTLS ... 435
CAMELEON ADAPTER PROFILE ... 455
CAMERON ... 184, 185
CANOE ... 294
CAYO ... 475
CEARA ... 478
CEDRO ... 163
CEDRO A ... 162
CEDRO B ... 162
CEDRO L ... 160, 161
CEDRO M ... 160, 161
CEDRO S ... 160, 161
CERAMIC LED ... 138, 139
CEZANNE LED L ... 491
CEZANNE LED M ... 491
CEZANNE LED S ... 491
CHARLIE ... 484
CHILLIN ... 198
CIRCLET LED ... 569
CIRCOLO LED ... 25, 26, 27
CIRCOLO LED M ... 24, 29, 32
CIRCOLO LED S ... 24, 29, 32
CIRCOLO LED XS ... 29
CIRCOLO POWER LED ... 25, 26
CL DIA LED 18W ... 348
CL DIA LED 30W ... 348
CL IOS LED 20W, ANGLE 36 ... 332
CL IOS LED 20W, ANGLE 60 ... 332
CL IOS LED 30W, ANGLE 36 ... 333
CL IOS LED 30W, ANGLE 60 ... 333
CL IOS LED 40W, ANGLE 60 ... 333
CL KEA LED 20W ... 349
CL KEA LED 40W ... 349
CL KOS LED 10W ... 346
CL KOS LED 16W ... 346
CL KOS LED 24W ... 346
CL KOS LED 8W ... 346
CL OFFICE LED PRO 120 ... 306
CL OFFICE LED PRO 150 ... 307
CL OFFICE PRO/HALL PRO POWER SUPPLY KIT ... 306, 307
CL OFFICE PRO/HALL PRO SUSPENSION KIT ... 306, 307
CLAY M ... 141
CLAY S ... 141
CLINE LED ... 560
COBBLE ... 322
COMMA LED L ... 275
COMMA LED M ... 275
COMMA LED S ... 275
CRAFT ... 287
CRATE ... 282
CRES ... 340
CRISTAL ... 133
CRISTAL L ... 133
CRISTAL M ... 132
CTLS DEAD END CAP ... 439
CTLS MILO LED 15W ... 426
CTLS MILO LED 25W ... 427
CTLS MONO ... 435
CTLS NEA LED 20W ... 428
CTLS NEA LED 30W ... 429
CTLS NEA LED 40W ... 430
CTLS POWER END CAP, LEFT (PE-L) ... 438
CTLS POWER END CAP, RIGHT (PE-R) ... 438
CTLS POWER FLEX CONNECTOR ... 439
CTLS POWER L CONNECTOR, LEFT (L-L) ... 438
CTLS POWER L CONNECTOR, RIGHT (L-R) ... 438
CTLS POWER STRAIGHT CONNECTOR ... 438
CTLS POWER SUPPLY KIT 3 CIRCUIT ... 437
CTLS POWER T CONNECTOR, LEFT 1 (T-L1) ... 439
CTLS POWER T CONNECTOR, LEFT 2 (T-L2) ... 439
CTLS POWER T CONNECTOR, RIGHT 1 (T-R1) ... 439
CTLS POWER T CONNECTOR, RIGHT 2 (T-R2) ... 439
CTLS POWER X CONNECTOR ... 439
CTLS RECESSED DEAD END CAP ... 443
CTLS RECESSED FIXING SET ... 443
CTLS RECESSED POWER END CAP, LEFT (PE-L) ... 442
CTLS RECESSED POWER END CAP, RIGHT (PE-R) ... 442
CTLS RECESSED POWER FLEX CONNECTOR ... 443
CTLS RECESSED POWER L CONNECTOR, LEFT (L-L) ... 442
CTLS RECESSED POWER L CONNECTOR, RIGHT (L-R) ... 442
CTLS RECESSED POWER STRAIGHT CONNECTOR ... 442
CTLS RECESSED POWER T CONNECTOR, LEFT 1 (T-L1) ... 443
CTLS RECESSED POWER T CONNECTOR, LEFT 2 (T-L2) ... 443
CTLS RECESSED POWER T CONNECTOR, RIGHT 1 (T-R1) ... 443
CTLS RECESSED POWER T CONNECTOR, RIGHT 2 (T-R2) ... 443
CTLS RECESSED POWER X CONNECTOR ... 443
CTLS RECESSED TRACK 3 CIRCUIT 1M ... 440
CTLS RECESSED TRACK 3 CIRCUIT 2M ... 440
CTLS SNOWBALL ... 434
CTLS STRAIGHT CONNECTOR MINI ... 439
CTLS SUSPENSION KIT 3 CIRCUIT ... 437
CTLS TINOS LED 10W ... 432
CTLS TINOS LED 20W ... 432
CTLS TINOS LED 30W ... 433
CTLS TRACK 3 CIRCUIT 1M ... 436
CTLS TRACK 3 CIRCUIT 2M ... 436
CUMULUS CUBE L ... 502
CUMULUS CUBE M ... 502
CUMULUS L ... 498, 499
CUMULUS M ... 498, 499
CUMULUS S ... 498, 499
CUMULUS XL ... 498
CUP ... 343
CUP 3 PC SET ... 343
CYLINDER L ... 100
CYLINDER M ... 100

D

DELTA ... 484
DEMI LED L ... 533
DEMI LED M ... 533
DISK ... 218
DON ... 573
DOT ... 353
DOVER ... 226, 227
DOWNLIGHT ES111 ... 351
DROPS WOOD A ... 205
DROPS WOOD B ... 205
DROPS WOOD C ... 202
DROPS WOOD D ... 202
DROPS WOOD E ... 203
DROPS WOOD F ... 203

E

EASY LED LEFT ... 46
EASY LED RIGHT ... 46
ECHO ... 485
EDESA LED M ... 545
EDESA LED S ... 545
EGG L ... 295
EGG M ... 295
EGG XL ... 295

EGINA LED 10W ... 345
EGINA LED 15W ... 345
EGINA LED 5W ... 345
ELLIPSES LED ... 536
EXE ... 543
EYE ... 97, 102
EYE FLEX ... 103
EYE FLEX S ... 103
EYE L ... 96, 98, 101
EYE M ... 96, 101
EYE MOD ... 352
EYE S ... 101
EYE SPOT ... 104, 105
EYE SUPER ... 106-109
EYE SUPER A ... 107
EYE SUPER B ... 107
EYE TONE ... 337, 338
EYE WALL ... 102
EYE WALL CUT ... 102

F

FALCON ... 189
FESTOON LIGHTS 6m ... 577
FESTOON LIGHTS 9m ... 577
FLEA ... 335
FLOWERPOT L ... 500
FLOWERPOT M ... 500
FLOWERPOT S ... 500
FOCUS MINI LED ... 330
FOG ... 542
FORM L ... 183
FORM M ... 183
FOURTY ... 70, 71, 74, 76, 77
FOURTY L ... 72
FOURTY M ... 72,73
FOURTY S ... 72,73
FOURTY SURFACE ... 76
FOURTY WALL M ... 74
FOURTY WALL S ... 74
FOURTY WALL XL ... 75
FOURTY XL ... 72
FOXTROT ... 482

G

GAP ... 322
GARRET ... 289
GARRET M ... 289
GARRET S ... 289
GIAVELLOTTO LED L ... 37
GIAVELLOTTO LED M ... 37
GIAVELLOTTO LED S ... 37
GIOTTO LED M ... 297
GIOTTO LED S ... 297
GLOBE PLUS ... 123
GLOBE PLUS M ... 123
GLOBE PLUS S ... 123
GOLF ... 485
GROOVE ... 322, 323

H

HAGA ... 269
HAITI L ... 234
HAITI M ... 234
HAITI S ... 234
HALO ... 334
HAMPTON ... 134
HANGING SET FOR PICNIC LED ... 550
HARMONY ... 284
HAVANA L ... 232, 233
HAVANA M ... 232, 233
HAVANA S ... 232, 233
HEFT ... 219
HELIOS LED ... 486
HEMISPHERE HIT L ... 292
HEMISPHERE HIT S ... 292
HEMISPHERE RUST L ... 290
HEMISPHERE RUST S ... 290
HEMISPHERE SUPER L ... 291, 293
HEMISPHERE SUPER S ... 291, 293
HERMANOS ... 261
HERMANOS A ... 260
HERMANOS B ... 260
HERMANOS C ... 260
HEXA ... 545
HIGH-BAY ... 288
HONEY COMB ... 589
HORN ... 522
HOTEL MOOD ... 192, 194
HOTEL MOOD LED ... 192
HOTEL PLUS ... 196
HVAR ... 341

I

ICE BALL ... 466
ICE EGG A ... 474
ICE EGG C ... 474
ICE TUBE LED M ... 470, 471
ICE TUBE LED S ... 470, 471
IDA ... 511
IKA A ... 223
IKA D ... 223
IMBRIA ... 112
IMPULSE LED L ... 52
IMPULSE LED M ... 52
IMPULSE LED S ... 53
INA ... 564
INDIA ... 335
ION LED L ... 305
ION LED M ... 305
IRIS LED ... 299
ISLA LED ... 532

J

JAPANDI M ... 236
JAPANDI S ... 236
JULIET ... 486

K

KARO ... 116, 117
KASAI ... 317
KHUMBU ... 549
KIER L ... 121
KIER M ... 121
KIER S ... 121
KRABI ... 237
KYMI A ... 222
KYMI B ... 222
KYMI C ... 222

L

LAGO ... 169
LAGO A ... 168
LAGO B ... 168
LAGO L ... 166, 167
LAGO M ... 166, 167
LAGO S ... 166, 167
LAGUNA ... 179
LANTERN ... 573
LASER 1000 ... 61, 62, 63
LASER 490 ... 60, 62, 63
LASER 750 ... 62, 63, 64
LASER 900 ... 64
LASER WALL ... 67
LASER WALL L ... 66
LATH LED ... 489
LENS LED ... 539
LHOTSE LED ... 513
LIA LED ... 299
LID ROUND LED 15W ... 313
LID ROUND LED 25W ... 313
LID ROUND LED 35W ... 313
LID ROUND LED 50W ... 313
LID SQUARE LED 15W ... 314
LID SQUARE LED 25W ... 314
LID SQUARE LED 35W ... 314
LID SQUARE LED 50W ... 314
LINEO LED ... 34
LIV LED ... 509
LUKSOR S ... 243
LUSSO ... 199
LUXORA LED ... 130, 131
LVM 48V, 150W, INSIDE POWER SUPPLY ... 418, 422
LVM CORNER CONDUCTIV ... 422
LVM CORNER CONDUCTIVE MODULE ... 419
LVM FOCUS LED 15W ... 400
LVM FOCUS LED 9W ... 401
LVM FOCUS OUT LED 15W ... 402
LVM FOCUS OUT LED 9W ... 403
LVM HORIZONTAL CORNER ... 419
LVM INSIDE CORNER ... 419
LVM LID LED 8W ... 410
LVM LINE LED 15W ... 404
LVM LINE LED 9W ... 405
LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE 419, 422
LVM POWER SUPPLY KIT ... 417
LVM RECESSED HORIZONTAL CORNER ... 423
LVM RECESSED INSIDE CORNER ... 423
LVM RECESSED TRACK 1M ... 420
LVM RECESSED TRACK 2M ... 420
LVM ROLLER LED 9W ... 408
LVM SLOT LED 5W ... 411
LVM SLOT LED 8W ... 411
LVM SPOT LED 15W ... 406
LVM SPOT LED 9W ... 407
LVM STRAIGHT CONDUCTIVE MODULE ... 419, 422
LVM SUSPENSION KIT ... 417
LVM TRACK 1M ... 416
LVM TRACK 2M ... 416
LVM TRACK BUCKLE CONNECTOR ... 419, 422

M

MAHE LED ... 555
MALAKKA LED ... 477
MALMO ... 269
MARGOT ... 538
MAUN ... 481
MEKONG ... 526
MERIDA LED ... 556
MIA LED L ... 510
MIA LED M ... 510
MICROWAVE SENSOR ... 587
MIDI LED ... 324, 325
MIDI LED RECESSED ... 326
MINI LED RECESSED ... 329

MINIMAL ... 228
MIST ... 182
MISTRAL ... 527
MLJET ... 340
MOD ... 350
MOD PLUS ... 350
MON LED ... 569
MONACO ... 144, 145
MONO ... 82, 83, 86, 89, 94, 95
MONO 2x150 ... 86
MONO 2x200 ... 86
MONO CORNER 2x150 ... 87
MONO CORNER 2x200 ... 87
MONO DEEP ... 92
MONO LONG ... 88
MONO LONG M ... 88
MONO S ... 81
MONO SLIDE ... 93
MONO SLIDE TRIMLESS ... 93
MONO SURFACE ... 90, 91
MONTERREY LED ... 516
MORE EYE ... 110
MORE TONE ... 111
MOSS ... 197
MOTIVE LED L ... 42
MOTIVE LED M ... 42
MULTI LED ... 308
MUNO LED ... 549
MURTER ... 340
MYKONOS LED 10W ... 344
MYKONOS LED 15W ... 344
MYKONOS LED 18W ... 344
MYKONOS LED 24W ... 344
MYKONOS LED 6W ... 344

N

NALA LED ... 554
NANO - LVM CORNER CONDUCTIVE MODULE ... 375, 378
NANO - LVM CURVE TRACK R400 ... 372
NANO - LVM FLEX LINE LED 6W ... 365
NANO - LVM FOCUS OUT LED 10W ... 360
NANO - LVM FOCUS OUT LED 5W ... 361
NANO - LVM HORIZONTAL CORNER ... 375
NANO - LVM INSIDE CORNER ... 375
NANO - LVM LINE IN LED 6W ... 364
NANO - LVM LINE OUT LED 10W ... 363
NANO - LVM LINE OUT LED 20W ... 362
NANO - LVM MUG LED 7W ... 367
NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE ... 375, 378
NANO - LVM OUTSIDE POWER SUPPLY CONDUCTIVE MODULE FOR SUSPENSION TRACK ... 373
NANO - LVM RECESSED HORIZONTAL CORNER ... 378
NANO - LVM RECESSED INSIDE CORNER ... 378
NANO - LVM RECESSED OUTSIDE POWER SUPPLY CONDUCTIVE MODULE FOR SUSPENSION TRACK ... 373
NANO - LVM RECESSED TRACK 1M ... 376
NANO - LVM RECESSED TRACK 2M ... 376
NANO - LVM SPOT LED 1W ... 366
NANO - LVM SPOT ZOOM LED 15W ... 369
NANO - LVM SPOT ZOOM LED 2W ... 368
NANO - LVM SPOT ZOOM LED 5W ... 368
NANO - LVM SPOT ZOOM LED 7W ... 369
NANO - LVM STRAIGHT CONDUCTIVE MODULE ... 375, 378
NANO - LVM SUSPENSION KIT ... 373
NANO - LVM TRACK 1M ... 372
NANO - LVM TRACK 2M ... 372
NANO - LVM TRACK BUCKLE CONNECTOR ... 375, 379
NATALIE ... 469
NEGRO ... 543
NEL LED ... 530
NESS ... 242
NEWPORT ... 135
NICO ... 541
NIKKI ROUND LED ... 310
NOOK ... 574
NORIN ... 522

O

OIA LED ... 565
OIR ... 525
ORBIT ... 263, 264, 265
ORGANIC ... 298
ORINOKO ... 546
ORLA LED M ... 531
ORLA LED S ... 531
ORTO ... 58
ORTO A ... 59
ORTO B ... 59
OSCAR ... 548
OSLO 30 ... 228
OSLO LED 90 ... 229
OTTAWA ... 520
OUTLINE LED L ... 558
OUTLINE LED M ... 558
OUTLINE LED S ... 558
OVAL ... 323

P

PAG ... 322
PALMAS LED ... 479
PAN LED M ... 477
PAN LED S ... 477
PANTOGRAPH ... 286
PAOLI ... 569
PARANA ... 480
PAT LED ... 569
PATHWAY FOUNDATION KIT ... 528
PATHWAY LED L ... 529
PATHWAY LED M ... 529
PATHWAY LED PRO ... 528
PATHWAY LED S ... 529
PATIO ... 503
PEAR ... 127
PEAR L ... 126
PEAR M ... 126
PEAR S ... 126
PICASSO LED ... 489
PICCO LED L ... 568
PICCO LED M ... 568
PICCO LED S ... 568
PICNIC LED ... 550
PIK ... 122
PILLS ... 266, 267
PIN LED L ... 488
PIN LED M ... 488
PIN LED S ... 488
PIX LED ... 557
PLANT ... 283
POINT DUO ... 248
POINT PLEXI L ... 339
POINT PLEXI M ... 339
POINT S ... 339
POINT TONE ... 334
POLARIS ... 142
POLE LED ... 518
POWER CORD FOR FESTOON LIGHTS ... 577
POWER SUPPLY COVER ... 375
POWER SUPPLY, 24V DC, 150W ... 588
POWER SUPPLY, 24V DC, 75W ... 588
POWER SUPPLY, 48V DC, 200W ... 588
POWER SUPPLY, 48V DC, 320W ... 588
POWER SUPPLY, 48V DC, 80W ... 588
PRIMM ... 540
PROFILE BIT ... 453
PROFILE BIT PLUS ... 453
PROFILE DEAD END CAP ... 459
PROFILE EYE ... 453
PROFILE EYE SPOT ... 454
PROFILE EYE SUPER A ... 452
PROFILE EYE SUPER C ... 452
PROFILE FLEX CONNECTOR ... 459
PROFILE FOCUS LED ... 450
PROFILE INDIA ... 450
PROFILE IRIS LED 12W ... 448
PROFILE IRIS LED 20W ... 449
PROFILE IRIS LED 7W ... 448
PROFILE L CONNECTOR ... 459
PROFILE MIKE ... 450
PROFILE MONO ... 454
PROFILE POWER END CAP ... 458
PROFILE POWER STRAIGHT CONNECTOR ... 458
PROFILE POWER SUPPLY KIT ... 457
PROFILE PUCK ... 454
PROFILE RECESSED DEAD END CAP ... 463
PROFILE RECESSED FIXING SET ... 463
PROFILE RECESSED FLEX CONNECTOR ... 463
PROFILE RECESSED L CONNECTOR ... 463
PROFILE RECESSED POWER END CAP ... 462
PROFILE RECESSED POWER STRAIGHT CONNECTOR ... 462
PROFILE RECESSED STRAIGHT CONNECTOR ... 463
PROFILE RECESSED T CONNECTOR ... 463
PROFILE RECESSED TRACK 1 METER ... 460
PROFILE RECESSED TRACK 2 METERS ... 460
PROFILE RECESSED X CONNECTOR ... 463
PROFILE SNOWBALL ... 452, 455
PROFILE STRAIGHT CONNECTOR ... 459
PROFILE SUSPENSION KIT ... 457
PROFILE T CONNECTOR ... 459
PROFILE TINOS LED 10W ... 446
PROFILE TINOS LED 20W ... 447
PROFILE TINOS LED 30W ... 447
PROFILE TINOS LED 7W ... 446
PROFILE TRACK 1 M ... 456
PROFILE TRACK 2 M ... 456
PROFILE VESPA ... 455
PROFILE X CONNECTOR ... 459
PROFILE ZOOM LED ... 451
PUEBLA LED ... 556
PUKET L ... 231
PUKET M ... 231
PUKET S ... 231
PUMPKIN L ... 241
PUMPKIN M ... 241
PUMPKIN S ... 240

Q

QUARTZ ... 546

R

RADIUS ... 276
RATTAN L ... 230
RATTAN M ... 230
RATTAN S ... 230
REFLECTOR DIFFUSER LED, GU10, ES111, 9W ... 583
REFLECTOR LED, GU10, R35, 4W ... 581
REFLECTOR LED, GU10, R50, 7W ... 581

REFLECTOR LED, GU10, R50, 7W, DIMMABLE ... 581
REFLECTOR LENS LED, GU10, ES111, 9W ... 583
RING LED L ... 272, 273
RING LED M ... 272, 273
RING LED S ... 272, 273
RING MIRROR LED L ... 271
RING MIRROR LED M ... 271
RING MIRROR LED S ... 271
RING TIMBER LED L ... 212
RING TIMBER LED M ... 212
RING TIMBER LED S ... 212
RING TIMBER LED XL ... 212
RING TIMBER LED XXL ... 212
RING WOOD LED L ... 216
RING WOOD LED M ... 216
RING WOOD LED S ... 216
RIO ... 524
RIO SENSOR ... 524, 525
ROCK PRO ... 544
RUBY LED ... 508
RUMI LED ... 567

S

SABER LED L ... 45
SABER LED M ... 44
SANTANA ... 153
SANTANA L ... 151
SANTANA M ... 150, 151
SANTANA A ... 152
SANTANA B ... 152
SANTANA S ... 150
SATELLITE L ... 259
SATELLITE M ... 258, 259
SATELLITE S ... 258, 259
SATELLITE S SENSOR ... 259
SEMI LED ... 537
SEMI LED M ... 537
SET ... 336, 585
SHINE ... 341
SIDEWALK ROUND LED ... 563
SIDEWALK SQUARE LED ... 563
SIERRA ... 544
SILBA ... 340
SILICONE ... 279
SIMI ... 473
SIMONE ... 246
SIS ... 475
SLASH LED ... 49
SLIM LED ... 513
SLING ... 113
SLIT LED ... 512
SMART LED ... 319
SNOWBALL ... 120
SOFT CEILING LED 120X6 ... 304
SOFT CEILING LED 60X20 ... 304
SOFT CEILING LED 60X6 ... 304
SOFT CEILING LED 60X60 ... 304
SOFT CEILING LED 90X20 ... 304
SOFT CEILING LED 90X6 ... 304
SOFT LED 120X6 ... 303
SOFT LED 90X6 ... 303
SOFT WALL LED 60X6 ... 302
SOFT WALL LED 90X6 ... 302
SOLTA ... 341
SOUL ... 521
SPHERE ... 125
SPHERE L ... 124
SPHERE M ... 124
SPHERE S ... 124
SPHERE XL ... 124
SPIDER ... 280
SPIKE LED M ... 566
SPIKE LED S ... 566
SPIN LED L ... 51
SPIN LED M ... 51
SPIN LED S ... 51
STALACTITE ... 65
STAR ... 503
STEP LED ... 565
STONE L ... 496
STONE M ... 496
STONE S ... 496
STRAIGHT CEILING LED S ... 300
STRAIGHT CEILING LED L ... 300
STRAIGHT CEILING LED M ... 300
STRAIGHT WALL LED L ... 301
STRAIGHT WALL LED M ... 301
STRAIGHT WALL LED S ... 301
STRAIGHT WALL XS ... 301
STRUCTURE LED ... 514
SUN LED ... 211
SUNRISE LED ... 210
SUNSET ... 211
SUNSET A ... 208
SUNSET B ... 208
SUNSET C ... 208
SUNSET LED D ... 210
SUNSET NATURAL A ... 209
SUNSET NATURAL B ... 209
SUNSET NATURAL C ... 209
SYMMETRY LED ... 515

T

TAHOE II ... 575
TAHOE SENSOR ... 575
TAY ... 572
TECHNO ... 284, 285
TEPIC LED ... 516
TESSA LED ... 508
THIKA LED ... 517
THIKA LED B ... 517
TORCH ... 478
TRIANGLES LED ... 536
TUBE ... 299
TUBE LED T8, 11W ... 586
TUBE LED T8, 16W ... 586
TUBE LED T8, 22W ... 586
TUBINGS ... 523
TUBINGS M ... 523
TUBINGS S ... 523
TURDA ... 176, 177, 178
TUTOIA ... 171
TWIG ... 281
TYBR ... 573

U

UNIT LED ... 547
UNO L ... 342
UNO M ... 342
UNO S ... 342
UT-LVM 48V, 100W INSIDE POWER SUPPLY ... 397
UT-LVM 48V, 200W INSIDE POWER SUPPLY ... 397
UT-LVM END CAP ... 397
UT-LVM FOCUS LED 12W ... 383
UT-LVM FOCUS LED 18W ... 382
UT-LVM FOCUS OUT LED 12W ... 386
UT-LVM FOCUS OUT LED 6W ... 387
UT-LVM FOCUS SWING LED 12W ... 388
UT-LVM FOCUS SWING LED 6W ... 389
UT-LVM L CONNECTOR ... 397
UT-LVM LINE LED 12W ... 385
UT-LVM LINE LED 18W ... 384
UT-LVM OUTSIE POWER SUPPLY CONDUCTIVE MODULE ... 397
UT-LVM ROLLER LED 10W ... 393
UT-LVM SPOT LED 12W ... 392
UT-LVM SPOT LED 5W ... 390
UT-LVM SPOT LED 9W ... 391
UT-LVM STRAIGHT CONNECTOR ... 397
UT-LVM TRACK 1M ... 395
UT-LVM TRACK 2M ... 395
UT-LVM VERTICAL CONNECTOR ... 397

V

VAN GOGH LED L ... 54
VAN GOGH LED M ... 54
VAN GOGH LED S ... 54
VERTIC LED ... 35
VETRO ... 146, 147
VIOLET ... 187
VIPER ... 188
VIS ... 341
VISTA ... 476
VIVIANE ... 186

W

WATERPROOF „Y" CONNECTOR IP68 ... 587
WATERPROOF CONNECTOR IP68 ... 587
WAVE S ... 242
WHEEL ... 214
WHEEL LUX ... 214, 215
WORKSHOP ... 278
WORKSHOP A ... 278
WORKSHOP B ... 278
WORKSHOP C ... 278

Z

ZENITH L ... 253, 254
ZENITH M ... 253, 254
ZENITH S ... 252, 254
ZENITH XS ... 252
ZOLA LED ... 507
ZURI LED ... 519

INDEX	STRONA PAGE СТРАНИЦА
203	296
205	296
206	296
3394	527
3401	566
3402	542
3403	542
3404	542
3408	547
3411	546
3412	564
4171	223
4174	223
4387	546
4418	526
4420	526
4422	544
4423	524
4424	524
4425	543
4443	549
4446	522
4448	513
4453	564
4454	569
4686	573
4687	573
4692	572
4694	572
4698	526
4906	522
4907	564
4961	190
4963	191
5067	288
5255	101
5292	572
5294	572
5397	96
5455	96
5463	101
5471	101
5654	102
6000	339
6014	104
6015	104
6016	104
6017	105
6018	104
6020	104
6021	104
6022	105
6336	278
6337	278
6345	301
6350	301
6367	290
6368	290
6390	186
6391	186
6403	279
6404	279
6442	289
6443	289
6444	289
6481	97
6487	107
6488	107
6490	107
6491	108
6492	109
6493	106
6501	107
6502	107
6503	107
6504	108
6505	109
6506	106
6512	188
6513	188
6525	339
6526	339
6528	339
6530	339
6532	186
6605	278
6607	105
6611	105
6640	188
6641	188
6768	242
6772	186
6773	186
6774	186
6775	537
6776	549
6785	280
6788	280
6792	280
6836	101
6837	101
6838	101
6840	96
6841	96
6842	102
6907	565
6908	565
6911	573

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
6913	299
6948	472
6950	472
6951	472
6976	498
6977	498
6978	498
7017	524
7487	585
7500	586
7501	586
7502	586
7503	580
7504	580
7520	229
7522	229
7524	304
7525	303
7526	304
7527	304
7528	302
7530	304
7531	304
7533	304
7534	302
7535	303
7536	304
7537	303
7538	304
7540	304
7541	302
7542	304
7544	304
7546	304
7547	303
7548	302
7551	300
7552	300
7553	300
7556	300
7557	300
7558	300
7560	301
7561	301
7562	301
7566	301
7567	301
7568	301
7581	454
7582	454
7583	454
7584	454
7585	454
7594	301
7595	301
7596	301
7597	300
7598	300
7600	300
7601	301
7603	339
7605	123
7606	123
7607	123
7614	133
7616	132
7618	450
7620	450
7621	450
7622	450
7623	451
7624	451
7625	451
7626	451
7627	132
7630	133
7633	133
7634	272
7635	272
7636	272
7637	272
7638	272
7640	272
7641	146
7642	146
7644	218
7645	218
7646	215
7647	211
7651	211
7652	210
7653	208
7654	208
7655	208
7657	450
7661	450
7663	486
7664	486
7665	338
7666	338
7667	61
7668	61
7671	88
7672	88
7674	88
7675	88
7683	90
7688	90

INDEX	STRONA PAGE
7694	86
7695	87
7696	86
7697	87
7698	86
7700	87
7701	86
7702	87
7703	95
7704	95
7705	94
7706	95
7707	95
7708	94
7710	95
7711	95
7712	94
7713	95
7714	95
7715	94
7716	95
7717	95
7718	94
7720	86
7721	87
7722	86
7723	87
7725	88
7726	88
7728	88
7730	88
7750	86
7751	87
7752	86
7753	87
7754	86
7755	87
7762	276
7763	82
7764	89
7766	82
7767	83
7768	83
7770	86
7771	82
7772	89
7774	82
7775	83
7776	83
7777	86
7778	82
7780	89
7782	82
7783	83
7784	83
7785	86
7786	89
7787	89
7788	125
7790	322
7791	322
7792	322
7793	322
7794	127
7797	126
7798	126
7800	126
7801	265
7802	264
7803	264
7804	265
7805	264
7806	264
7807	82
7808	89
7810	82
7811	83
7812	83
7813	86
7814	111
7817	111
7822	110
7825	110
7827	90
7828	90
7830	91
7831	91
7832	91
7833	90
7834	90
7835	91
7836	91
7837	91
7838	82
7840	89
7841	82
7842	83
7843	83
7844	86
7846	124
7847	124
7848	124
7850	124
7851	99
7852	99
7855	99
7856	99
7858	335

INDEX	STRONA PAGE
7860	335
7862	97
7863	97
7864	100
7865	100
7867	100
7868	100
7871	577
7872	577
7873	577
7926	294
7927	294
7931	276
7932	276
7938	264
7941	263
7942	263
7943	264
7945	263
7946	263
7950	189
7951	189
7952	317
7958	187
7960	187
7961	187
7972	574
7976	574
7978	574
7988	180
7991	181
7993	102
7994	102
7995	102
7996	254
7997	254
7998	254
8001	254
8002	254
8003	254
8005	254
8006	254
8007	254
8010	259
8011	259
8012	259
8013	259
8014	259
8015	259
8016	259
8017	259
8018	259
8020	259
8021	259
8022	259
8023	259
8024	259
8030	261
8032	261
8047	67
8048	67
8050	476
8051	476
8052	473
8054	475
8055	475
8056	473
8057	473
8072	102
8073	102
8074	102
8084	439
8085	439
8086	338
8087	338
8088	338
8091	338
8092	338
8093	338
8100	260
8102	260
8103	260
8105	260
8106	550
8107	550
8115	53
8116	52
8117	52
8118	471
8120	471
8121	470
8122	470
8123	478
8124	474
8126	466
8127	488
8128	488
8130	488
8131	489
8132	474
8140	536
8141	536
8142	536
8143	536
8145	514
8146	514
8147	563
8148	563

INDEX	STRONA PAGE
8154	134
8155	134
8156	135
8157	135
8158	523
8160	523
8161	523
8162	569
8163	569
8164	562
8165	562
8168	297
8170	297
8171	305
8172	305
8173	477
8174	477
8175	489
8176	515
8177	550
8178	550
8180	515
8182	536
8190	180
8191	181
8192	260
8194	260
8195	334
8196	334
8197	198
8201	198
8202	335
8203	335
8213	198
8216	198
8221	334
8222	334
8223	334
8224	334
8225	334
8227	438
8228	438
8230	442
8231	442
8232	438
8233	438
8234	442
8235	442
8236	439
8237	439
8238	443
8240	443
8241	439
8242	439
8243	439
8244	439
8245	443
8246	443
8247	443
8248	443
8250	306
8250	307
8262	267
8263	267
8264	266
8265	266
8266	266
8267	267
8268	267
8270	266
8281	435
8282	435
8283	437
8284	437
8288	306
8288	307
8290	306
8291	306
8302	298
8303	298
8304	298
8305	298
8306	443
8308	67
8330	543
8331	543
8347	581
8348	581
8351	65
8352	65
8355	65
8358	319
8360	455
8361	455
8362	481
8363	481
8364	480
8365	480
8366	484
8367	484
8368	484
8370	484
8371	485
8372	485
8373	482
8374	482
8375	485
8376	485

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
8377	582
8378	582
8381	143
8382	459
8383	459
8384	463
8385	463
8397	555
8398	555
8430	214
8431	63
8432	63
8433	63
8434	63
8435	63
8436	63
8447	580
8671	126
8672	126
8673	126
8676	443
8677	443
8678	443
8680	443
8681	443
8682	443
8683	442
8684	442
8685	442
8686	442
8687	443
8688	443
8690	442
8691	442
8692	440
8693	440
8694	440
8695	440
8696	437
8697	437
8698	439
8700	439
8701	439
8702	439
8703	439
8704	439
8705	438
8706	438
8707	438
8708	438
8710	439
8711	439
8712	438
8713	438
8714	436
8715	436
8716	436
8717	436
8720	348
8722	348
8724	333
8727	333
8731	333
8732	333
8738	332
8740	332
8741	332
8742	332
8743	332
8747	430
8752	429
8756	428
8757	428
8762	427
8763	426
8764	426
8765	426
8766	426
8767	349
8772	349
8773	349
8774	346
8775	346
8776	346
8777	346
8778	346
8780	346
8781	346
8782	346
8794	145
8795	528
8796	63
8797	63
8798	63
8800	96
8802	177
8805	463
8816	104
8817	104
8818	104
8819	105
8820	105
8821	587
8823	453
8824	455
8825	455
8826	353
8834	463

INDEX	STRONA PAGE
8835	463
8836	463
8837	463
8845	587
8846	587
8851	243
8858	242
8864	243
8895	336
8896	336
8898	336
8900	336
8901	336
8911	101
8912	101
8913	101
8914	96
8915	98
8916	98
8917	98
8918	60
8920	60
8921	60
8922	60
8923	60
8924	60
8925	337
8926	337
8928	337
8930	337
8931	337
8932	337
8934	103
8935	103
8937	352
8938	352
8940	352
8942	182
8943	182
8944	182
8945	176
8946	178
8947	178
8950	177
8952	176
8953	178
8954	179
8955	177
8957	179
8958	176
8960	178
8962	179
8965	502
8966	502
8967	463
8968	463
8970	463
8971	463
8972	462
8973	462
8974	463
8975	463
8991	486
8992	486
8993	299
8994	299
8995	448
8996	448
8997	448
8998	448
9000	448
9001	448
9002	448
9003	448
9004	449
9005	449
9006	449
9007	449
9012	460
9013	460
9014	460
9015	460
9018	453
9021	295
9022	295
9023	295
9024	295
9025	295
9026	295
9028	214
9033	214
9045	282
9046	282
9047	282
9054	65
9056	142
9057	142
9058	142
9060	142
9067	103
9068	103
9070	103
9071	196
9072	196
9084	190
9091	190
9097	525
9100	566

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
9101	566
9102	565
9103	565
9104	568
9105	568
9106	568
9107	545
9108	545
9111	545
9112	539
9113	539
9118	517
9120	517
9122	547
9123	540
9124	540
9125	529
9126	286
9131	147
9132	147
9138	281
9140	281
9142	285
9145	284
9150	287
9151	287
9152	143
9153	143
9154	143
9155	143
9158	525
9173	580
9177	582
9178	581
9180	581
9185	518
9186	459
9187	459
9188	459
9190	459
9192	112
9197	580
9211	583
9212	583
9213	583
9214	583
9237	457
9238	457
9240	323
9241	323
9244	452
9245	452
9252	529
9261	227
9263	226
9264	226
9266	227
9316	323
9317	299
9320	299
9321	454
9322	454
9324	452
9325	452
9337	453
9338	453
9342	583
9343	583
9344	583
9345	583
9362	144
9363	144
9364	145
9377	228
9378	353
9381	283
9382	283
9383	323
9384	322
9385	322
9387	322
9403	350
9404	350
9407	350
9408	350
9412	350
9413	350
9416	350
9417	350
9420	529
9426	503
9448	456
9450	456
9451	456
9452	456
9453	459
9454	459
9455	459
9456	459
9457	459
9458	459
9460	457
9461	457
9462	458
9463	458
9482	339
9486	339
9490	317

INDEX	STRONA PAGE
9491	317
9501	477
9505	475
9507	516
9508	516
9513	556
9514	556
9516	541
9517	541
9518	541
9551	540
9554	569
9555	521
9557	521
9561	520
9562	520
9563	520
9564	545
9565	545
9570	351
9571	351
9574	351
9575	351
9605	184
9606	184
9607	499
9672	183
9673	183
9675	112
9677	112
9680	112
9682	185
9687	185
9700	228
9705	269
9706	269
9707	269
9708	269
9710	269
9711	500
9712	500
9713	500
9714	498
9715	499
9736	197
9737	197
9743	280
9744	280
9751	499
9890	284
10035	575
10037	575
10038	575
10040	575
10042	329
10043	329
10045	329
10046	329
10047	325
10048	324
10050	324
10051	325
10052	324
10053	324
10054	325
10055	324
10056	324
10057	325
10058	324
10060	324
10062	326
10063	326
10064	326
10065	326
10067	330
10068	330
10070	330
10071	330
10105	503
10142	407
10143	405
10144	401
10145	403
10146	408
10147	406
10148	404
10150	400
10151	402
10152	410
10153	410
10154	411
10155	411
10156	420
10157	420
10158	423
10160	423
10161	418
10161	422
10162	416
10163	416
10164	419
10165	419
10166	419
10166	422
10167	419
10167	422
10168	419
10168	422

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
10170	417
10171	419
10171	422
10175	316
10176	316
10177	316
10184	316
10185	316
10186	316
10208	306
10210	306
10212	306
10213	307
10214	307
10225	458
10226	458
10227	462
10228	462
10230	581
10231	581
10235	435
10236	435
10237	435
10238	435
10239	435
10276	271
10277	271
10278	271
10280	216
10281	216
10282	216
10283	528
10284	54
10285	54
10286	54
10287	54
10288	54
10289	54
10290	54
10291	54
10292	54
10296	291
10299	122
10300	122
10301	122
10302	121
10303	116
10304	116
10305	116
10306	121
10307	121
10308	121
10310	121
10311	42
10312	44
10313	42
10314	45
10315	273
10316	273
10317	273
10347	273
10348	273
10350	273
10351	273
10352	273
10353	273
10354	113
10355	113
10356	219
10358	454
10362	35
10363	40
10364	41
10365	41
10366	48
10367	48
10368	51
10370	51
10371	51
10372	446
10373	446
10374	447
10375	447
10376	446
10377	446
10378	447
10380	447
10381	446
10382	446
10383	447
10384	447
10385	446
10386	446
10387	447
10388	447
10390	432
10391	432
10393	432
10394	432
10395	433
10396	432
10397	432
10398	433
10399	432
10400	432
10401	433
10402	313
10403	313

INDEX	STRONA PAGE
10404	313
10406	313
10407	313
10408	313
10410	313
10411	313
10412	313
10413	313
10415	313
10416	313
10417	313
10418	313
10420	314
10421	314
10422	314
10423	314
10424	314
10426	314
10427	314
10428	314
10430	314
10431	314
10432	314
10444	62
10445	62
10446	62
10447	62
10448	62
10450	62
10451	62
10452	62
10453	62
10455	269
10456	269
10457	269
10460	92
10463	92
10465	92
10468	92
10476	340
10477	340
10478	340
10480	340
10481	481
10482	481
10483	481
10484	481
10485	341
10486	341
10487	341
10488	341
10489	340
10490	340
10491	341
10492	341
10493	340
10494	340
10495	571
10496	571
10497	571
10498	571
10499	570
10500	570
10501	570
10502	570
10503	538
10504	538
10525	466
10526	467
10527	467
10535	344
10536	344
10537	344
10538	344
10540	344
10541	344
10542	344
10543	344
10544	344
10545	344
10546	345
10547	345
10548	345
10550	345
10551	345
10552	345
10553	345
10554	345
10555	345
10556	345
10557	345
10558	345
10562	67
10563	67
10564	67
10570	222
10571	222
10572	222
10573	222
10574	222
10575	222
10576	209
10577	209
10578	209
10579	496
10580	496
10581	496
10587	585
10588	585
10589	585
10593	584
10594	584
10595	584
10596	584
10597	417
10618	291
10620	51
10621	51
10622	51
10623	121
10633	528
10637	265
10638	265
10643	400
10644	401
10645	402
10646	403
10647	410
10648	410
10650	404
10651	405
10652	408
10653	411
10654	411
10655	406
10656	407
10665	491
10666	491
10667	491
10668	491
10670	491
10671	491
10672	491
10673	491
10674	491
10676	491
10677	491
10678	491
10680	491
10681	491
10682	491
10683	491
10684	491
10685	491
10686	544
10687	544
10688	544
10695	293
10696	293
10700	293
10701	293
10702	292
10703	292
10704	60
10705	60
10711	487
10712	487
10713	478
10714	478
10715	478
10716	478
10717	480
10718	480
10719	480
10720	480
10723	469
10724	469
10725	469
10726	469
10727	469
10728	469
10729	479
10730	479
10734	72
10735	72
10737	76
10739	76
10741	77
10743	77
10746	74
10747	74
10748	74
10752	74
10753	74
10754	74
10758	75
10759	75
10760	75
10764	73
10765	73
10766	73
10770	73
10771	73
10772	73
10776	81
10777	81
10778	81
10779	81
10780	81
10781	81
10782	81
10783	81
10784	81
10785	81
10786	81
10788	343

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
10789	343
10790	343
10791	343
10792	343
10793	343
10794	343
10795	93
10796	93
10797	93
10798	93
10799	93
10800	93
10801	93
10802	93
10803	93
10804	93
10805	93
10806	93
10807	93
10808	29
10810	32
10811	32
10812	24
10813	24
10814	25
10815	29
10816	27
10817	26
10820	72
10821	72
10822	72
10823	72
10824	72
10825	72
10840	342
10841	342
10842	342
10843	342
10844	342
10845	342
10847	40
10848	41
10850	41
10851	42
10852	42
10853	44
10854	45
10855	48
10856	48
10857	35
10858	29
10860	32
10861	32
10862	24
10863	24
10864	25
10865	29
10866	27
10867	26
10872	253
10873	253
10878	253
10879	253
10880	252
10881	252
10882	72
10883	72
10884	72
10885	72
10886	72
10887	72
10888	74
10889	74
10890	74
10891	74
10892	75
10893	75
10894	72
10895	72
10896	72
10897	72
10898	72
10899	72
10900	73
10901	73
10902	73
10903	73
10905	261
10906	261
10907	64
10910	64
10913	64
10915	64
10928	29
10930	29
10933	580
10934	117
10971	492
10972	492
10973	492
10974	492
10975	492
10976	492
10977	492
10978	492
10979	492
10980	492
10981	492

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
10982	492
10983	493
10984	493
10985	493
10986	493
10987	493
10988	493
10989	493
10990	493
10991	493
10992	493
10993	493
10994	493
10995	581
10996	581
10997	581
10998	581
11150	235
11151	235
11152	235
11153	230
11154	230
11155	230
11156	236
11157	236
11158	237
11160	231
11161	231
11162	231
11163	234
11164	234
11165	234
11166	234
11167	234
11168	234
11170	232
11171	232
11172	232
11173	205
11174	205
11175	202
11176	202
11177	203
11178	212
11180	203
11200	310
11201	310
11202	310
11203	310
11204	310
11205	310
11206	310
11207	310
11208	310
11210	310
11211	310
11212	310
11225	258
11226	258
11227	258
11228	258
11230	258
11231	258
11232	258
11233	258
11242	240
11243	240
11244	241
11245	241
11251	241
11252	241
11278	588
11287	588
11288	212
11290	212
11291	212
11292	212
11295	434
11296	434
11297	452
11298	455
11301	588
11305	383
11306	382
11307	385
11308	384
11310	389
11311	388
11312	387
11313	386
11314	390
11315	391
11316	392
11317	393
11318	395
11320	395
11321	397
11322	397
11325	397
11326	397
11327	397
11328	397
11330	397
11331	383
11332	382
11333	385
11334	384
11335	389

INDEX	STRONA PAGE
11336	388
11337	387
11338	386
11340	390
11341	391
11342	392
11343	393
11346	548
11347	548
11348	341
11350	341
11357	308
11358	308
11360	558
11361	558
11362	558
11363	537
11364	537
11365	537
11366	537
11367	557
11368	530
11370	530
11371	511
11372	511
11373	511
11374	510
11375	510
11376	512
11377	560
11378	44
11380	44
11381	45
11382	45
11395	233
11396	233
11397	233
11398	26
11400	41
11401	32
11402	29
11403	24
11408	120
11410	246
11411	246
11412	246
11413	246
11414	246
11425	46
11426	46
11427	589
11431	49
11432	210
11433	76
11434	76
11435	77
11436	77
11437	76
11438	76
11440	77
11441	77
11442	76
11443	76
11444	76
11445	70
11446	71
11447	70
11448	71
11450	70
11451	71
11452	252
11453	252
11454	252
11455	252
11456	252
11460	58
11461	58
11462	59
11463	59
11464	59
11465	59
11466	76
11467	76
11468	77
11470	77
11471	70
11472	71
11473	76
11482	253
11483	253
11484	253
11485	253
11486	253
11487	253
11488	252
11490	252
11491	252
11492	252
11493	252
11494	241
11495	241
11496	240
11510	248
11511	248
11512	248
11513	248
11520	199
11521	199

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
11525	582
11528	561
11530	561
11531	552
11532	552
11533	552
11534	552
11535	552
11536	554
11537	554
11538	509
11540	513
11541	508
11542	508
11543	567
11544	507
11545	507
11546	507
11547	519
11548	531
11550	531
11551	531
11552	531
11553	532
11554	532
11555	533
11556	533
11557	533
11558	533
11560	533
11561	533
11562	535
11563	535
11564	535
11565	535
11566	535
11567	535
11568	535
11570	535
11571	535
11572	535
11573	535
11574	535
11578	46
11580	46
11581	41
11582	41
11583	40
11584	40
11585	51
11586	51
11587	51
11588	45
11590	45
11591	44
11592	44
11601	29
11602	26
11603	29
11604	24
11605	32
11606	35
11607	35
11616	418
11616	422
11617	419
11618	419
11620	419
11621	419
11621	422
11622	423
11623	423
11624	420
11625	420
11626	416
11627	416
11628	419
11628	422
11630	400
11631	400
11632	401
11633	401
11634	403
11635	403
11636	404
11637	404
11638	405
11639	405
11640	408
11641	408
11642	406
11643	406
11644	407
11645	407
11646	25
11647	25
11648	26
11649	26
11650	150
11651	150
11652	151
11653	151
11654	152
11655	152
11656	153
11657	154
11658	154

INDEX	STRONA PAGE
11659	155
11660	155
11661	156
11662	156
11663	157
11664	160
11665	160
11666	160
11667	163
11668	162
11669	162
11670	161
11671	161
11672	161
11673	166
11674	166
11675	166
11676	169
11677	168
11678	168
11679	167
11680	167
11681	167
11682	171
11683	171
11684	171
11699	139
11700	139
11701	138
11702	138
11703	139
11704	138
11705	130
11706	130
11707	131
11708	131
11712	366
11713	368
11714	368
11715	369
11716	369
11717	364
11718	361
11720	360
11721	362
11722	367
11723	365
11724	372
11725	372
11726	375
11726	379
11727	375
11728	375
11730	376
11731	376
11732	378
11733	378
11734	375
11734	378
11735	375
11735	378
11736	375
11736	378
11737	372
11738	373
11740	373
11743	363
11744	373
11746	141
11747	141
11748	141
11750	141
11763	74
11764	74
11765	74
11766	74
11778	194
11780	193
11781	192
11782	194
11783	194
11784	193
11785	192
11786	194
11787	193
11788	192
11790	194
11791	194
11792	193
11793	192
11794	589
11795	589
11796	589
11797	589
11798	589
11800	589
11801	589
11802	589
11803	417
11804	547
11805	547
11812	66
11813	66
11814	66
11815	66
11874	588
11875	588
11876	275

INDEKS LAMP / PROGRESSIVE CODE INDEX

INDEX	STRONA PAGE
11877	275
11878	275
11879	34
11882	275
11883	275
11884	275
11885	34
11886	37
11887	37
11888	37
11893	375
11894	375
11894	379

Nowodvorski LIGHTING

Nowodvorski
LIGHTING

Nowodvorski Lighting sp. z o.o.
ul. Bojemskiego 11
42-202 Czestochowa
POLAND

+48 34 344 91 10 / 11
nowodvorski@nowodvorski.com
www.nowodvorski.com



www.nowodvorski.com